ELMARK HOLDING SE

CATALOGUE Q4 2021

7 YEARS WARRANTY

ELMARK®

The Brand of Electricity

DUNCAN
TABLE & FLOOR LAMPS
PAGE 749

DIMMABLE TABLE LAMP
TABLE & FLOOR LAMPS
PAGE 751

ELINOR
TABLE & FLOOR LAMPS
PAGE 752

LUKE
TABLE & FLOOR LAMPS
PAGE 753

MICKEY BLUE
SPOTLIGHTS
PAGE 757

MICKEY WHITE
SPOTLIGHTS
PAGE 759

JIM
SPOTLIGHTS
PAGE 771

PICASSO
SPOTLIGHTS
PAGE 775

INDOOR LIGHTING

TETRAGON IP20
LED PANELS
PAGE 777

TETRAGON IP44
LED PANELS
PAGE 778

LED PANEL ROUND IP20
LED PANELS
PAGE 782

LED PANEL ROUND IP44
LED PANELS
PAGE 786

SUPER SLIM WITH CLIPS
LED PANELS
PAGE 789

LED PANEL ROUND OM
LED PANELS
PAGE 790

COLOUR TEMP. ADJUSTABLE
LED PANELS
PAGE 793

INDIRECT DOWNLIGHTS
LED PANELS
PAGE 794

LED PANEL SQUARE
LED PANELS
PAGE 795

LED PANEL SQUARE OM
LED PANELS
PAGE 796

GLASS PANEL ROUND
LED PANELS
PAGE 798

RECESSED FIXTURE
LED FIXTURE
PAGE 800

IVOR
LED PANELS
PAGE 801

LUCE
LED FIXTURE
PAGE 803

MALIA
LED FIXTURE
PAGE 807

DONUT
LED FIXTURE
PAGE 808

TRACY SUPER SLIM
LED FIXTURE
PAGE 810

LED WALL LIGHT IP65
LED FIXTURE
PAGE 815

SENSOR CABINET LAMP
LED FIXTURE
PAGE 816

ELR627
DOWNLIGHT
PAGE 819

SA-045
DOWNLIGHT
PAGE 825

GYPSUM DOWNLIGHTS
DOWNLIGHT
PAGE 828

SA-71
DOWNLIGHT
PAGE 831

RECESSED ROUND
DOWNLIGHT
PAGE 839

DEEP RECESSED IP44
DOWNLIGHT
PAGE 844

SKY TLR
DOWNLIGHT
PAGE 851

DL-044 SQUARE
DOWNLIGHT
PAGE 853

FLCOM COB
DOWNLIGHT
PAGE 855

FRANCA 90
DOWNLIGHT
PAGE 857

FOUR POLES MAGNETIC
TRACK LIGHTING
PAGE 861

FOUR POLES MAGNETIC
TRACK LIGHTING
PAGE 863

FOUR POLES 48V TRACK
TRACK LIGHTING
PAGE 864

2/4 LINES SKY B60
TRACK LIGHTING
PAGE 869

2/4 LINES TL2044
TRACK LIGHTING
PAGE 874

2/4 LINES SKY TFL
TRACK LIGHTING
PAGE 876

SKY FIXTURES TLBM
TRACK LIGHTING
PAGE 881

TRITON
LUMINAIRES
PAGE 886

LED MOD FIXTURE
LUMINAIRES
PAGE 888

ACOUSTIC HIGH POWER LED
LUMINAIRES
PAGE 891

ACOUSTIC LED RINGS
LUMINAIRES
PAGE 892

LED RINGS
LUMINAIRES
PAGE 893

LED PROFILES S48
LUMINAIRES
PAGE 894

RAINBOW LED SMD
LUMINAIRES
PAGE 901

LENA-V BM/
LUMINAIRES
PAGE 906

XL101
EMERGENCY LIGHTS
PAGE 918

XL3114
EMERGENCY LIGHTS
PAGE 920

EMERGENCY DRIVER
EMERGENCY LIGHTS
PAGE 921

TRITON
BATHROOM
PAGE 934

DORIA
BATHROOM
PAGE 937

LED PANEL ROUND IP44
BATHROOM
PAGE 939

WATERPROOF LED PANEL
BATHROOM
PAGE 941

ELR627
BATHROOM
PAGE 943

OUTDOOR LIGHTING

JOSH
GARDEN
PAGE 947

ERIK
GARDEN
PAGE 950

LED PANEL STELLAR IP40
99XPANEL020W
99XPANEL020CW



LED PANEL STELLAR IP40
99XPANEL021W

LED | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP40**

LED PANELS STELLAR

Catalogue number	Catalogue number with Emergency kit	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
99XPANEL020W	**99XPANEL020WE**	C	48	4320	4000	white	595	595	30	1/6	A++→A
99XPANEL020CW	**99XPANEL020CWE**	C	48	4320	6400	white	595	595	30	1/6	A++→A
99XPANEL021W	**99XPANEL021WE**	C	48	4320	4000	white	295	1195	30	1/6	A++→A

Emergency kit with a possibility for work in an emergency regime more than two hours.

Frame for LED panel with dimensions 595/595/30mm for surface mounting.
Catalogue number:
92FRAME020W

Frame for LED panel with dimensions 295/1195/30mm for surface mounting.
Catalogue number:
92FRAME021W

*Suitable for surface and ceiling mounting. | **Body:** Iron+PS | 1YEAR WARRANTY
Suitable for mountig in suspended celling Armstrong type (in grid cellings)
Body: aluminium | **Light source:** SMD 4014 | **Starting time:** < 0.5s | **Power factor:** 0.9 | Recessed mounted luminaire | **Until Supply Last

~230V | 50/60 Hz | SMD | 120° | Ra≥80 | >10000 | INSTANT 100% | 15000h | Hg | IP 40 | RoHS COMPLIANT | EMC | F | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LED PANEL 110LM/W

NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP40** | **UGR<19**

LED PANEL

Catalogue number	Catalogue number with Emergency kit	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
92PANEL028W	**92PANEL028WE**	C	48	5280	4000	595	595	30	1/5	A++→A
92PANEL028CW	**92PANEL028CWE**	C	48	5280	6400	595	595	30	1/5	A++→A
92PANEL029W	**92PANEL029WE**	C	48	5280	4000	1195	295	30	1/5	A++→A
92PANEL029CW	**92PANEL029CWE**	C	48	5280	6400	1195	295	30	1/5	A++→A

INSTALLATION ACCESSORIES FOR LED PANELS
Suspension wire for suspended mounting
Catalogue number: **99ACC18**

Emergency kit with a possibility for work in an emergency regime more than two hours.

Panel frame 595/595 mm ceiling mounting white
Catalogue number: **92FRAME020W**

Panel frame 295/1195 mm ceiling mounting white
Catalogue number: **92FRAME021W**

Suitable for mounting in suspended ceiling Armstrong type (in grid ceilings).
Body: iron + PS | **Light source:** SMD2835 | **Driver:** Isolated | **Starting time:** <0.5s | **Power factor:** λ>0.9

~230V | 50/60 Hz | SMD | 120° | Ra≥80 | >15000 | INSTANT 100% | 30000h | Hg | RoHS COMPLIANT | EMC | F | CE | 4+1 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LED PANEL IP44 110LM/W

NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP44** | **UGR<19**

LED PANEL IP44

Catalogue number	Catalogue number with Emergency kit	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
92PANEL028W44	**92PANEL028W44E**	C	48	5280	4000	595	595	30	1/5	A++→A
92PANEL028CW44	**92PANEL028CW44E**	C	48	5280	6400	595	595	30	1/5	A++→A
92PANEL029W44	**92PANEL029W44E**	C	48	5280	4000	1195	295	30	1/5	A++→A
92PANEL029CW44	**92PANEL029CW44E**	C	48	5280	6400	1195	295	30	1/5	A++→A

INSTALLATION ACCESSORIES FOR LED PANELS
Suspension wire for suspended mounting
Catalogue number: **99ACC18**

Emergency kit with a possibility for work in an emergency regime more than two hours.

Suitable for mounting in suspended ceiling Armstrong type (in grid ceilings).
Body: iron + PS | **Light source:** SMD2835 | **Driver:** Isolated | **Starting time:** <0.5s | **Power factor:** λ>0.9

~230V | 50/60 Hz | SMD | 120° | Ra≥80 | >15000 | INSTANT 100% | 30000h | Hg | IP 44 | RoHS COMPLIANT | EMC | 4+1 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LED THIN PANEL WITH CLIPS FOR MOUNTING IN DRYWALL

LED PANEL
WHITE FRAME COLOUR

LED | NEUTRAL WHITE 4000K | COOL WHITE 6400K | IP40 | DIMMABLE

LED PANEL

Catalogue number	Catalogue number with Emergency kit	Product category	Additional function	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/ Box (pcs)	Energy class
92PANEL012W	**92PANEL012WE**	F	-	24*	2400	4000	white	295	295	11	1/12	A++→A
92PANEL013W	**92PANEL013WE**	C	-	36	3600	4000	white	595	295	11	1/6	A++→A
92PANEL018W	**92PANEL018WE**	C	Dimmable	45	4500	4000	white	595	595	9	1/5	A++→A
92PANEL018	-	F	Dimmable	45*	4500	4000	aluminium	595	595	9	1/5	A++→A
92PANEL020W	**92PANEL020WE**	C	-	48	4800	4000	white	595	595	30	1/6	A++→A
92PANEL020CW	**92PANEL020CWE**	C	-	48	4800	6400	white	595	595	30	1/6	A++→A
92PANEL021W	**92PANEL021WE**	C	-	48	4800	4000	white	1195	295	30	1/6	A++→A
92PANEL030W	**92PANEL030WE**	C	With clips	48	4800	4000	white	595	595	9	1/6	A++→A
92PANEL030CW	**92PANEL030CWE**	C	With clips	48	4800	6400	white	595	595	9	1/6	A++→A
92PANEL031W	-	C	High power	60	6000	4000	white	595	595	30	1/5	A++→A
92PANEL031CW	-	C	High power	60	6000	6400	white	595	595	30	1/5	A++→A

INSTALLATION ACCESSORIES FOR LED PANELS
Suspension wire for suspended mounting
Catalogue number: **99ACC18**
Clips for mounting on plasterboard
Catalogue number: **99ACC21**
Fasteners for surface mounting
Catalogue number: **99ACC22**



Panel frame for 595/595 mm ceiling mounting white
Catalogue number: **92FRAME020W**

Panel frame for 295/1195 mm ceiling mounting white
Catalogue number: **92FRAME021W**

Frame for LED panel with dimensions 595/595/9mm and 595/595/11mm for surface mounting.
Catalogue number: **92FRAME014W**

Suitable for mounting in suspended ceiling Armstrong type (in grid ceilings). 99ACC21 and 99ACC22 are suitable only for LED panels with height 9-11mm
Body: aluminium | **Light source:** Epistar SMD4014 | **Starting time:** <0.5s | **Power factor:** λ>0.9 | *Until Supply Last | LED panels can be dimmed using a suitable dimmable driver and remote control.

~230V | 50/60 Hz | SMD | 120° | Ra≥80 | >15000 | INSTANT 100% | 30000h | Hg | IP 40 | RoHS COMPLIANT | EMC | F | CE | 4+1 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

HIGH POWER LED PANEL 60W IP44
WHITE FRAME COLOUR

LED PANEL IP44
WHITE FRAME COLOUR

LED | NEUTRAL WHITE 4000K | COOL WHITE 6400K | IP44 | DIMMABLE

LED PANEL IP44

Catalogue number	Catalogue number with Emergency kit	Product category	Additional function	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/ Box (pcs)	Energy class
92PANEL013WIP44	**92PANEL013WIP44E**	C	-	36	3600	4000	white	595	295	11	1/6	A++→A
92PANEL020WIP44	**92PANEL020WIP44E**	C	-	48	4800	4000	white	595	595	30	1/6	A++→A
92PANEL020CWIP44	**92PANEL020CWIP44E**	C	-	48	4800	6400	white	595	595	30	1/6	A++→A
92PANEL018WIP44	**92PANEL018WIP44E**	C	Dimmable	45	4500	4000	white	595	595	9	1/5	A++→A
92PANEL021WIP44	**92PANEL021WIP44E**	C	-	48	4800	4000	white	1195	295	30	1/6	A++→A
92PANEL031WIP44	-	C	-	60	6000	4000	white	595	595	30	1/5	A++→A
92PANEL031CWIP44	-	C	-	60	6000	6400	white	595	595	30	1/5	A++→A

INSTALLATION ACCESSORIES FOR LED PANELS
Suspension wire for suspended mounting
Catalogue number: **99ACC18**
Clips for mounting on plasterboard
Catalogue number: **99ACC21**
Fasteners for surface mounting
Catalogue number: **99ACC22**

Emergency kit with a possibility for work in an emergency regime more than two hours.

Suitable for mounting in suspended ceiling Armstrong type (in grid ceilings). 99ACC21 and 99ACC22 are suitable only for LED panels with height 9-11mm
Body: aluminium | **Light source:** Epistar SMD4014 | **Starting time:** <0.5s | **Power factor:** λ>0.9
LED panels can be dimmed using a suitable dimmable driver and remote control.

~230V | 50/60 Hz | SMD | 120° | Ra≥80 | >15000 | INSTANT 100% | 30000h | Hg | IP 44 | RoHS COMPLIANT | EMC | F | CE | 4+1 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LED PANEL ROUND
99XLED621
99XLED620
99XLED620CW

LED PANEL ROUND
99XLED615
99XLED614
99XLED614CW

LED PANEL ROUND
99XLED612
99XLED611
99XLED611CW

LED PANEL ROUND
99XLED610
99XLED609
99XLED609CW

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP40**

LED PANELS ROUND STELLAR

Catalogue number	Catalogue number with Emergency kit	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Diameter1 (mm)	Packing/ Box (pcs)	Energy class
99XLED610	**99XLED610E**	C	6	330	2700	white	118	18	100	1/30	A++→A
99XLED609	**99XLED609E**	C	6	330	4000	white	118	18	100	1/30	A++→A
99XLED609CW	**99XLED609CWE**	C	6	330	6500	white	118	18	100	1/30	A++→A
99XLED612	**99XLED612E**	C	12	840	2700	white	167	18	150	1/24	A++→A
99XLED611	**99XLED611E**	C	12	840	4000	white	167	18	150	1/24	A++→A
99XLED611CW	**99XLED611CWE**	C	12	840	6500	white	167	18	150	1/24	A++→A
99XLED615	**99XLED615E**	C	18	1350	2700	white	225	18	205	1/20	A++→A
99XLED614	**99XLED614E**	C	18	1350	4000	white	225	18	205	1/20	A++→A
99XLED614CW	**99XLED614CWE**	C	18	1350	6500	white	225	18	205	1/20	A++→A
99XLED621	**99XLED621E**	C	24	1800	2700	white	295	18	268	1/24	A++→A
99XLED620	**99XLED620E**	C	24	1800	4000	white	295	18	268	1/24	A++→A
99XLED620CW	**99XLED620CWE**	C	24	1800	6500	white	295	18	268	1/20	A++→A

Emergency kit with a possibility for work in an emergency regime more than two hours.

Voltage: 185-240V | **Body:** aluminium | **Light source:** SMD 2835 | **Starting time:** < 0.5s | **Power factor:** 0.55 | Recessed mounted luminaire

~230V | 50/60 Hz | SMD | 120° | Ra≥80 | >10000 | INSTANT 100% | 15000h | Hg | RoHS COMPLIANT | EMC | F | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LED PANEL ROUND

LED PANEL ROUND
DIMMABLE

UNTIL SUPPLY LAST

LED PANEL ROUND

Catalogue number	Catalogue number with Emergency kit	Product category	Dimmable	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Diameter1 (mm)	Packing/ Box (pcs)	Energy class
99LED971	**99LED971E**	F		6	350	4000	white	118	17	103	1/50	A++→A
99LED971WW	**99LED971WWE**	F		6	350	2700	white	118	17	103	1/50	A++→A
99LED971CW	**99LED971CWE**	F		6	350	6400	white	118	17	103	1/50	A++→A
99LED972	**99LED972E**	F		12	890	4000	white	166	18	151	1/30	A++→A
99LED972WW	**99LED972WWE**	F		12	890	2700	white	166	18	151	1/30	A++→A
99LED972CW	**99LED972CWE**	F		12	890	6400	white	166	18	151	1/30	A++→A
99LED973	**99LED973E**	F		18	1420	4000	white	225	18	205	1/20	A++→A
99LED973WW	**99LED973WWE**	F		18	1420	2700	white	225	18	205	1/20	A++→A
99LED973CW	**99LED973CWE**	F		18	1420	6400	white	225	18	205	1/20	A++→A
99LED617D	**99LED617DE**	F	Yes	21	1680	4000	white	225	21	205	1/20	A++→A
99LED974	**99LED974E**	F		24	1900	4000	white	296	13	275	1/20	A++→A
99LED974WW	**99LED974WWE**	F		24	1900	2700	white	296	13	275	1/20	A++→A
99LED974CW	**99LED974CWE**	F		24	1900	6400	white	296	13	275	1/20	A++→A

Emergency kit with a possibility for work in an emergency regime more than two hours.

Voltage: 185-240V | **Body:** aluminium | **Reflector:** policarbonate (pc) | **Light source:** Epistar SMD2835 | **Starting time:** <0.5s | **Power factor:** λ>0.8

Easy installation due to handy clips | Recessed mounted luminaire.

3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LED PANEL ROUND

99LED621T
99LED620TCW
99LED618T

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP40**

UNTIL SUPPLY **LAST**

LED PANEL ROUND

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Diameter1 (mm)	Packing/Box (pcs)	Energy class
99LED618T	F	18	1440	2700-3000	white	225	24	207	1/20	A++→A
99LED621T	F	24	1920	2700-3000	white	297	24	277	1/20	A++→A
99LED620TCW	F	24	1920	6000-6400	white	297	24	277	1/20	A++→A

Body: aluminium | **Reflector:** policarbonate (pc) | **Light source:** Epistar SMD2835 | **Starting time:** <0.5s | **Power factor:** λ>0.8
Easy installation due to handy clips | Recessed mounted luminaire.

~230V | 50/60 Hz | SMD | 120° | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | IP 40 | RoHS COMPLIANT | EMC | F | CE | 3+0 standard +extended | 3 YEAR TOTAL WARRANTY

LED PANEL ECO

99LED962CW
99LED962
99LED962WW
99LED963CW
99LED963
99LED963WW
99LED964CW
99LED964
99LED964WW

LED PANEL ECO

99LED960CW
99LED960
99LED960WW
99LED961CW
99LED961
99LED961WW

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP40**

LED PANEL ROUND ECO SERIES

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Diameter1 (mm)	Packing/Box (pcs)	Energy class
99LED960CW	C	6	510	6000-6400	white	100	25	77	1/100	A++→A
99LED960	C	6	510	4000-4300	white	100	25	77	1/100	A++→A
99LED960WW	C	6	510	2700-3000	white	100	25	77	1/100	A++→A
99LED961CW	C	12	1020	6000-6400	white	141	25	117	1/60	A++→A
99LED961	C	12	1020	4000-4300	white	141	25	117	1/60	A++→A
99LED961WW	C	12	1020	2700-3000	white	141	25	117	1/60	A++→A
99LED962CW	C	18	1530	6000-6400	white	168	25	143	1/60	A++→A
99LED962	C	18	1530	4000-4300	white	168	25	143	1/60	A++→A
99LED962WW	C	18	1530	2700-3000	white	168	25	143	1/60	A++→A
99LED963CW	C	24	2040	6000-6400	white	200	25	168	1/30	A++→A
99LED963	C	24	2040	4000-4300	white	200	25	168	1/30	A++→A
99LED963WW	C	24	2040	2700-3000	white	200	25	168	1/30	A++→A
99LED964CW	F	28*	2500	6000-6400	white	220	25	190	1/20	A++→A
99LED964	F	28*	2500	4000-4300	white	220	25	190	1/20	A++→A
99LED964WW	F	28*	2500	2700-3000	white	220	25	190	1/20	A++→A

Body: PC | **Reflector:** policarbonate (pc) | **Light source:** Epistar SMD2835 | **Starting time:** <0.5s | **Power factor:** λ>0.8
Easy installation due to handy clips | Recessed mounted luminaire.

*Until Supply Last

~230V | 50/60 Hz | SMD | 160° | Ra≥80 | >25000 | INSTANT 100% | 30000h | Hg | IP 40 | RoHS COMPLIANT | EMC | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LED PANEL ROUND IP44
99LED609IP44
99LED609IP44CW

LED PANEL ROUND IP44
99LED611IP44
99LED611IP44CW

LED PANEL ROUND IP44
99LED617IP44
99LED617IP44CW

LED | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP44**

LED PANEL ROUND IP44

Catalogue number	Catalogue number with Emergency kit	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
99LED609IP44	**99LED609IP44E**	C	5	400	4000	white	90	21	40	A++→A
99LED609IP44CW	**99LED609IP44CWE**	C	5	400	6500	white	90	21	40	A++→A
99LED611IP44	**99LED611IP44E**	C	12	960	4000	white	175	21	20	A++→A
99LED611IP44CW	**99LED611IP44CWE**	C	12	960	6500	white	175	21	20	A++→A
99LED617IP44	**99LED617IP44E**	C	18	1440	4000	white	225	21	20	A++→A
99LED617IP44CW	**99LED617IP44CWE**	C	18	1440	6500	white	225	21	20	A++→A

Emergency kit with a possibility for work in an emergency regime more than two hours.

Body: aluminium | **Light source:** SMD 2835 | **Recessed mounted luminaire** | **Beam angle:** 120°| **Driver:** Isolated
Easy installation due to handy clips | Recessed mounted luminaire.

~230V | 50/60 Hz | SMD | 120° | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | RoHS COMPLIANT | EMC | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LED PANEL ROUND WATERPROOF, DUSTPROOF AND OILY SMOKE
99LED607IP65
99LED607IP65CW

LED PANEL ROUND WATERPROOF, DUSTPROOF AND OILY SMOKE
99LED610IP65
99LED610IP65CW

LED PANEL ROUND WATERPROOF, DUSTPROOF AND OILY SMOKE
99LED616IP65
99LED616IP65CW

LED PANEL ROUND WATERPROOF, DUSTPROOF AND OILY SMOKE
99LED623IP65
99LED623IP65CW

LED | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP65**

LED PANEL ROUND WATERPROOF, DUSTPROOF AND OILY SMOKE

Catalogue number	Catalogue number with Emergency kit	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Diameter1 (mm)	Height (mm)	Packing/Box (pcs)	Energy class
99LED607IP65	**99LED607IP65E**	C	7	660	4000	white	115	100-110	27	1/20	A++→A
99LED607IP65CW	**99LED607IP65CWE**	C	7	660	6500	white	115	100-110	27	1/20	A++→A
99LED610IP65	**99LED610IP65E**	C	10	770	4000	white	170	150-160	27	1/20	A++→A
99LED610IP65CW	**99LED610IP65CWE**	C	10	770	6500	white	170	150-160	27	1/20	A++→A
99LED616IP65	**99LED616IP65E**	C	16	1300	4000	white	220	200-210	27	1/20	A++→A
99LED616IP65CW	**99LED616IP65CWE**	C	16	1300	6500	white	220	200-210	27	1/20	A++→A
99LED623IP65	**99LED623IP65E**	C	23	1750	4000	white	240	220-230	39	1/20	A++→A
99LED623IP65CW	**99LED623IP65CWE**	C	23	1750	6500	white	240	220-230	39	1/20	A++→A

Emergency kit with a possibility for work in an emergency regime more than two hours.

Body: policarbonate (pc) | **Reflector:** policarbonate (pc) | Light source: SMD2835 | **Starting time:** <0.5s | Power factor: >0.9
Waterproof, dustproof and oily smoke|Milky white mask, soft light, not dazzling| Ultra-thin lamp body

~230V | 50/60 Hz | SMD | 120° | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | RoHS COMPLIANT | EMC | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

WATERPROOF LED PANEL ROUND
99LED609IP65

WATERPROOF LED PANEL ROUND
99LED611IP65CW

WATERPROOF LED PANEL ROUND
99LED617IP65CW

LED | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP65**

UNTIL SUPPLY LAST

WATERPROOF LED PANEL ROUND

Catalogue number	Catalogue number with Emergency kit	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
99LED609IP65	**99LED609IP65E**	F	5	400	4000	white	88	30	1/40	A++→A
99LED611IP65CW	**99LED611IP65CWE**	F	10	800	6500	white	150	27	1/40	A++→A
99LED617IP65CW	**99LED617IP65CWE**	F	18	1440	6500	white	225	27	1/20	A++→A

Emergency kit with a possibility for work in an emergency regime more than two hours.

Body: policarbonate (pc) | **Reflector:** policarbonate (pc) | **Light source:** Epistar | **Starting time:** <0.5s | **Power factor:** λ>0.8

Easy installation due to handy clips | Recessed mounted luminaire.

~230V | 50/60 Hz | SMD | 120° | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | IP 65 | RoHS COMPLIANT | EMC | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

SUPER SLIM LED PANELS
WITH SLIDABLE FIXING CLIPS

SUPER SLIM LED PANELS
WITH SLIDABLE FIXING CLIPS

LED NEUTRAL WHITE 4000K **IP40**

SUPER SLIM LED PANELS WITH SLIDABLE FIXING CLIPS

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter/ Length (mm)	Width (mm)	Height (mm)	Diameter1 (mm)	Packing/Box (pcs)	Energy class
99LED934/W	C	15	1000	4000	white	173		11	50-160	1/40	A++→A
99LED935/W	C	15	1000	4000	white	175	175	20	50-160	1/40	A++→A

Body: aluminium | **Light source:** San'an 2835SMD | 175-264V AC | Can by mounted in cut sizes from 50 to 160mm



~230V | 50/60 Hz | SMD 4014 | G13 | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | RoHS COMPLIANT | EMC | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LED PANEL ROUND OM
99xLED628
99xLED627
99xLED627CW

LED PANEL ROUND OM
99XLED623
99XLED622
99XLED622CW

LED PANEL ROUND OM
99XLED626
99XLED625
99XLED625CW

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP40**

LED PANELS ROUND OM STELLAR

Catalogue number	Catalogue number with Emergency kit	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
99XLED626	-	C	12	840	2700	white	165	32	1/30	A++→A
99XLED625	-	C	12	840	4000	white	165	32	1/30	A++→A
99XLED625CW	-	C	12	840	6500	white	165	32	1/30	A++→A
99XLED623	**99XLED623E**	C	18	1350	2700	white	219	32	1/20	A++→A
99XLED622	**99XLED622E**	C	18	1350	4000	white	219	32	1/20	A++→A
99XLED622CW	**99XLED622CWE**	C	18	1350	6500	white	219	32	1/20	A++→A
99XLED628	**99XLED628E**	C	24	1800	2700	white	295	32	1/20	A++→A
99XLED627	**99XLED627E**	C	24	1800	4000	white	295	32	1/20	A++→A
99XLED627CW	**99XLED627CWE**	C	24	1800	6500	white	295	32	1/20	A++→A

Emergency kit with a possibility for work in an emergency regime more than two hours.

Voltage: 185-240V | **Body:** aluminium | **Starting time:** <0.5s | **Power factor:** λ>0.8

OM - surface mounted luminaire

~230V | 50/60 Hz | SMD | 120° | Ra≥80 | >10000 | INSTANT 100% | 15000h | Hg | IP 40 | RoHS COMPLIANT | EMC | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LED PANEL ROUND OM
99LED625

LED PANEL ROUND OM
99LED623T

LED PANEL ROUND OM
99LED625T

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP40**

UNTIL SUPPLY **LAST**

LED PANEL ROUND OM

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
99LED625T	F	12	960	2700-3000	white	170	38	1/24	A++→A
99LED623T	F	18	1440	2700-3000	white	225	38	1/24	A++→A
99LED625	F	13	1040	2700-3000	satin nickel	170	38	1/40	A++→A

Body: aluminium | **Light source:** Epistar SMD 2835 | **Starting time:** <0.5s | **Power factor:** λ>0.8 | **OM** - surface mounted luminaire

~230V | 50/60 Hz | SMD | 120° | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | IP 40 | RoHS COMPLIANT | EMC | F | CE | 3+0 standard +extended | 3 YEAR TOTAL WARRANTY

LED PANEL ROUND OM

99LED966CW
99LED966
99LED966WW

LED PANEL ROUND OM

99LED965CW
99LED965
99LED965WW

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP40**

LED PANEL ROUND OM

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
99LED965CW	C	18	1530	6300-6500	white	175	33	1/60	A++→A
99LED965	C	18	1530	4000-4300	white	175	33	1/60	A++→A
99LED965WW	C	18	1530	2700-3000	white	175	33	1/60	A++→A
99LED966CW	C	28	2500	6300-6500	white	285	30	1/20	A++→A
99LED966	C	28	2500	4000-4300	white	285	30	1/20	A++→A
99LED966WW	C	28	2500	2700-3000	white	285	30	1/20	A++→A

Voltage: 185-240V | **Body:** Policarbonate (PC) | **Starting time:** <0.5s | **Power factor:** λ>0.8

OM - surface mounted luminaire

~230V | 50/60 Hz | SMD | 120° | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | IP 40 | RoHS COMPLIANT | EMC | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LED FIXTURES WITH ADJUSTABLE COLOUR TEMPERATURE

99DS406

LED | 3000 K | 4000 K | 6000 K | IP40

UNTIL SUPPLY LAST

LED FIXTURES WITH ADJUSTABLE COLOUR TEMPERATURE

Catalogue number	Product category	Sensor	Watt (W)	Whole fixture lumens (lm)	Colour body	Colour temp. (K)	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
99DS406	F	No	18	1440	white	3000 / 4000 / 6000	220	18.8	1/40	A++→A

Input Voltage: 110-240 VAC | **Body:** Alluminium | **Light source:** Sanan SMD2835 | **Starting Time:** <0.5s | **Power factor:** λ>0.9

3 options of colour temperature:
1. Cool White 6000K
2. Neutral White 4000K
3. Warm White 3000K

50/60 Hz | SMD 2835 | 110° | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | IP 40 | RoHS COMPLIANT | EMC | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

92DL1240/WH

LED NEUTRAL WHITE 4000K **IP40**

UNTIL SUPPLY LAST

INDIRECT LED DOWNLIGHTS

Catalogue number	Catalogue number with Emergency kit	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Diameter1 (mm)	Packing/Box (pcs)	Energy class
92DL1240/WH	**92DL1240/WHE**	F	12	480	4000K	white	149	45	130	1/1	A++→A

Body: aluminium

FRONT

BACK

Emergency kit with a possibility for work in an emergency regime more than two hours.

~230V | 50/60 Hz | SMD | 60° | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | RoHS COMPLIANT | EMC | F | CE | 4+1 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LED PANEL STELLAR SQUARE

99XLED637
99XLED636
99XLED636CW

LED PANEL STELLAR SQUARE

99XLED635
99XLED634
99XLED634CW

LED PANEL STELLAR SQUARE

99XLED633
99XLED632
99XLED632CW

LED PANEL STELLAR SQUARE OM

99XLED969
99XLED970

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP40**

LED PANELS STELLAR SQUARE

Catalogue number	Catalogue number with Emergency kit	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Length1 (mm)	Width1 (mm)	Packing/Box (pcs)	Energy class
99XLED633	**99XLED633E**	C	12	840	2700	white	167	167	18	150	150	1/24	A++→A
99XLED632	**99XLED632E**	C	12	840	4000	white	167	167	18	150	150	1/24	A++→A
99XLED632CW	**99XLED632CWE**	C	12	840	6500	white	167	167	18	150	150	1/24	A++→A
99XLED635	**99XLED635E**	C	18	1350	2700	white	221	221	18	200	200	1/20	A++→A
99XLED634	**99XLED634E**	C	18	1350	4000	white	221	221	18	200	200	1/20	A++→A
99XLED634CW	**99XLED634CWE**	C	18	1350	6500	white	221	221	18	200	200	1/20	A++→A
99XLED637	**99XLED637E**	C	24	1800	2700	white	296	296	18	275	275	1/20	A++→A
99XLED636	**99XLED636E**	C	24	1800	4000	white	296	296	18	275	275	1/20	A++→A
99XLED636CW	**99XLED636CWE**	C	24	1800	6500	white	296	296	18	275	275	1/20	A++→A
99XLED969	**99XLED969E**	C	18	1350	4000	white	220	220	32	-	-	1/20	A++→A
99XLED970	**99XLED970E**	C	24	1800	4000	white	300	300	32	-	-	1/20	A++→A

Emergency kit with a possibility for work in an emergency regime more than two hours.

Body: aluminium | **Light source:** SMD 2835 | **Starting time:** <0.5s | **Power factor:** 0.55 | Recessed mounted luminaire

~230V | 50/60 Hz | SMD | 120° | Ra≥80 | >10000 | INSTANT 100% | 15000h | Hg | IP 40 | RoHS COMPLIANT | EMC | F | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LED PANEL SQUARE
99LED968CW
99LED968
99LED968WW

LED PANEL SQUARE
99LED967CW
99LED967
99LED967WW

LED PANEL SQUARE OM
99LED969CW
99LED969
99LED969WW

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP40**

LED PANEL SQUARE

Catalogue number	Catalogue number with Emergency kit	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Length1 (mm)	Width1 (mm)	Packing/Box (pcs)	Energy class
99LED967CW	**99LED967CWE**	C	12	890	6400	white	175	175	13	155	155	1/20	A++→A
99LED967	**99LED967E**	C	12	890	4000	white	175	175	13	155	155	1/20	A++→A
99LED967WW	**99LED967WWE**	C	12	890	2700	white	175	175	13	155	155	1/20	A++→A
99LED968CW	**99LED968CWE**	C	18	1420	6400	white	225	225	13	205	205	1/20	A++→A
99LED968	**99LED968E**	C	18	1420	4000	white	225	225	13	205	205	1/20	A++→A
99LED968WW	**99LED968WWE**	C	18	1420	2700	white	225	225	13	205	205	1/20	A++→A
99LED969CW	**99LED969CWE**	C	18	1420	6400	white	220	220	32			1/20	A++→A
99LED969	**99LED969E**	C	18	1420	4000	white	220	220	32			1/20	A++→A
99LED969WW	**99LED969WWE**	C	18	1420	2700	white	220	220	32			1/20	A++→A

Emergency kit with a possibility for work in an emergency regime more than two hours.

Body: aluminium | **Light source:** Epistar SMD | **Starting time:** <0.5s | **Power factor:** λ>0.8

OM - surface mounted luminaire

~230V | 50/60 Hz | SMD | 120° | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | IP 40 | RoHS COMPLIANT | EMC | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LED PANEL SQUARE
99LED635T

LED PANEL SQUARE
99LED633T
99LED633

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | IP40

UNTIL SUPPLY LAST

LED PANEL SQUARE

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Length1 (mm)	Width1 (mm)	Packing/Box (pcs)	Energy class
99LED633T	F	9	720	2700-3000	white	148	148	21	130	130	1/40	A++→A
99LED633	F	12	960	2700-3000	white	145	145	21	130	130	1/40	A++→A
99LED635T	F	18	1440	2700-3000	white	218	218	21	200	200	1/20	A++→A

Body: aluminium | **Light source:** Epistar SMD | **Starting time:** <0.5s | **Power factor:** λ>0.8

OM - surface mounted luminaire

~230V | 50/60 Hz | SMD | 120° | Ra≥80 | >20000 | INSTANT 100% | 30000h | IP 40 | RoHS COMPLIANT | EMC | F | CE | 3+0 standard +extended | 3 YEAR TOTAL WARRANTY

LED GLASS PANEL SQUARE
99LED642
99LED643

LED GLASS PANEL ROUND
99LED638
99LED639

LED GLASS PANEL SQUARE
99LED644
99LED645

LED GLASS PANEL ROUND
99LED640
99LED641

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | **IP40**

LED GLASS PANELS SQUARE / ROUND

Catalogue number	Catalogue number with Emergency kit	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter/ Length (mm)	Height (mm)	Diameter1/ Length1 (mm)	Packing/Box (pcs)	Energy class
99LED642	**99LED642E**	C	6	480	4000	white	97	40	77	1/100	A++→A
99LED643	**99LED643E**	C	6	480	2700	white	97	40	77	1/100	A++→A
99LED644	**99LED644E**	C	18	1440	4000	white	200	40	180	1/20	A++→A
99LED645	**99LED645E**	C	18	1440	2700	white	200	40	180	1/20	A++→A
99LED638	**99LED638E**	C	6	480	4000	white	100	35	60	1/100	A++→A
99LED639	**99LED639E**	C	6	480	2700	white	100	35	60	1/100	A++→A
99LED640	**99LED640E**	C	18	1440	4000	white	200	35	148	1/20	A++→A
99LED641	**99LED641E**	C	18	1440	2700	white	200	35	148	1/20	A++→A

Emergency kit with a possibility for work in an emergency regime more than two hours.

Body: aluminium | **Light source:** Epistar SMD2835 | **Starting time:** <0.5s | **Power factor:** λ>0.8
Easy installation due to handy clips | Recessed mounted luminaire.

~230V | 50/60 Hz | SMD | 120° | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | IP 40 | RoHS COMPLIANT | EMC | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

RECESSED LED
CEILING LAMP ELLIS
95ELLISLEDR9/W
95ELLISLEDR18/W
95ELLISLEDR24/W

RECESSED LED
CEILING LAMP ELLIS
95ELLISLEDS9/W
95ELLISLEDS18/W

LED NEUTRAL WHITE 4000K **IP20**

RECESSED LED CEILING LAMP ELLIS

Catalogue number	Product category	Type	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Diameter 1 (mm)	Packing/Box (pcs)	Energy class
95ELLISLEDR9/W	C	ROUND	9	760	4000	White	100	21	55-70	1/100	A++→A
95ELLISLEDS9/W	C	SQUARE	9	760	4000	White	101/101	21	55-70	1/100	A++→A
95ELLISLEDR18/W	C	ROUND	18	1520	4000	White	119	21	55-90	1/60	A++→A
95ELLISLEDS18/W	C	SQUARE	18	1520	4000	White	120/120	21	55-90	1/60	A++→A
95ELLISLEDR24/W	C	ROUND	24	2280	4000	White	168	21	55-135	1/40	A++→A

Body: Alluminium| **Reflector:** PP | **Light source:** Sanan SMD2835-MLS | **Driver isolated:** 180-265V

Easy installation due to handy clips | Recessed mounted luminaire.

~230V | 50/60 Hz | SMD | 120° | Ra≥80 | >10000 | INSTANT 100% | 15000h | Hg | RoHS COMPLIANT | EMC | 2+0 standard +extended 2 YEAR TOTAL WARRANTY

RECESSED LED FIXTURE GLOSS
95GLOSS24

RECESSED LED FIXTURE BRILLIANCE
95BRILLIANCE24

LED | COOL WHITE 6400K | **IP20**

UNTIL SUPPLY **LAST**

RECESSED LED FIXTURE GLOSS / BRILLIANCE

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Diameter 1 (mm)	Packing/Box (pcs)	Energy class
95GLOSS24	F	24	1800	6500	White	220	20	205	1/20	A++→A
95BRILLIANCE24	F	24	1800	6500	White	220	20	205	1/20	A++→A

Gloss

Brilliance

Clips

Body: Alluminium| **Reflector:** policarbonate (pc) | **Light source:** Sanan SMD2835 | **Starting time:** <0.5s

Easy installation due to handy clips | Recessed mounted luminaire.

~230V | 50/60 Hz | SMD 2835 | 110° | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | IP 20 | RoHS | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

IVOR
95IVOR22LED

ASIA
95ASIA24LED

LED NEUTRAL WHITE 4000K **IP40**

UNTIL SUPPLY LAST

CEILING LAMPS IVOR/ ASIA

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95IVOR22LED	F	21	1330	2700	Black+gold	400	100	1/1	A++→A
95ASIA24LED	F	21	1100	2700	Chrome	350	55	1/1	A++→A

Body: Metal | Surface mounted luminaire

~230V | 50/60 Hz | SMD | 160° | Ra>80 | 30000h | RoHS COMPLIANT | EMC | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

NEOS
95NEOS18LED

REGO
95REGO18LED

LED IP40 DIMMABLE

CEILING LAMPS REGO / NEOS WITH REMOTE CONTROL

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95REGO18LED	C	18	1260	CCT - adjustable	White	410	90	1/5	A++→A
95NEOS18LED	C	18	2160	CCT - adjustable	White &Chrome	380	50	1/5	A++→A

Body: Metal and plastic | **Surface mounted luminaire** | **Beam angle:** Rego- 130°; Neos- 120° | **LED chip:** Rego- SANAN 5730; Neos- SANAN 2835 with LENS

~230V 50/60 Hz SMD Ra>80 30000h Hg RoHS EMC F CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LUCE
95LUCE24LED
95LUCE36LED

SELENA
95SELENA18LED

LED IP40 DIMMABLE

CEILING LAMPS SELENA / LUCE WITH REMOTE CONTROL

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95SELENA18LED	C	18	1170	CCT - adjustable	Chrome	400	60	1/5	A++→A
95LUCE24LED	C	24	1480	CCT - adjustable	Chrome	410	70	1/5	A++→A
95LUCE36LED	C	36	2150	CCT - adjustable	Chrome	510	80	1/5	A++→A

Body: Metal | **Surface mounted luminaire** | **Beam angle:** Luce- 130°; Selena- 120° | **LED chip:** Luce- SANAN 2835 with LENS; Selena- SANAN 5730

~230V 50/60 Hz SMD Ra>80 30000h Hg RoHS EMC F CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

SHELLY
95SHELLY18LED/WH

SHELLY
95SHELLY18LED/GR

LED IP40 DIMMABLE

CEILING LAMPS SHELLY WITH REMOTE CONTROL

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95SHELLY18LED/WH	C	18	2160	CCT - adjustable	White	400	60	1/5	A++→A
95SHELLY18LED/GR	C	18	2160	CCT - adjustable	Black	400	60	1/5	A++→A

Body: Metal | **Surface mounted luminaire** | **Beam angle:** 120° | **LED chip:** SANAN 2835 with LENS

~230V 50/60 Hz SMD Ra>80 30000h Hg RoHS EMC F CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

CEILING LAMPS NIGHT SKY WITH REMOTE CONTROL

95NIGHTSKY60LED

LED IP40 DIMMABLE

CEILING LAMPS NIGHT SKY WITH REMOTE CONTROL

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95NIGHTSKY60LED	C	60	4800	CCT - ADJUSTABLE	Chrome	400	40	1/1	A++→A

Body: Steel | **Diffuser:** PMMA | **LED chip:** 2835 SMD SANAN | **Surface mounted luminaire**

~230V 50/60 Hz SMD Ra>80 30000h Hg RoHS EMC F CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

ASTRA
95ASTRA24LED

LED | NEUTRAL WHITE 4000K | IP40

UNTIL SUPPLY LAST

CEILING LAMPS ASTRA

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95ASTRA24LED	F	21	1750	2700	Chrome	410	90	1/1	A++→A

Body: Metal | **Surface mounted luminaire**

~230V | 50/60 Hz | SMD | 160° | Ra>80 | 30000h | Hg | RoHS COMPLIANT | EMC | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

NEIL
95NEIL14LED/WH

MALIA
95MALIA12LED/WH

MALIA
95MALIA24LED/BL

LED NEUTRAL WHITE 4000K **IP20**

LED FIXTURES NEIL/ MALIA

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length/ Diameter (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95NEIL14LED/WH	C	14	770	4200	white	240		60	1/30	A++→A
95MALIA12LED/WH	C	12	660	4200	white	120	130		1/30	A++→A
95MALIA12LED/BL	C	12	660	4200	black	120	130		1/30	A++→A
95MALIA24LED/WH	C	24	1320	4200	white	265	130	100	1/20	A++→A
95MALIA24LED/BL	C	24	1320	4200	black	265	130	100	1/20	A++→A

Body: Aluminium & acrylic | **Light source:** SANAN SMD2835 | **Flicker free** | **Driver:** isolated IC

~230V | 50/60 Hz | SMD | Ra>80 | 30000h | Hg | RoHS COMPLIANT | EMC | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

DONUT
95DONUT20LED

DONUT
95DONUT32LED

LED | NEUTRAL WHITE 4000K | **IP20**

ROUND CEILING LAMP DONUT

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95DONUT20LED	C	20	1300	4000	white	285	80	1	A++→A
95DONUT32LED	C	32	2000	4000	white	385	95	1	A++→A

Body: Metal+ MS | **Light source:** Nationstar SMD 2835 | **Surface mounted luminaire** | **Beam angle:** 120°

~230V | 50/60 Hz | SMD | Ra>80 | 30000h | Hg | RoHS COMPLIANT | EMC | CE | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

AMY SUPER SLIM
95AMYLEDS12/W

AMY SUPER SLIM
95AMYLEDS18/W

AMY SUPER SLIM
95AMYLEDS24/W

LED NEUTRAL WHITE 4000K **IP20**

AMY SUPER SLIM

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height 1 (mm)	Packing/Box (pcs)	Energy class
95AMYLEDS12/W	C	12	960	4000	White	276	276	55	1/100	A++→A
95AMYLEDS18/W	C	18	1440	4000	White	330	330	57	1/200	A++→A
95AMYLEDS24/W	C	24	1920	4000	White	375	375	60	1/200	A++→A

Body: Steel| **Reflector:** PMMA | Light source: Sanan SMD2835-Sanan | **Driver isolated:** 180-265V

~230V | 50/60 Hz | SMD | 120° | Ra≥80 | >10000 | INSTANT 100% | 15000h | Hg | RoHS COMPLIANT | EMC | F | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

TRACY SUPER SLIM

95TRACYLEDS20
95TRACYLEDS32

TRACY SUPER SLIM

95TRACYLED20
95TRACYLED32
95TRACYLED42

LED NEUTRAL WHITE 4000K **IP20**

TRACY SUPER SLIM

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	IP code	Length/Diameter (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95TRACYLED20	C	20	1400	4000	white	20	290	-	65	1/10	A++>A
95TRACYLED32	C	32	2400	4000	white	20	390	-	65	1/10	A++>A
95TRACYLED42	C	42	2950	4000	white	20	480	-	65	1/10	A++>A
95TRACYLEDS20	C	20	1400	4000	white	20	280	280	60	1/10	A++>A
95TRACYLEDS32	C	32	2400	4000	white	20	330	330	65	1/10	A++>A

Material: Metal bottom and MS cover | **LED driver:** mounted in the body | **Light source:** 2835 SMD

~230V 50/60 Hz SMD Ra>80 30000h Hg RoHS EMC CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LITE
95LITE12LED
95LITE24LED

SENSOR LIGHT
99DS401

SHINE
95SHINE16LED

SHINE
95SHINE36LED

LED NEUTRAL WHITE 4000K **IP40**

LITE / SHINE

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	IP code	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95LITE12LED	C	12	960	4000	white	40	250	250	100	1/20	A++→A
95LITE24LED	C	24	1920	4000	white	40	350	350	100	1/10	A++→A
99DS401	C	12	800	4000	white	40	290	290	80	1/10	A++→A
95SHINE16LED	C	16	1040	4000	white	40	330	330	107	1/10	A++→A
95SHINE36LED	C	36	2340	4000	white	40	480	480	115	1/5	A++→A

detail SHINE 16W / 36W

Body: polycarbonate | **LED driver:** mounted in the body | **Light source:** EPISTAR
95DS401 - Detection Distance: max. 6m (<24°), Time Delay: 10 sec ± 3 sec to 3 min ± 30 sec (adjustable), Ambient Light: < 3-2000LUX

~230V | 50/60 Hz | SMD | Ra>80 | 30000h | Hg | RoHS | EMC | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

EMERGENCY CEILING LAMP NEPTUN

95NEPTUN18LEDE

LED COOL WHITE 6400K **IP65**

EMERGENCY CEILING LAMP NEPTUN

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95NEPTUN18LEDE	C	18	1800	6000K	White	280	65	1/10	A++→A

Material: Fireproof ABS | **Battery:** 7.4V 4400mAh 18650 | **Charging time:** ≤ 24h | **Emergency time:** ≥ 180 min | **Monthly inspection & Manual simulation check**

~230V | 50/60 Hz | SMD | Ra>80 | 30000h | Hg | RoHS COMPLIANT | EMC | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

ST73U

99DS201

LED NEUTRAL WHITE 4000K **UV LAMP**

ST73U DOUBLE WORK MODES INFRARED LED SENSOR/UV LAMP

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
99DS201	C	10	800	4000	250	49	1/100	A++→A

Automatic switching from disinfection mode to normal mode, via infrared sensor | **UV Lamp mode:** Prohibit disinfecting time: 5min | Power: 3W | **Disinfecting Time:** 30mins | **Sensor:** Detection range: 140° | **Detection distance:** max. 9m | **Installation height:** 1.8-2m | **Ambient light:** <3-2000LUX (adjustable)

Body material: UV proof PC

~230V | 50/60 Hz | SMD | Ra>80 | 30000h | Hg | RoHS COMPLIANT | EMC | CE | 3+0 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LED WALL LIGHT
95LIGHTS6

LED WALL LIGHT
95LIGHTB6
95LIGHTB12

LED NEUTRAL WHITE 4000K **IP20**

LED WALL LIGHT

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95LIGHTS6	C	6W	480	4000	white	140	70	1/20	A++→A
95LIGHTB6	F*	6W	480	4000	white	135	45	1/36	A++→A
95LIGHTB12	F*	12W	960	4000	white	180	45	1/24	A++→A

95LIGHTS6

95LIGHTS6

95LIGHTB6 / 95LIGHTB12

95LIGHTB6 / 95LIGHTB12


95LIGHTB6 / 95LIGHTB12

Body material: Aluminium | **Light source:** 95LIGHTS6 - Epistar COB, 95LIGHTB6 & 95LIGHTB12 - Epistar SMD2835

* Until Supply Last

~230V 50/60 Hz Ra>80 30000h Hg RoHS EMC F CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LED WALL LIGHT
ROUND IP54
White / Black / Grey

LED WALL LIGHT
SQUARE IP54
White / Black / Grey

LED WALL LIGHT
ROUNDED IP65
White / Black / Grey

LED NEUTRAL WHITE 4000K **IP54** **IP65**

LED WALL LIGHT

Catalogue number	Product category	Watt (W)	Type	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
969LED100R/WH	C	2X5W	Round	900	4000	white	130	110	100	1/12	A++→A
969LED100R/BL	C	2X5W	Round	900	4000	black	130	110	100	1/12	A++→A
969LED100R/GR	C	2X5W	Round	900	4000	grey	130	110	100	1/12	A++→A
969LED100S/WH	C	2X5W	Square	900	4000	white	100	100	100	1/10	A++→A
969LED100S/BL	C	2X5W	Square	900	4000	black	100	100	100	1/10	A++→A
969LED100S/GR	C	2X5W	Square	900	4000	grey	100	100	100	1/10	A++→A
969LEDW12/WH	C	**2X6W**	Rounded	1080	4000	white	175	28	90	1/40	A++→A
969LEDW12/BL	C	**2X6W**	Rounded	1080	4000	black	175	28	90	1/40	A++→A
969LEDW12/GR	C	**2X6W**	Rounded	1080	4000	grey	175	28	90	1/40	A++→A

Body material: Aluminium | **Diffuser:** Glass | **Light source 969led100:** Epistar LED COB **Light source 969LEDW12:** Epistar SMD2835

~230V 50/60 Hz Ra>80 30000h Hg RoHS EMC F CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

CABINET LAMP WITH SENSOR
99DS408

LED NIGHT LAMP WITH USB
99USB2

CABINET HINGE LED LIGHT
9HINGE2

LED NEUTRAL WHITE 4000K **IP20**

CABINET LAMP WITH SENSOR / LED NIGHT LAMP WITH USB

Catalogue number	Product category	Watt (W)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
99DS408	C	1.5	4000	white	88	26	1/50	A++→A
99USB2	C	0.5	4000	white	90	61	1/64	A++→A
9HINGE2	C	2	-	grey	20	48	1/300	A++→A

High-quality ABS material, environmental-friendly, sturdy and durable to use. Easy to install and convenient to use| Operated by 12V 23A battery (Not included) | When opening the cabinet,lamp will turns on automatically. When closing the cabinet, the light turns off

CABINET LAMP WITH SENSOR - Mode: ON/OF & auto | **Battery:** 3 X AAA | **Sensor distance:** max. 4m | **Duration:** 30s | **Sensors:** PIR sensor- workt when light intensity is less than 10lx

LED NIGHT LAMP with USB - Mode: ON/OF & auto | **Sensors:** PIR sensor- workt when light intensity is less than 10lx

RoHS COMPLIANT CE 3+0 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

DOWNLIGHT

ELR627
92627/W

ELR627
92627/SN

IP44

ELR627 - BATHROOM, IP44

Catalogue number	Product category	Model	Diameter (mm)	Height (mm)	Diameter1 (mm)	Colour body	Packing/Box (pcs)	Energy class
92627/W	C	ELR627	90	33	60	white	1/100	A++→E
92627/SN	C	ELR627	90	33	60	satin nickel	1/100	A++→E

Body: steel | **Diffuser:** glass

~230V | 12V | 50/60 Hz | max. 50W | IP 44 | RoHS COMPLIANT | III | F | CE | 3+0 standard +extended | 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

ELR627
92627/CH

ELR627
92627/AB

IP44

ELR627 - BATHROOM, IP44

Catalogue number	Product category	Model	Diameter (mm)	Height (mm)	Diameter1 (mm)	Colour body	Packing/Box (pcs)	Energy class
92627/CH	C	ELR627	90	33	60	chrome	1/100	A++→E
92627/AB	C	ELR627	90	33	60	antique brass	1/100	A++→E

Body: steel | **Diffuser:** glass

~230V | 12V | 50/60 Hz | max. 50W | IP 44 | RoHS COMPLIANT | 3+0 standard +extended | 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

SA-044
92044/G

SA-144
92144/RAB

IP44

UNTIL SUPPLY LAST

SA

Catalogue number	Product category	Model	Diameter (mm)	Length (mm)	Height (mm)	Diameter1 (mm)	Colour body	Packing/Box (pcs)	Energy class
92044/G	F	SA-044	80	-	37	71	gold	1/50	A++→E
92144/RAB	F	SA-144	-	85	48	72	red antique brass	1/50	A++→E

Body: steel | **Diffuser:** glass | **Ring:** aluminium alloy
With the purchase of additional lampholder GU10, spotlights can be used with 230V GU10 lamps.

12V | 50/60 Hz | MR-16 | GU5.3 | max. 50W | IP 20 IP 44 | RoHS COMPLIANT | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

ELMARK

www.elmarkholding.eu

CR-773

925773R/CL

CR-773

925773S/CL

IP20

CR-773

Catalogue number	Product category	Width/ Diameter (mm)	Length (mm)	Height (mm)	Cutting hole (mm)	Packing/ Box (pcs)	Energy class
925773R/CL	C	100	-	50	60	1/50	A++→E
925773S/CL	C	105	105	50	60	1/50	A++→E

Material: Stainless steel with crystal, **Lamps Not Included**

12V | MR-16 | GU5.3 | max. 50W | RoHS COMPLIANT | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY



ELMARK

www.elmarkholding.eu

CR-771

925P771R/CL

CR-772

925772S/CL

CR-772

925772S/CF

IP20

CR-771 / CR-772

Catalogue number	Product category	Watt (W)	Diameter (mm)	Height (mm)	Cutting hole (mm)	Colour temp. (K)	Packing/ Box (pcs)	Energy class
925P771R/CL	C	3	95	22	60	4000K	1/50	A++→A
925772S/CL	C	3	100	22	60	4000K	1/50	A++→A
925772S/CF	C	3	100	22	60	4000K	1/50	A++→A

Material: Aluminium & polyester with decorative LED lighting 150lm, **Lamps Not Included,** 3W Driver for LED ring included

12V MR-16 LED GU5.3 RoHS COMPLIANT CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

ELMARK

www.elmarkholding.eu

CR-774

925774S/CL

CR-775

925775S/CL



IP20

CR-774 / CR-775

Catalogue number	Product category	Watt (W)	Diameter (mm)	Height (mm)	Cutting hole (mm)	Colour temp. (K)	Packing/ Box (pcs)	Energy class
925774S/CL	C	3	100	22	60	4000	1/50	A++→A
925775S/CL	C	3	100	22	60	4000	1/50	A++→A

Material: Aluminium & polyester with decorative LED lighting 150lm, **Lamps Not Included,** 3W Driver for LED ring included

12V MR-16 LED GU53 RoHS COMPLIANT CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

CR-777
925777R/BK

CR-777
925777S/BK

CR-778
925778R/CL



CR-778
925778S/CL

IP20

CR-777 / CR-778

Catalogue number	Product category	Description	Colour	Width/Diameter (mm)	Length (mm)	Height (mm)	Cutting hole (mm)	Packing/Box (pcs)	Energy class
925777R/BK	C	Spotlight	Chrome and black	90	-	22	60	1/50	A++→E
925777S/BK	C	Spotlight	Chrome and black	90	90	22	60	1/50	A++→E
925778R/CL	C	Spotlight	Chrome and clear	90	-	32	60	1/50	A++→E
925778S/CL	C	Spotlight	Chrome and clear	90	90	32	60	1/50	A++→E

Material: Aluminium with glass, **Lamps Not Included**

12V | MR-16 | GU5.3 | max. 50W | RoHS COMPLIANT | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

SA-045
92045R1/WHFR

SA-045
92045S1/WHFR

SA-045
92045R1/BLFR

SA-045
92045S1/BLFR

IP20

SA-045

Catalogue number	Product category	Description	Colour	Width/Diameter (mm)	Length (mm)	Height (mm)	Cutting hole (mm)	Packing/Box (pcs)	Energy class
92045R1/WHFR	C	Downlight	white	98		45	70	1/50	A+→E
92045R1/BLFR	C	Downlight	black	98		45	70	1/50	A+→E
92045S1/WHFR	C	Downlight	white	92	92	45	70	1/50	A+→E
92045S1/BLFR	C	Downlight	black	92	92	45	70	1/50	A+→E

Material: Aluminium with acrylic, **Lamps Not Included. LED bulb only**

12V MR-16 GU5.3 RoHS CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

SA-045
92045S2/WHFR

SA-045
92045S3/WHFR

SA-045
92045S4/WHFR

IP20

SA-045

Catalogue number	Product category	Description	Colour	Width (mm)	Length (mm)	Height (mm)	Cutting hole (mm)	Packing/Box (pcs)	Energy class
92045S2/WHFR	C	Downlight	white	92	182	45	165x70	1/50	A++→E
92045S3/WHFR	C	Downlight	white	95	275	45	240x70	1/20	A++→E
92045S4/WHFR	C	Downlight	white	180	180	45	150x150	1/20	A++→E

Material: Aluminium with acrylic, **Lamps Not Included. LED bulb only**

12V MR-16 GU5.3 RoHS CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

SA-045
92045S2/BLFR

SA-045
92045S3/BLFR

SA-045
92045S4/BLFR

IP20

SA-045

Catalogue number	Product category	Description	Colour	Width (mm)	Length (mm)	Height (mm)	Cutting hole (mm)	Packing/Box (pcs)	Energy class
92045S2/BLFR	C	Downlight	black	92	182	45	165x70	1/50	A++→E
92045S3/BLFR	C	Downlight	black	95	275	45	240x70	1/20	A++→E
92045S4/BLFR	C	Downlight	black	180	180	45	150x150	1/20	A++→E

Material: Aluminium with acrylic, Lamps Not Included. LED bulb only

12V MR-16 GU5.3 RoHS CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

92GDL05R
92GDL09R

92GDL11R

92GDL06S
92GDL10S

92GDL06SGL

92GDL13S

92GDL14LEDS

IP20

GYPSUM DOWNLIGHTS

Catalogue number	Product category	Model	Lamp holder	Diameter/ Length (mm)	Diameter 1 (mm)	Width (mm)	Height (mm)	Colour body	Packing/Box (pcs)	Energy class
92GDL05R	C	round	GU10	100	90	-	40	white	1/20	A++→E
92GDL09R	C	round	GU10	128	108	-	43	white	1/20	A++→E
92GDL11R	C	round	GU10	131	116	-	72	white	1/20	A++→E
92GDL06S	C	square	GU10	122	107/107	122	57	white	1/20	A++→E
92GDL10S	C	square	GU10	122	107/107	122	60	white	1/20	A++→E
92GDL06SGL	C	square with diffuser	GU10	120	100/100	120	56	white	1/20	A++→E
92GDL13S	C	square	GU10	120	100/100	120	58	white	1/20	A++→E
92GDL14LEDS	C	square	LED CREE 1W	142	-	170	50	white	1/20	A++→E

92GDL06S

92GDL14LEDS: 70 lm/4000K/Beam angle 30°

Material: Plaster | Lamp not included
With the purchase of additional lampholder GU10/G9, spotlights can be used with 230V GU10/G9 lamps.

~230V | 50/60 Hz | max. 20W | IP 20 | RoHS | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

92GDL08W



92GDL07W

92GDL12W

92GDL15W

IP20

GYPSUM WALL FUXTURES

Catalogue number	Product category	Model	Lamp holder	Diameter/ Length (mm)	Width (mm)	Height (mm)	Colour body	Packing/Box (pcs)	Energy class
92GDL07W	C	square	G9	75	100	100	white	1/20	A++→E
92GDL08W	C	round	G9	70	100	100	white	1/20	A++→E
92GDL12W	C	round	G9	100	180	90	white	1/20	A++→E
92GDL15W	C	round	E27	300	165	120	white	1/12	A++→E

92GDL07W 92GDL08W 92GDL12W

Material: Plaster | Lamp not included
With the purchase of additional lampholder GU10/G9, spotlights can be used with 230V GU10/G9 lamps.

~230V | 50/60 Hz | max. 20W | IP 20 | RoHS | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.



BOUTIQUES MINI LED DOWNLIGHTS
99JR1201WW/SN
99JR1201CW/SN

BOUTIQUES MINI LED DOWNLIGHTS
99JR1202CW/GL

BOUTIQUES MINI LED DOWNLIGHTS
99JR1203CW/WH

LED | WARM WHITE 2700K | COOL WHITE 6400K | IP20 | 12V DC

UNTIL SUPPLY LAST

BOUTIQUES MINI LED DOWNLIGHTS

Catalogue number	Product category	Wattage (W)	Whole fixture lumens (lm)	Colour temp. (K)	Beam angle	Colour body	Body material	Diameter (mm)	Height (mm)	Diameter1 (mm)	Packing/Box (pcs)	Energy class
99JR1201WW/SN	F	3	150	2700-3000	30°	satin nickel	aluminium	48	22	32	1/100	A+
99JR1201CW/SN	F	3	150	6000-6400	30°	satin nickel	aluminium	48	22	32	1/100	A+
99JR1202CW/GL	F	3	150	6000-6400	30°	transparent	PMMA+ aluminium	45	41	32	1/100	A+
99JR1203CW/WH	F	3	150	6000-6400	30°	white	aluminium	50	43	32	1/100	A+

Residences, Jewelry, Showrooms, Hotels & Boutiques etc.
Light source: LED COB
Easy installation due to handy clips.

12V DC | 50/60 Hz | COB | Ra>80 | >15000 | INSTANT 100% | 30000h | Hg | RoHS COMPLIANT | EMC | 3+0 standard +extended | 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

SA-71
9271/SN-CH

SA-71
9271/PCH-CH

SA-71
9271/GR-CH

SA-91
9291/SN-CH

SA-91
9291/GR-CH

SA-91
9291/PCH-CH

IP20

SA

Catalogue number	Product category	Model	Fitting	Diameter (mm)	Height (mm)	Diameter1 (mm)	Colour body	Packing/Box (pcs)	Energy class
9271/SN-CH	C	SA-71	Fixed	78	25	58	satin nickel/chrome	1/100	A++→E
9271/PCH-CH	C	SA-71	Fixed	78	25	58	pearl chrome/chrome	1/100	A++→E
9271/GR-CH	C	SA-71	Fixed	78	25	58	graphite/chrome	1/100	A++→E
9291/SN-CH	C	SA-91	Movable	80	25	72	satin nickel/chrome	1/100	A++→E
9291/PCH-CH	C	SA-91	Movable	80	25	72	pearl chrome/chrome	1/100	A++→E
9291/GR-CH	C	SA-91	Movable	80	25	72	graphite/chrome	1/100	A++→E

Body: aluminium alloy
With the purchase of additional lampholder GU10, spotlights can be used with 230V GU10 lamps.

12V | 50/60 Hz | MR-16 | GU5.3 | max. 50W | IP 20 | RoHS COMPLIANT | F | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

SA-70
9270/W

SA-70
9270/CH

SA-70
9270/SN

SA-70
9270/AB

SA-90
9290/W

SA-90
9290/CH

SA-90
9290/SN

SA-90
9290/AB

IP20

SA

Catalogue number	Product category	Model	Fitting	Diameter (mm)	Height (mm)	Diameter1 (mm)	Colour body	Packing/Box (pcs)	Energy class
9270/W	C	SA-70	Fixed	78	25	58	white	1/100	A++→E
9270/CH	C	SA-70	Fixed	78	25	58	chrome	1/100	A++→E
9270/SN	C	SA-70	Fixed	78	25	58	satin nickel	1/100	A++→E
9270/AB	C	SA-70	Fixed	78	25	58	antique brass	1/100	A++→E
9290/W	C	SA-90	Movable	85	25	70	white	1/100	A++→E
9290/CH	C	SA-90	Movable	85	25	70	chrome	1/100	A++→E
9290/SN	C	SA-90	Movable	85	25	70	satin nickel	1/100	A++→E
9290/AB	C	SA-90	Movable	85	25	70	antique brass	1/100	A++→E

Body: aluminium alloy
With the purchase of additional lampholder GU10, spotlights can be used with 230V GU10 lamps.

12V | 50/60 Hz | MR-16 | GU5.3 | max. 50W | IP 20 | RoHS COMPLIANT | F | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

SA-702
92702/CH

SA-702H
92702H/G

SA-702H
92702H/SN

IP20

UNTIL SUPPLY LAST

SA

Catalogue number	Product category	Model	Fitting	Diameter (mm)	Height (mm)	Diameter1 (mm)	Colour body	Packing/Box (pcs)	Energy class
92702/CH	F	SA-702	Fixed	78	40	58	chrome	1/50	A++→E
92702H/SN	F	SA-702H	Movable	78	40	58	satin nickel	1/50	A++→E
92702H/G	F	SA-702H	Movable	78	40	58	gold	1/50	A++→E

Body: aluminium alloy
With the purchase of additional lampholder GU10, spotlights can be used with 230V GU10 lamps.

12V | 50/60 Hz | MR-16 | GU5.3 | max. 50W | IP 20 | RoHS COMPLIANT | F | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

SA-712
92712/CH

SA-712H
92712/SN

SA-712
92712/G



SA-712H
92712H/CH

SA-712H
92712H/SN



SA-712H
92712H/G

IP20

UNTIL SUPPLY LAST

SA

Catalogue number	Product category	Model	Fitting	Diameter (mm)	Height (mm)	Diameter1 (mm)	Colour body	Packing/Box (pcs)	Energy class
92712/CH	F	SA-712	Fixed	78	40	56	chrome	1/50	A++→E
92712/SN	F	SA-712	Fixed	78	40	56	satin nickel	1/50	A++→E
92712/G	F	SA-712	Fixed	78	40	56	gold	1/50	A++→E
92712H/CH	F	SA-712H	Movable	78	40	56	chrome	1/50	A++→E
92712H/SN	F	SA-712H	Movable	78	40	56	satin nickel	1/50	A++→E
92712H/G	F	SA-712H	Movable	78	40	56	gold	1/50	A++→E

Body: aluminium alloy
With the purchase of additional lampholder GU10, spotlights can be used with 230V GU10 lamps.

12V | 50/60 Hz | MR-16 | GU5.3 | max. 50W | IP 20 | RoHS COMPLIANT | F | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

SA-710
9271/G

SA-910
9291/G

SIM-5
9205/G

SIM-55
9255/G

IP20

UNTIL SUPPLY LAST

SIM / SA

Catalogue number	Product category	Model	Diameter (mm)	Height (mm)	Diameter1 (mm)	Colour body	Packing/Box (pcs)	Energy class
9205/G	F	SIM-5	70	20	56	gold	1/100	A++→E
9255/G	F	SIM-55	70	23	-	gold	1/100	A++→E
9271/G	F	SA-710	78	30	60	gold	1/100	A++→E
9291/G	F	SA-910	84	23	66	gold	1/100	A++→E

Body: aluminium alloy

12V | 50/60 Hz | JC | G4 | max. 20W | IP 20 | RoHS | F | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

89151

89144

89152

IP20

UNTIL SUPPLY LAST

PLASTIC DOWNLIGHTS

Catalogue number	Product category	Model	Diameter -Length (mm)	Height (mm)	Diameter1 (mm)	Colour body	Packing/Box (pcs)	Energy class
89151	F	PLM- 92W	90	32	70	white	1/1	A++→E
89152	F	PLS- 92W	90	30	70	white	1/1	A++→E
89144	F	PLW- 92W	92/172	27	2X73	white	1/1	A++→E

Body: Plastic | **Lamp not included**

~230V | 12V | 50/60 Hz | max. 20W | IP 20 | RoHS COMPLIANT | F | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

89153



89154

89156

89155

IP20

UNTIL SUPPLY LAST

DOWNLIGHTS

Catalogue number	Product category	Material	Model	Diameter -Length (mm)	Height (mm)	Diameter1 (mm)	Colour body	Packing/Box (pcs)	Energy class
89153	F	Metal	MS- 92CH	85/85	26	70	chrome	1/1	
89155	F	Metal	MR- 92CH	79	33	69	chrome	1/1	
89154	F	Metal	MS- 92SN	85/85	27	70	satin nickel	1/1	
89156	F	Metal	MR- 92SN	80	30	70	satin nickel	1/1	

Lamp not included

~230V 12V 50/60 Hz max. 20W IP 20 RoHS COMPLIANT III F CE 2+0 standard +extended 2 YEAR TOTAL WARRANTY

SA-914
92914WH/G
92914WW/G

SA-914
92914WH/GR
92914WW/GR



SA-913
92913WH/G
92913WW/G

SAS-14
9214WH/G
9214WW/G

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | IP40

UNTIL SUPPLY LAST

SAS

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Diameter1 (mm)	Packing/Box (pcs)	Energy class
9214WH/G	F	1	80	4000-4300	gold	60	21	50	1/100	A++→A
9214WW/G	F	1	80	2700-3000	gold	60	21	50	1/100	A++→A
92913WH/G	F	3	240	4000-4300	gold	88	40	65	1/100	A++→A
92913WW/G	F	3	240	2700-3000	gold	88	40	65	1/100	A++→A
92914WH/G	F	3	240	4000-4300	gold	90	41	70	1/100	A++→A
92914WW/G	F	3	240	2700-3000	gold	90	41	70	1/100	A++→A
92914WH/GR	F	3	240	4000-4300	graphite	90	41	70	1/100	A++→A
92914WW/GR	F	3	240	2700-3000	graphite	90	41	70	1/100	A++→A

Body: aluminium alloy | **Light source:** Epistar
LED recessed round spotlight. Easy installation due to handy clips.

~230V | 50/60 Hz | High power | 60° | Ra>80 | >15000 | INSTANT 100% | 30000h | Hg | IP 20 | RoHS COMPLIANT | EMC | F | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

RECESSED ROUND DOWN LIGHT
92R6868

RECESSED SQUARE DOWN LIGHT
92R6869

RECESSED ROUND DOWN LIGHT
92R6870

IP20

RECESSED DOWN LIGHT

Catalogue number	Product category	Model	Fitting	Diameter/ Length (mm)	Height (mm)	Cut size (mm)	Lampholder	Packing/Box (pcs)	Energy class
92R6870	C	R6870	Movable	90	37	83	1XGU10	1/60	A++→E
92R6868	C	R6868	Movable	90	53	83	1XGU10	1/60	A++→E
92R6869	C	R6869	Movable	90/90	53	80x83	1XGU10	1/60	A++→E

Material: Aluminium + PC | **Input voltage:** 220-240VAC | **Mounting:** Recessed | Compatible with GU10 LED lamp | Lamp Not included

4+1 standard +extended 5 YEAR TOTAL WARRANTY

ROUND ADJUSTABLE
FRAME
+
LED LAMP 10W / 15W

ROUND ADJUSTABLE DEEP ANTI-GLARE
FRAME
+
LED LAMP 10W / 15W

SQUARE ADJUSTABLE DEEP ANTI-GLARE
FRAME
+
LED LAMP 10W / 15W

ROUND PIN-HOLE
FRAME
+
LED LAMP 10W / 15W

LED LAMPS 10W / 15W

10W
NON-DIMABLE
COLOUR TEMP. 3000K / 4000K
BEAM ANGLE 36° / 60°

15W
DIMMABLE
COLOUR TEMP. 3000K / 4000K
BEAM ANGLE 36° / 60°

FRAMES FOR LED LAMPS 10W / 15W

ROUND ADJUSTABLE

ROUND DEEP ADJUSTABLE

SQUARE DEEP ADJUSTABLE

ROUND PIN-HOLE

ADJUSTABLE DEEP ANTI-GLARE ROUND FRAME
92A6020

ADJUSTABLE DEEP ANTI-GLARE SQUARE FRAME
92A6215

ADJUSTABLE FRAME
92A6154

PIN-HOLE FRAME
92A6255

FRAMES FOR LED LAMP 10W / 15W

Catalogue number	Product category	Type	Diameter / Length (mm)	Height (mm)	Cut size (mm)	Packing/Box (pcs)
92A6154	C	Adjustable	90	34	83	1/60
92A6020	C	Adjustable deep anti-glare round	90	53	83	1/60
92A6215	C	Adjustable deep anti-glare square	90/90	53	80/83	1/60
92A6255	C	Pin-hole	90	37	83	1/60

Material: Aluminium | **Decorative frames are compatible with all LED Lamps 10W & 15W**

4+1 standard +extended 5 YEAR TOTAL WARRANTY

LED LAMP 10W

92M6210W36
92M6210W60
92M6210WW36
92M6210WW60

LED LAMP 15W

92M6215W36
92M6215W60
92M6215WW36
92M6215WW60

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | **IP44** | **10W** | **15W**

LED LAMPS

Catalogue number	Product category	Dimmable	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Beam angle	Diameter (mm)	Height (mm)	Packing/ Box (pcs)	Energy class
92M6210W36	C	Non- dimmable	10	1200	4000	36°	62	38	1/60	A++→A
92M6210W60	C	Non- dimmable	10	1200	4000	60°	62	38	1/60	A++→A
92M6210WW36	C	Non- dimmable	10	1200	3000	36°	62	38	1/60	A++→A
92M6210WW60	C	Non- dimmable	10	1200	3000	60°	62	38	1/60	A++→A
92M6215W36	C	Triac- dimmable	15	1540	4000	36°	62	51	1/60	A++→A
92M6215W60	C	Triac- dimmable	15	1540	4000	60°	62	51	1/60	A++→A
92M6215WW36	C	Triac- dimmable	15	1540	3000	36°	62	51	1/60	A++→A
92M6215WW60	C	Triac- dimmable	15	1540	3000	60°	62	51	1/60	A++→A

Material: Aluminium + PC | **Input voltage:** 220-240VAC | **Light source:** COB LED with a lens of optical

~230V | 50/60 Hz | COB | Ra>80 | RoHS | EMC | CE | 4+1 standard +extended | 5 YEAR TOTAL WARRANTY

ELMARK
www.elmarkholding.eu

92FLD1530/WH
92FLD1540/WH
92FLD1565/WH

92FLD2530/WH
92FLD2540/WH
92FLD2565/WH

92FLD3530/WH
92FLD3540/WH
92FLD3565/WH

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP44**

DEEP RECESSED LED DOWNLIGHT, IP44

Catalogue number	Catalogue number with Emergency kit	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Diameter1 (mm)	Packing/ Box (pcs)	Energy class
92FLD1530/WH	**92FLD1530/WHE**	C	15	1350	3000	white	128	70	108	1/40	A++→A
92FLD1540/WH	**92FLD1540/WHE**	C	15	1350	4000	white	128	70	108	1/40	A++→A
92FLD1565/WH	**92FLD1565/WHE**	C	15	1350	6500	white	128	70	108	1/40	A++→A
92FLD2530/WH	**92FLD2530/WHE**	C	25	2250	3000	white	183	97	165	1/20	A++→A
92FLD2540/WH	**92FLD2540/WHE**	C	25	2250	4000	white	183	97	165	1/20	A++→A
92FLD2565/WH	**92FLD2565/WHE**	C	25	2250	6500	white	183	97	165	1/20	A++→A
92FLD3530/WH	**92FLD3530/WHE**	C	35	3150	3000	white	220	100	195	1/20	A++→A
92FLD3540/WH	**92FLD3540/WHE**	C	35	3150	4000	white	220	100	195	1/20	A++→A
92FLD3565/WH	**92FLD3565/WHE**	C	35	3150	6500	white	220	100	195	1/20	A++→A

Body: aluminium | **Reflector:** plastic

FRONT

BACK

Emergency kit with a possibility for work in an emergency regime more than two hours.

~230V | 50/60 Hz | SMD | 100° | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | IP 44 | RoHS | EMC | 4+1 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

92TS0940/WH

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP44**

DEEP RECESSED LED DOWNLIGHT

Catalogue number	Catalogue number with Emergency kit	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Diameter1 (mm)	Packing/Box (pcs)	Energy class
92TS0940/WH	**92TS0940/WHE**	C	9	765	4000	white	95	65	80	1/60	A++→A
92TS0930/WH	**92TS0930/WHE**	C	9	765	3000	white	95	65	80	1/60	A++→A
92TS0964/WH	**92TS0964/WHE**	C	9	765	6400	white	95	65	80	1/60	A++→A
92TS1540/WH	**92TS1540/WHE**	C	15	1275	4000	white	115	70	95	1/40	A++→A
92TS1530/WH	**92TS1530/WHE**	C	15	1275	3000	white	115	70	95	1/40	A++→A
92TS1564/WH	**92TS1564/WHE**	C	15	1275	6400	white	115	70	95	1/40	A++→A
92TS2440/WH	**92TS2440/WHE**	C	24	2040	4000	white	140	75	120	1/24	A++→A
92TS2430/WH	**92TS2430/WHE**	C	24	2040	3000	white	140	75	120	1/24	A++→A
92TS2464/WH	**92TS2464/WHE**	C	24	2040	6400	white	140	75	120	1/24	A++→A
92TS3040/WH	**92TS3040/WHE**	C	30	2550	4000	white	185	80	150	1/18	A++→A
92TS3030/WH	**92TS3030/WHE**	C	30	2550	3000	white	185	80	150	1/18	A++→A
92TS3064/WH	**92TS3064/WHE**	C	30	2550	6400	white	185	80	150	1/18	A++→A

Voltage: 220-240VAC | **Beam angle:** 60° | **Body material:** Aluminium + PC | **LED Chip:** SANAN 2835 SMD | **Driver:** external isolated driver | Short circuit protection

~230V | 50/60 Hz | SMD | Ra≥80 | Hg | RoHS COMPLIANT | EMC | CE | 4+1 standard +extended | 5 YEAR TOTAL WARRANTY

SIM-1552

SIM-155

SIM-1553

SIM-255

IP20

UNTIL SUPPLY LAST

SIM

Catalogue number	Product category	Model	Length (mm)	Width (mm)	Height (mm)	Colour body	Packing/Box (pcs)	Energy class
92255/CH	F	SIM-255	130	130	40	chrome	1/50	A++→E
92255/AB	F	SIM-255	130	130	40	antique brass	1/50	A++→E
92255/G	F	SIM-255	130	130	40	gold	1/50	A++→E
92255K/G	F	SIM-255 with key	130	130	40	gold	1/50	A++→E
92155/CH	F	SIM-155	82	132	85	chrome	1/50	A++→E
92155/SN	F	SIM-155	82	132	85	satin nickel	1/50	A++→E
92155/AB	F	SIM-155	82	132	85	antique brass	1/50	A++→E
92155/G	F	SIM-155	82	132	85	gold	1/50	A++→E
92155K/SN	F	SIM-155 with key	82	132	85	satin nickel	1/50	A++→E
921552K/SN	F	SIM-1552 with key	450	130	80	satin nickel	1/50	A++→E
921553K/SN	F	SIM-1553 with key	600	130	80	satin nickel	1/50	A++→E

SIM-255 with key

SIM-155 with key

Body: stainless steel | **Model SIM-255K** - with switch

12V | 50/60 Hz | JC | G4 | max. 20W | IP 20 | RoHS | F | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

GL FILM

GL 222

RDL60COB

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | IP40

UNTIL SUPPLY LAST

GL

Catalogue number	Product category	Model	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Diameter1 (mm)	Packing/ Box (pcs)	Energy class
92LED222WW	F	GL 222	18X1W	1260	2700-3000	aluminium	160	95	145	1/12	A++→A
92LED215WH	F	GL FILM	5	375	4000-5000	white	125	70	110	1/20	A++→A
92LED215WW	F	GL FILM	5	375	2700-3000	white	125	70	110	1/20	A++→A
92DL62040	F	RDL 60 COB	20	1800	4000-4300	white	140	97	120	1/12	A++→A
92DL62027	F	RDL 60 COB	20	1800	2700-3000	white	140	97	120	1/12	A++→A

Body: aluminium | **Diffuser:** glass | **Light source:** Epistar
Power factor: λ>0.9 | **Starting time:** <0.5s | LED recessed round downlight COB. Easy installation due to handy clips.

~230V | 50/60 Hz | COB | 90° | Ra>80 | 30000h | >20000 | INSTANT 100% | Hg | IP 40 | RoHS COMPLIANT | EMC | F | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

GL 201E
satin nickel / white

GL 202E
satin nickel / white

GL 203E
satin nickel / white

GL205E
satin nickel / white

GL 204E
satin nickel / white

GL103E
satin nickel / white

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | IP44

UNTIL SUPPLY LAST

DOWNLIGHT SET WITH LED STICK LAMPS

Catalogue number 4000K	Catalogue number 2700K	Product category	Type	Watt (W)	LED lamp lumens (lm)	Socket type	Colour body	Diameter (mm)	Height (mm)	Diameter1 (mm)	Packing/ Box (pcs)	Energy class
92201LEDW/SN	**92201LEDWW/SN**	F	GL201E	2X9	2x750	E27	satin nickel	226	110	210	1/12	A+ A++→A
92201LEDW/W	**92201LEDWW/W**	F	GL201E	2X9	2x750	E27	white	226	110	210	1/12	A+ A++→A
92202LEDW/SN	**92202LEDWW/SN**	F	GL202E	2X9	2x750	E27	satin nickel	226	110	210	1/12	A+ A++→A
92202LEDW/W	**92202LEDWW/W**	F	GL202E	2X9	2x750	E27	white	226	110	210	1/12	A+ A++→A
92203LEDW/SN	**92203LEDWW/SN**	F	GL203E	2X9	2x750	E27	satin nickel	235	110	210	1/12	A+ A++→A
92203LEDW/W	**92203LEDWW/W**	F	GL203E	2X9	2x750	E27	white	235	110	210	1/12	A+ A++→A
92204LEDW/SN	**92204LEDWW/SN**	F	GL204E	2X9	2x750	E27	satin nickel	230	110	210	1/12	A+ A++→A
92204LEDW/W	**92204LEDWW/W**	F	GL204E	2X9	2x750	E27	white	230	110	210	1/12	A+ A++→A
92205LEDW/SN	**92205LEDWW/SN**	F	GL205E	2X9	2x750	E27	satin nickel	225	110	210	1/12	A+ A++→A
92205LEDW/W	**92205LEDWW/W**	F	GL205E	2X9	2x750	E27	white	225	110	210	1/12	A+ A++→A
92103LEDW/TCH	**92103LEDWW/TCH**	F	GL103E	2X9	2x750	E27	satin nickel	190	100	170	1/12	A+ A++→A
92103LEDW/W	**92103LEDWW/W**	F	GL103E	2X9	2x750	E27	white	190	100	170	1/12	A+ A++→A

Downlight

LED STICKS LAMP

LED STICKS LAMP

White

Satin nickel

~230V | 50/60 Hz | Ra≥80 | >20000 | INSTANT 100% | 30000h | IP 44 | RoHS | EMC | F | CE | 3+0 standard +extended | 3 YEAR TOTAL WARRANTY

GL 206E
satin nickel / white

GL 210E
satin nickel / white

GL 213E
satin nickel / white

GL 214E
satin nickel / white

GL 211E
satin nickel / white

GL 120E
satin nickel / white

LED WARM WHITE 2700K NEUTRAL WHITE 4000K **IP44**

UNTIL SUPPLY LAST

DOWNLIGHT SET WITH LED STICK LAMPS

Catalogue number 4000K	Catalogue number 2700K	Product category	Type	Watt (W)	LED lamp lumens (lm)	Socket type	Colour body	Diameter (mm)	Height (mm)	Diameter1 (mm)	Packing/ Box (pcs)	Energy class
92206LEDW/GH	**92206LEDWW/GH**	F	GL206E	2X9	2x750	E27	graphite/chrome	225	110	210	1/12	A+ A++→A
92206LEDW/SH	**92206LEDWW/SH**	F	GL206E	2X9	2x750	E27	satin nickel/chrome	225	110	210	1/12	A+ A++→A
92210LEDW/SN	**92210LEDWW/SN**	F	GL210E	2X9	2x750	E27	satin nickel	228	110	210	1/12	A+ A++→A
92210LEDW/W	**92210LEDWW/W**	F	GL210E	2X9	2x750	E27	white	228	110	210	1/12	A+ A++→A
92211LEDW/SN	**92211LEDWW/SN**	F	GL211E	2X9	2x750	E27	white	230	110	210	1/12	A+ A++→A
92211LEDW/W	**92211LEDWW/W**	F	GL211E	2X9	2x750	E27	satin nickel	230	110	210	1/12	A+ A++→A
92213LEDW/SN	**92213LEDWW/SN**	F	GL213E*	2X9	2x750	E27	satin nickel	266	65	-	1/12	A+ A++→A
92213LEDW/W	**92213LEDWW/W**	F	GL213E*	2X9	2x750	E27	white	266	65	-	1/12	A+ A++→A
92214LEDW/SN	**92214LEDWW/SN**	F	GL214E*	2X9	2x750	E27	satin nickel	240	60	-	1/12	A+ A++→A
92214LEDW/W	**92214LEDWW/W**	F	GL214E*	2X9	2x750	E27	white	240	60	-	1/12	A+ A++→A
92120LED6W/TCH	**92120LED6WW/TCH**	F	GL120E	1X9	750	E27	satin nickel	190	200	170	1/12	A+ A++→A
92120LED6W/W	**92120LED6WW/W**	F	GL120E	1X9	750	E27	white	190	200	170	1/12	A+ A++→A
92120LED4W/TCH	**92120LED4WW/TCH**	F	GL120E	1X9	750	E27	satin nickel	140	160	120	1/12	A+ A++→A
92120LED4W/W	**92120LED4WW/W**	F	GL120E	1X9	750	E27	white	140	160	120	1/12	A+ A++→A

Downlight

LED STICKS LAMP

LED STICKS LAMP

White

Satin nickel

*surface mounting

~230V 50/60 Hz Ra≥80 >20000 INSTANT 100% 30000h Hg IP 44 RoHS EMC F CE 3+0 standard +extended 3 YEAR TOTAL WARRANTY

QUAD612
92Q61240WH
92Q61227WH
92Q61240DGR
92Q61227DGR

QUAD312
92Q31240WH
92Q31227WH

QUAD412
92Q41240WH
92Q41227WH
92Q41240DGR
92Q41227DGR

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | **IP20**

UNTIL SUPPLY LAST

QUAD

Catalogue number	Product category	Watt	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
92Q31240WH	F	3X15W	3825	4000K	white	490	192	143		A+ A++→A
92Q31227WH	F	3X15W	3825	2700K	white	490	192	143		A+ A++→A
92Q41240WH	F	4X15W	5100	4000K	white	342	342	160		A+ A++→A
92Q41227WH	F	4X15W	5100	2700K	white	342	342	160		A+ A++→A
92Q41240DGR	F	4X15W	5100	4000K	dark grey	342	342	160		A+ A++→A
92Q41227DGR	F	4X15W	5100	2700K	dark grey	342	342	160		A+ A++→A
92Q61240WH	F	6X15W	7650	4000K	white	490	340	140		A+ A++→A
92Q61227WH	F	6X15W	7650	2700K	white	490	340	140		A+ A++→A
92Q61240DGR	F	6X15W	7650	4000K	dark grey	490	340	140		A+ A++→A
92Q61227DGR	F	6X15W	7650	2700K	dark grey	490	340	140		A+ A++→A

white

dark grey

Body: aluminium | **Light source:** LED lamp PAR30 LED recessed downlight. Easy installation due to handy clips.

~230V | 50/60 Hz | LED PAR30 | E27 | 38° | Ra>80 | 30000h | >20000 | INSTANT 100% | Hg | IP 20 | RoHS COMPLIANT | EMC | F | CE | 3+0 standard +extended 3 YEAR TOTAL WARRANTY

SKY TLOM

SKY TLR

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP40**

UNTIL SUPPLY **LAST**

SKY TLR / SKY TLOM

Catalogue number WHITE	Catalogue number BLACK	Catalogue number GREY	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Body material	Diameter (mm)	Height (mm)	Beam angle	Packing/Box (pcs)	Energy class
	93TLOM180W/BL	**93TLOM180W/GR**	F	20	1800	4000	aluminium	130	98	24°	1/24	A++→A
		93TLOM180WW/GR	F	20	1800	2700	aluminium	130	98	24°	1/24	A++→A
93TLOM180CW/WH	**93TLOM180CW/BL**	**93TLOM180CW/GR**	F	20	1800	6400	aluminium	130	98	24°	1/24	A++→A
93TLOM190W/WH	**93TLOM190W/BL**	**93TLOM190W/GR**	F	30	2700	4000	aluminium	163	145	24°	1/12	A++→A
93TLOM190WW/WH		**93TLOM190WW/GR**	F	30	2700	2700	aluminium	163	145	24°	1/12	A++→A
93TLOM190CW/WH	**93TLOM190CW/BL**	**93TLOM190CW/GR**	F	30	2700	6400	aluminium	163	145	24°	1/12	A++→A
93TLR503W/WH			F	10	900	4000	aluminium	142	105	24°	1/12	A++→A
93TLR503CW/WH		**93TLR503CW/GR**	F	10	900	6400	aluminium	142	105	24°	1/12	A++→A
		93TLR504W/GR	F	15	1350	4000	aluminium	142	105	24°	1/12	A++→A
		93TLR504WW/GR	F	15	1350	2700	aluminium	142	105	24°	1/12	A++→A
93TLR504CW/WH	**93TLR504CW/BL**	**93TLR504CW/GR**	F	15	1350	6400	aluminium	142	105	24°	1/12	A++→A

SKY TLOM

SKY TLOM

SKY TLR

SKY TLR

white colour

black colour

grey colour

~230V | 50/60 Hz | COB | Ra>80 | 30000h | >20000 | INSTANT 100% | Hg | IP 40 | RoHS COMPLIANT | EMC | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

DL-044 ROUND
92DL044R1/WH

DL-044 ROUND
92DL044R1/BL

IP20

DL-044 ROUND

Catalogue number	Product category	Description	Colour	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
92DL044R1/WH	C	Downlight	white	100	125	1/20	A++→E
92DL044R1/BL	C	Downlight	black	100	125	1/20	A++→E

Body: Aluminium | **Lamps Not Included** | **Lamp holder:** GU10

RoHS COMPLIANT CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

DL-044 SQUARE
92DL044S1/BL

DL-044 SQUARE
92DL044S1/BLWH

DL-044 SQUARE
92DL044S1/GDWH

DL-044 SQUARE
92DL044S1/GDBL

IP20

DL-044 SQUARE

Catalogue number	Product category	Description	Colour	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
92DL044S1/BL	C	Downlight	black	110	110	110	1/30	A++→E
92DL044S1/BLWH	C	Downlight	black & white	110	110	110	1/30	A++→E
92DL044S1/GDWH	C	Downlight	gold & white	110	110	110	1/30	A++→E
92DL044S1/GDBL	C	Downlight	gold & black	110	110	110	1/30	A++→E

Body: Aluminium | **Lamps Not Included** | **Lamp holder:** GU10

RoHS COMPLIANT CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

DL-044 SQUARE
92DL044S2/BL

DL-044 SQUARE
92DL044S2/BLWH



DL-044 SQUARE
92DL044S2/GDWH



DL-044 SQUARE
92DL044S2/GDBL

IP20

DL-044 SQUARE

Catalogue number	Product category	Description	Colour	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
92DL044S2/BL	C	Downlight	black	210	110	110	1/10	A++→E
92DL044S2/BLWH	C	Downlight	black & white	210	110	110	1/10	A++→E
92DL044S2/GDWH	C	Downlight	gold & white	210	110	110	1/10	A++→E
92DL044S2/GDBL	C	Downlight	gold & black	210	110	110	1/10	A++→E

Body: Aluminium | **Lamps Not Included** | **Lamp holder:** GU10

RoHS COMPLIANT CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

FLCOM COB
White

FLCOM COB
Black

LED NEUTRAL WHITE 4000K **IP44**

FLCOM COB

Catalogue number WHITE	Catalogue number BLACK	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
92FLCOM1040/WH	**92FLCOM1040/BL**	C	10	800	4000	90	90	1/8	A++→A
92FLCOM2040/WH	**92FLCOM2040/BL**	C	20	1600	4000	110	125	1/8	A++→A
92FLCOM3040/WH	**92FLCOM3040/BL**	C	30	2400	4000	130	155	1/8	A++→A
92FLCOM4040/WH	**92FLCOM4040/BL**	C	40	3200	4000	170	185	1/8	A++→A

Voltage: 85-265V AC| **Body:** Aluminium | **Beam angle:** 60°| **Mounting:** surface

~230V | 50/60 Hz | COB | 60° | Ra>80 | 30000h | >20000 | INSTANT 100% | Hg | RoHS COMPLIANT | EMC | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

RECESED FIXTURES GLOM 222
92GLOM222WW

RDLOMCOB
92DLOM1040/S
92DLOM1027/S

RDLOMCOB
92DLOM2040/S
92DLOM2027/S

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | IP40

UNTIL SUPPLY LAST

RDLOMCOB / RECESED FIXTURES GLOM

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Length (mm)	Packing/Box (pcs)	Energy class
92DLOM1040/S	F	10	800	4000-4300	silver	95	70	1/24	A++→A
92DLOM1027/S	F	10	800	2700-3000	silver	95	70	1/24	A++→A
92DLOM2040/S	F	20	1600	4000-4300	silver	95	110	1/12	A++→A
92DLOM2027/S	F	20	1600	2700-3000	silver	95	110	1/12	A++→A
92GLOM222WW	F	18X1	1260	2700-3000K		165	115	1/1	A++→A





Body: aluminium | **Light source:** Epistar | **Power factor:** λ>0.9 | **Starting time:** <0.5s
LED surface round downlight COB.

~230V | 50/60 Hz | COB | 60° | Ra>80 | 30000h | >20000 | INSTANT 100% | Hg | IP 40 | RoHS COMPLIANT | EMC | F | CE | 3+0 standard +extended | 3 YEAR TOTAL WARRANTY

FRANCA 90
96FRANCA90/GR

FRANCA 90
96FRANCA90/BL

LED IP55 Resin

UNTIL SUPPLY LAST

FRANCA

Catalogue number BLACK body	Product category	Description	Colour	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Height (mm)	Lampholder	Packing/Box (pcs)	Energy class
96FRANCA90/BL	F	Ceiling fixtures	black	6	600	2700/4000 settable	95	115	1xGU10	1/30	A+ A++→A
96FRANCA90/GR	F	Ceiling fixtures	gray	6	600	2700/4000 settable	95	115	1xGU10	1/30	A+ A++→A

Body material: Resin| UV resistant | Lamp included

The product is accomplished with a LED bulb which parameters are noted in the chart. If you need any other color temperature or power, we suggest you to purchase the variants compatible to this fixtures separately as follows:

99XLED727 GU10 LED SMD 3.5W 4000K | **99XLED728** GU10 LED SMD 3.5W 2700K | **99XLED731** GU10 LED SMD 3.5W 6400K

99LED729 GU10 LED SMD 6.5W 4000K | **99LED730** GU10 LED SMD 6.5W 2700K | **99LED796** GU10 LED SMD 6.5W 6400K

~230V 50/60 Hz 1,5mm² RoHS 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 60 days.

TRACK LIGHTING

NOT FOLDING LED FLOODLIGHT, MINI SERIES

93MFL2230/BL
93MFL2240/BL

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | IP20 | Ra≥85 | 48V DC

FOUR POLES MAGNETIC LED FLOODLIGHT, MINI SERIES

Catalogue number WHITE	Product category Type		Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Beam angle	Length (mm)	Height (mm)	Packing/Box (pcs)	Energy class
93MFL2230/BL	C	Not folding	22	1672	3000	120°	585	118	1	A++→A
93MFL2240/BL	C	Not folding	22	1672	4000	120°	585	118	1	A++→A

Input Voltage: 48V | PF≥ 0.9 | **LED Source:** OSRAM | **Body material:** Aluminium | **Diffuser material:** PC | **Body colour:** Black

COB | 30000h | >20000 | 100% | RoHS COMPLIANT | EMC | CE | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

FOLDING LED FLOODLIGHT, MINI SERIES

93MFFL1230/BL
93MFFL1240/BL
93MFFL1830/BL
93MFFL1840/BL

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | IP20 | Ra≥85 | 48V DC

FOUR POLES MAGNETIC LED FLOODLIGHT, MINI SERIES

Catalogue number WHITE	Product category Type		Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Beam angle	Length (mm)	Height (mm)	Packing/Box (pcs)	Energy class
93MFFL1230/BL	C	Folding	12	856	3000	120°	200	118	1	A++→A
93MFFL1240/BL	C	Folding	12	856	4000	120°	200	118	1	A++→A
93MFFL1830/BL	C	Folding	18	1317	3000	120°	305	118	1	A++→A
93MFFL1840/BL	C	Folding	18	1317	4000	120°	305	118	1	A++→A

Input Voltage: 48V | PF≥ 0.9 | **LED Source:** OSRAM | **Body material:** Aluminium | **Diffuser material:** PC | **Body colour:** Black

COB | 30000h | >20000 | INSTANT 100% | Hg | RoHS COMPLIANT | EMC | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

FOUR POLES MAGNETIC LED GRILL LIGHT, MINI SERIES

93MFGL1230/BL
93MFGL1240/BL

FOUR POLES MAGNETIC LED GRILL LIGHT, MINI SERIES

93MFGL1830/BL
93MFGL1840/BL

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | IP20 | Ra≥85 | 48V DC

FOUR POLES MAGNETIC LED GRILL LIGHT, MINI SERIES

Catalogue number WHITE	Product category	Type	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Beam angle	Length (mm)	Height (mm)	Packing/Box (pcs)	Energy class
93MFGL1230/BL	C	Folding	12	835	3000	30°	200	118	1	A++→A
93MFGL1240/BL	C	Folding	12	835	4000	30°	200	118	1	A++→A
93MFGL1830/BL	C	Folding	18	1507	3000	30°	305	118	1	A++→A
93MFGL1840/BL	C	Folding	18	1507	4000	30°	305	118	1	A++→A

Input Voltage: 48V | LED Source: OSRAM | Body material: Aluminium | Body colour: Black

COB | 30000h | >20000 | INSTANT 100% | RoHS COMPLIANT | EMC | CE | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

FOUR POLES MAGNETIC LED LIGHT, MINI SERIES
93MTL0530/BL
93MTL0540/BL

FOUR POLES MAGNETIC LED LIGHT, MINI SERIES
93MTL1030/BL
93MTL1040/BL

FOUR POLES MAGNETIC LED LIGHT, MINI SERIES
93MTL1530/BL
93MTL1540/BL

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | IP20 | Ra≥85 | 48V DC

FOUR POLES MAGNETIC LED LIGHT, MINI SERIES

Catalogue number WHITE	Product category	Type	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Beam angle	Length (mm)	Diameter (mm)	Packing/Box (pcs)	Energy class
93MTL0530/BL	C	Folding	5	286	3000	38°	125	26	1	A++→A
93MTL0540/BL	C	Folding	5	286	4000	38°	125	26	1	A++→A
93MTL1030/BL	C	Folding	10	1230	3000	38°	160	55	1	A++→A
93MTL1040/BL	C	Folding	10	1230	4000	38°	160	55	1	A++→A
93MTL1530/BL	C	Folding	15	1692	3000	38°	200	45	1	A++→A
93MTL1540/BL	C	Folding	15	1692	4000	38°	200	45	1	A++→A

Input Voltage: 48V | PF≥ 0.9 | **LED Source:** CREE | **Body material:** Aluminium | **Body colour:** Black

COB | 30000h | >20000 | INSTANT 100% | Hg | RoHS COMPLIANT | EMC | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

FOUR POLES MAGNETIC LED HANGING LIGHT, MINI SERIES

93MPL1530/BL
93MPL1540/BL

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | IP20 | Ra≥85 | 48V DC

FOUR POLES MAGNETIC LED HANGING LIGHT, MINI SERIES

Catalogue number WHITE	Product category Type		Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Beam angle	Length (mm)	Diameter (mm)	Packing/Box (pcs)	Energy class
93MPL1530/BL	C	Hanging	15	1894	3000	38°	200	45	1	A++→A
93MPL1540/BL	C	Hanging	15	1894	4000	38°	200	45	1	A++→A

Input Voltage: 48V | PF≥ 0.9 | **LED Source:** CREE | **Body material:** Aluminium | **Body colour:** Black

COB | 30000h | >20000 | INSTANT 100% | Hg | RoHS COMPLIANT | EMC | CE | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

93MRBM1/BL

93MROM1/BL

93MA015
93MA011

93MA001

93MA002

93MA003

FOUR POLES 48V TRACK RAILS AND ACCESSORIES FOR MAGNETIC LIGHTS MINI SERIES

Catalogue number WHITE	Product category	Type	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)
93MROM1/BL	C	track rail OM	1000	30	53	1
93MROM2/BL	C	track rail OM	2000	30	53	1
93MRBM1/BL	C	track rail BM	1000	30	47	1
93MRBM2/BL	C	track rail BM	2000	30	47	1
93MA015	C	end cap for MRBM				1
93MA011	C	end cap for MROM				1
93MA001	C	L ceiling corner BM				1
93MA002	C	L wall ceiling corner BM				1
93MA003	C	L ceiling corner OM				1
93MA004	C	L wall ceiling corner OM				1
93MA013	C	T ceiling connector BM				1
93MA014	C	T ceiling connector OM				1

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

93MA006

93MA007

93MA008

93MA005

93MA010

93MA012

93MA009

FOUR POLES ACCESSORIES FOR MAGNETIC LIGHTS MINI SERIES

Catalogue number WHITE	Product category	Type	Packing/Box (pcs)
93MA005	C	I-flexible connector	1
93MA007	C	I-connector	1
93MA016	C	T-connector	1
93MA006	C	rail power adapter with cable 2x1.5mm²/0.5m	1
93MA008	C	fixture adaptor	1
93MA009	C	Inside connector	1
93MA010	C	mouting plate	1
93MA012	C	hanging wire 2m	1

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

TWO & FOUR LINES TRACK LIGHTS
K30 SERIES, LED CHIP OSRAM
93K302L12CCT/BL
93K304L12CCT/BL

TWO & FOUR LINES TRACK LIGHTS
K30 SERIES, LED CHIP OSRAM
93K302L24CCT/BL
93K304L24CCT/BL
93K302L48CCT/BL
93K304L48CCT/BL

LED 3000 K 4000 K 6000 K **IP40**

TWO & FOUR LINES TRACK LIGHTS K30 SERIES, LED CHIP OSRAM

Catalogue number	Product category	Type	Rail connectors	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Width (mm)	Height (mm)	Beam angle	Packing/Box (pcs)	Energy class
93K302L12CCT/BL	C	2 LINES	1	12	840	CCT- SETTABLE	281,5	42	127,7/71,7	120°	1/1	A++→A
93K302L24CCT/BL	C	2 LINES	2	24	1680	CCT- SETTABLE	562	42	127,7/71,7	120°	1/1	A++→A
93K302L48CCT/BL	C	2 LINES	2	48	3360	CCT- SETTABLE	1122	42	127,7/71,7	120°	1/1	A++→A
93K304L12CCT/BL	C	4 LINES	1	12	840	CCT- SETTABLE	281,5	42	127,7/71,7	120°	1/1	A++→A
93K304L24CCT/BL	C	4 LINES	2	24	1680	CCT- SETTABLE	562	42	127,7/71,7	120°	1/1	A++→A
93K304L48CCT/BL	C	4 LINES	2	48	3360	CCT- SETTABLE	1122	42	127,7/71,7	120°	1/1	A++→A

Input Voltage: 175 - 265V AC | **Body Material:** Alu | **Body colour:** Black | **LED Chip:** OSRAM | **CCT- Setabble:** 3000/4000/5700K

~230V 50/60 Hz Ra>80 30000h >20000 100% IP 40 RoHS EMC 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

HANGING LED FIXTURE K30 SERIES, LED CHIP OSRAM

LED 3000 K 4000 K 6000 K **IP40**

HANGING LED FIXTURE K30 SERIES, LED CHIP OSRAM

Catalogue number	Product category	Type	Rail connectors	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Width (mm)	Height (mm)	Beam angle	Packing/Box (pcs)	Energy class
93K30S48CCT/BL	C	HANGING	48	3360	CCT- SETTABLE	CCT- SETTABLE	1122	42	1500/71,7	120°	1/1	A++→A

Input Voltage: 175 - 265V AC | **Body Material:** Alu | **Body colour:** Black | **LED Chip:** OSRAM | **CCT- Setabble:** 3000/4000/5700K

~230V 50/60 Hz Ra>80 30000h >20000 100% IP 40 RoHS EMC 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

TWO & FOUR LINES TRACK LIGHTS
T30 SERIES, LED CHIP OSRAM
93T302L12CCT/BL
93T304L12CCT/BL

TWO & FOUR LINES TRACK LIGHTS
T30 SERIES, LED CHIP OSRAM
93T302L24CCT/BL
93T304L24CCT/BL

LED 3000 K 4000 K 6000 K **IP40**

TWO & FOUR LINES TRACK LIGHTS T30 SERIES SUPER SLIM, LED CHIP OSRAM

Catalogue number	Product category	Type	Rail connectors	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Width (mm)	Height (mm)	Beam angle	Packing/Box (pcs)	Energy class
93T302L12CCT/BL	C	2 LINES	1	12	1200	CCT- SETTABLE	281,5	42	115,4/59,4	30°	1/1	A++→A
93T302L24CCT/BL	C	2 LINES	2	24	2400	CCT- SETTABLE	562	42	115,4/59,4	30°	1/1	A++→A
93T304L12CCT/BL	C	4 LINES	1	48	1200	CCT- SETTABLE	281,5	42	115,4/59,4	30°	1/1	A++→A
93T304L24CCT/BL	C	4 LINES	1	12	2400	CCT- SETTABLE	562	42	115,4/59,4	30°	1/1	A++→A

Input Voltage: 175 - 265V AC | **Body Material:** Alu | **Body colour:** Black | **LED Chip:** OSRAM | **CCT- Setabble:** 3000/4000/5700K

~230V 50/60 Hz Ra>80 30000h >20000 INSTANT 100% IP 40 RoHS COMPLIANT EMC 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

TWO & FOUR LINES TRACK LIGHTS
B60 SERIES SUPER SLIM,
LED CHIP OSRAM
93B602L24CCT/BL
93B604L24CCT/BL

TWO & FOUR LINES TRACK LIGHTS
B60 SERIES SUPER SLIM,
LED CHIP OSRAM
93B602L42CCT/BL
93B604L42CCT/BL

IP40

TWO & FOUR LINES TRACK LIGHTS B60 SERIES SUPER SLIM, LED CHIP OSRAM

Catalogue number	Product category	Type	Rail connectors	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Width (mm)	Height (mm)	Beam angle	Packing/Box (pcs)	Energy class
93B602L24CCT/BL	C	2 LINES	1	24	2400	CCT- SETTABLE	287	65,5	82,4/22,5	60°	1/1	A++→A
93B602L42CCT/BL	C	2 LINES	1	42	4200	CCT- SETTABLE	562	65,5	82,4/22,5	60°	1/1	A++→A
93B604L24CCT/BL	C	4 LINES	1	24	2400	CCT- SETTABLE	281,5	65,5	82,4/22,5	60°	1/1	A++→A
93B604L42CCT/BL	C	4 LINES	1	42	4200	CCT- SETTABLE	562	65,5	82,4/22,5	60°	1/1	A++→A

Input Voltage: 175 - 265V AC | **Body Material:** Alu | **Body colour:** Black | **LED Chip:** OSRAM | **CCT- Setabble:** 3000/4000/5700K

3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

TWO & FOUR LINES TRACK HANGING LIGHT, TL29 SERIES

TWO & FOUR LINES TRACK HANGING LIGHT, TL29 SERIES

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | IP40

TWO & FOUR LINES TRACK HANGING LIGHT, TL29 SERIES

Catalogue number WHITE	Catalogue number BLACK	Product category	Type	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Length (mm)	Beam angle	Packing/Box (pcs)	Energy class
93TL292L10WW/WH	**93TL292L10WW/BL**	C	2 LINES	10	800	2700	60	300	24°	1/16	A++→A
93TL292L10W/WH	**93TL292L10W/BL**	C	2 LINES	10	800	4000	60	300	24°	1/16	A++→A
93TL292L15WW/WH	**93TL292L15WW/BL**	C	2 LINES	15	1500	2700	60	300	24°	1/9	A++→A
93TL292L15W/WH	**93TL292L15W/BL**	C	2 LINES	15	1500	4000	60	300	24°	1/9	A++→A
93TL292LGU10/WH	**93TL292LGU10/BL**	C	2 LINES	EMPTY GU10			60	300	24°	1/16	A++→E
93TL294LGU10/WH	**93TL294LGU10/BL**	C	4 LINES	EMPTY GU10			60	300	24°	1/16	A++→E
93TL294L10WW/WH	**93TL294L10WW/BL**	C	4 LINES	10	800	2700	80	300	24°	1/16	A++→A
93TL294L10W/WH	**93TL294L10W/BL**	C	4 LINES	10	800	4000	80	300	24°	1/16	A++→A
93TL294L15WW/WH	**93TL294L15WW/BL**	C	4 LINES	15	1500	2700	80	300	24°	1/9	A++→A
93TL294L15W/WH	**93TL294L15W/BL**	C	4 LINES	15	1500	4000	80	300	24°	1/9	A++→A

Input Voltage: 175 - 265V AC | **Body Material:** Alu | **LED Chip:** COB SABAN

~230V | 50/60 Hz | Ra>80 | 30000h | >20000 | 100% | IP 40 | RoHS | EMC | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

TWO LINES SKY TL5016

TWO LINES TRACK LIGHTS SKY TLS

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | COOL WHITE 6400K | IP40

UNTIL SUPPLY LAST

TWO LINES SKY TL5016

Catalogue number BLACK	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Height (mm)	Beam angle	Packing/Box (pcs)	Energy class
93TL5016CW/BL	F	30	2400	6400	120	140	36°	1/34	A++→A

Body: aluminium

~230V | 50/60 Hz | COB | Ra>80 | 30000h | >20000 | INSTANT 100% | Hg | IP 40 | RoHS COMPLIANT | EMC | F | CE | 3+0 standard +extended | 3 YEAR TOTAL WARRANTY

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | COOL WHITE 6400K | IP40

UNTIL SUPPLY LAST

TWO LINES TRACK LIGHTS SKY TLS

Catalogue number WHITE	Catalogue number BLACK	Catalogue number GREY	Product category	Type	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Body material	Diameter (mm)	Height (mm)	Beam angle	Packing/ Box (pcs)	Energy class
93TLS503W/WH			F	2 LINES	10	900	4000	aluminium	142	105	24°	1/12	A++→A
93TLS503CW/WH		**93TLS503CW/GR**	F	2 LINES	10	900	6400	aluminium	142	105	24°	1/12	A++→A
		93TLS504W/GR	F	2 LINES	15	1350	4000	aluminium	142	105	24°	1/12	A++→A
93TLS504CW/WH	**93TLS504CW/BL**	**93TLS504CW/GR**	F	2 LINES	15	1350	6400	aluminium	142	105	24°	1/12	A++→A

SKY TLR

SKY TLR

~230V | 50/60 Hz | COB | Ra>80 | 30000h | >20000 | INSTANT 100% | Hg | IP 40 | RoHS COMPLIANT | EMC | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

TWO & FOUR LINES SKY TL5

White / Black

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | **IP40**

TWO & FOUR LINES SKY TL5

Catalogue number WHITE	Catalogue number BLACK	Product category	Type	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Height (mm)	Beam angle	Packing/Box (pcs)	Energy class
93TL5LEDW/WH	**93TL5LEDW/BL**	C	2 LINES	7	500	4000	57	147	40°	1/100	A+ A++→E
93TL5LEDWW/WH	**93TL5LEDWW/BL**	C	2 LINES	7	500	2700	57	147	40°	1/100	A+ A++→E
93TL5	**93TL5LEDBL**	C	2 LINES EMPTY				57	147		1/100	A++→E
94TL5LEDW/WH	**94TL5LEDW/BL**	C	4 LINES	7	500	4000	57	147	40°	1/100	A+ A++→E
94TL5LEDWW/WH	**94TL5LEDWW/BL**	C	4 LINES	7	500	2700	57	147	40°	1/100	A+ A++→E
94TL5	**94TL5LEDBL**	C	4 LINES EMPTY				57	147		1/100	A++→E

Body: aluminium | **Lampholder:** GU10

The product is accomplished with a LED bulb which parameters are noted in the chart. If you need any other color temperature or power, we suggest you to purchase the variants compatible to this fixtures separately as follows:

99XLED727 GU10 LED SMD 3.5W 4000K | **99XLED728** GU10 LED SMD 3.5W 2700K | **99XLED731** GU10 LED SMD 3.5W 6400K | **99LED729** GU10 LED SMD 6.5W 4000K | **99LED796** GU10 LED SMD 6.5W 6400K

~230V | 50/60 Hz | Ra>80 | 30000h | >20000 | 100% | IP 40 | RoHS | EMC | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

TWO & FOUR LINES SKY TL2032
White

TWO & FOUR LINES SKY TL2032
Black

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP40**

TWO & FOUR LINES SKY TL2032

Catalogue number WHITE	Catalogue number BLACK	Product category	Type	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Length (mm)	Height (mm)	Packing/Box (pcs)	Energy class
93TL2032/WH	**93TL2032/BL**	C	2 LINES EMPTY				55	84	162	1/80	A++→E
93TL2032WW/WH	**93TL2032WW/BL**	C	2 LINES	6,5	585	2700	55	84	162	1/80	A+ A++→E
93TL2032W/WH	**93TL2032W/BL**	C	2 LINES	6,5	585	4000	55	84	162	1/80	A+ A++→E
93TL2032CW/WH	**93TL2032CW/BL**	C	2 LINES	6,5	585	6400	55	84	162	1/80	A+ A++→E
94TL2032/WH	**94TL2032/BL**	C	4 LINES EMPTY				55	84	162	1/80	A++→E
94TL2032WW/WH	**94TL2032WW/BL**	C	4 LINES	6,5	585	2700	55	84	162	1/80	A+ A++→E
94TL2032W/WH	**94TL2032W/BL**	C	4 LINES	6,5	585	4000	55	84	162	1/80	A+ A++→E
94TL2032CW/WH	**94TL2032CW/BL**	C	4 LINES	6,5	585	6400	55	84	162	1/80	A+ A++→E

Body: iron | **Lampholder:** GU10

The product is accomplished with a LED bulb which parameters are noted in the chart. If you need any other color temperature or power, we suggest you to purchase the variants compatible to this fixtures separately as follows:

99XLED727 GU10 LED SMD 3.5W 4000K | **99XLED728** GU10 LED SMD 3.5W 2700K | **99XLED731** GU10 LED SMD 3.5W 6400K | **99LED729** GU10 LED SMD 6.5W 4000K | **99LED796** GU10 LED SMD 6.5W 6400K

~230V | 50/60 Hz | Ra>80 | 30000h | >20000 | INSTANT 100% | Hg | IP 40 | RoHS COMPLIANT | EMC | CE | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

TWO & FOUR LINES SKY TL2044
White

TWO & FOUR LINES SKY TL2044
Black

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP40**

TWO & FOUR LINES SKY TL2044

Catalogue number WHITE	Catalogue number BLACK	Product category	Type	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Length (mm)	Height (mm)	Packing/Box (pcs)	Energy class
93TL2044/WH	**93TL2044/BL**	C	2 LINES EMPTY				56	86	135	1/80	A++→E
93TL2044WW/WH	**93TL2044WW/BL**	C	2 LINES	6,5	585	2700	56	86	135	1/80	A+ A++→E
93TL2044W/WH	**93TL2044W/BL**	C	2 LINES	6,5	585	4000	56	86	135	1/80	A+ A++→E
93TL2044CW/WH	**93TL2044CW/BL**	C	2 LINES	6,5	585	6400	56	86	135	1/80	A+ A++→E
94TL2044/WH	**94TL2044/BL**	C	4 LINES EMPTY				56	86	135	1/80	A++→E
94TL2044WW/WH	**94TL2044WW/BL**	C	4 LINES	6,5	585	2700	56	86	135	1/80	A+ A++→E
94TL2044W/WH	**94TL2044W/BL**	C	4 LINES	6,5	585	4000	56	86	135	1/80	A+ A++→E
94TL2044CW/WH	**94TL2044CW/BL**	C	4 LINES	6,5	585	6400	56	86	135	1/80	A+ A++→E

Body: iron | **Lampholder:** GU10

The product is accomplished with a LED bulb which parameters are noted in the chart. If you need any other color temperature or power, we suggest you to purchase the variants compatible to this fixtures separately as follows:

99XLED727 GU10 LED SMD 3.5W 4000K | **99XLED728** GU10 LED SMD 3.5W 2700K | **99XLED731** GU10 LED SMD 3.5W 6400K | **99LED729** GU10 LED SMD 6.5W 4000K | **99LED796** GU10 LED SMD 6.5W 6400K

~230V | 50/60 Hz | Ra>80 | 30000h | >20000 | INSTANT 100% | Hg | IP 40 | RoHS COMPLIANT | EMC | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

TWO AND FOUR LINES SKY TL2025
White

TWO AND FOUR LINES SKY TL2025
Black

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | **IP40**

TWO AND FOUR LINES SKY TL2025

Catalogue number WHITE	Catalogue number BLACK	Product category	Type	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Height (mm)	Beam angle	Packing/Box (pcs)	Energy class
93TL202520WW/WH	**93TL202520WW/BL**	C	2 LINES	20	1400	2700	60	160	24°	1/40	A++→A
93TL202520W/WH	**93TL202520W/BL**	C	2 LINES	20	1400	4000	60	160	24°	1/40	A++→A
93TL202530WW/WH	**93TL202530WW/BL**	C	2 LINES	30	2000	2700	75	180	24°	1/30	A++→A
93TL202530W/WH	**93TL202530W/BL**	C	2 LINES	30	2000	4000	75	180	24°	1/30	A++→A
94TL202520WW/WH	**94TL202520WW/BL**	C	4 LINES	20	1400	2700	60	160	24°	1/40	A++→A
94TL202520W/WH	**94TL202520W/BL**	C	4 LINES	20	1400	4000	60	160	24°	1/40	A++→A
94TL202530WW/WH	**94TL202530WW/BL**	C	4 LINES	30	2000	2700	75	180	24°	1/30	A++→A
94TL202530W/WH	**94TL202530W/BL**	C	4 LINES	30	2000	4000	75	180	24°	1/30	A++→A

Body: aluminium | **Voltage:** 185-265 V AC | **Driver:** Non-isoalted

~230V | 50/60 Hz | COB | Ra>80 | 30000h | >20000 | INSTANT 100% | IP 40 | RoHS COMPLIANT | EMC | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

TWO & FOUR LINES SKY FTL
black

TWO & FOUR LINES SKY FTL
white

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP40**

TWO AND FOUR LINES SKY FTL

Catalogue number WHITE	Catalogue number BLACK	Product category	Type	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Length (mm)	Height (mm)	Beam angle	Packing/Box (pcs)	Energy class
93FTL25WW/WH	**93FTL25WW/BL**	C	2 LINES	25	2250	3000K	100	140	235	38°	1/20	A++→A
93FTL25W/WH	**93FTL25W/BL**	C	2 LINES	25	2250	4000K	100	140	235	38°	1/20	A++→A
93FTL25CW/WH	**93FTL25CW/BL**	C	2 LINES	25	2250	6000K	100	140	235	38°	1/20	A++→A
93FTL35WW/WH	**93FTL35WW/BL**	C	2 LINES	35	3150	3000K	100	140	235	38°	1/20	A++→A
93FTL35W/WH	**93FTL35W/BL**	C	2 LINES	35	3150	4000K	100	140	235	38°	1/20	A++→A
93FTL35CW/WH	**93FTL35CW/BL**	C	2 LINES	35	3150	6000K	100	140	235	38°	1/20	A++→A
934FTL25WW/WH	**934FTL25WW/BL**	C	4 LINES	25	2250	3000K	100	140	235	38°	1/20	A++→A
934FTL25W/WH	**934FTL25W/BL**	C	4 LINES	25	2250	4000K	100	140	235	38°	1/20	A++→A
934FTL25CW/WH	**934FTL25CW/BL**	C	4 LINES	25	2250	6000K	100	140	235	38°	1/20	A++→A
934FTL35WW/WH	**934FTL35WW/BL**	C	4 LINES	35	3150	3000K	100	140	235	38°	1/20	A++→A
934FTL35W/WH	**934FTL35W/BL**	C	4 LINES	35	3150	4000K	100	140	235	38°	1/20	A++→A
934FTL35CW/WH	**934FTL35CW/BL**	C	4 LINES	35	3150	6000K	100	140	235	38°	1/20	A++→A

Body: aluminium

side view black

back view black

side view white

back view white

93SKY01/W

CONNECTOR
TWO LINES RAILS
White: 93SKY01/W
Black: 93SKY01/BL
Grey: 93SKY01/G

93SKY03/W

CONNECTOR
FOUR LINES RAILS
White: 93SKY03/W
Black: 93SKY03/BL

~230V | 50/60 Hz | COB | Ra>80 | 30000h | >20000 | INSTANT 100% | Hg | IP 40 | RoHS COMPLIANT | EMC | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

TWO LINES SKY TL5030
White / Black / Grey

TWO LINES SKY TL5020
White / Black / Grey

LED WARM WHITE 2700K NEUTRAL WHITE 4000K COOL WHITE 6400K **IP40**

TWO LINES SKY TL 20W

Catalogue number WHITE	Catalogue number BLACK	Catalogue number GREY*	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Height (mm)	Beam angle	Packing/ Box (pcs)	Energy class
93TL5020W/WH	**93TL5020W/BL**		C	20	1800	4000	93	125	36°	1/20	A++→A
93TL5020WW/WH	**93TL5020WW/BL**		C	20	1800	2700	93	125	36°	1/20	A++→A
93TL5020CW/WH	**93TL5020CW/BL**	**93TL5020CW/GR**	C	20	1800	6400	93	125	36°	1/20	A++→A

* Until Supply Last

LED WARM WHITE 2700K NEUTRAL WHITE 4000K COOL WHITE 6400K **IP40**

UNTIL SUPPLY LAST

TWO LINES SKY TL 30W

Catalogue number WHITE	Catalogue number BLACK	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Height (mm)	Beam angle	Packing/Box (pcs)	Energy class
	93TL5030CW/BL	F	30	2700	6400	93	125	36°	1/20	A++→A

Body: aluminium

~230V 50/60 Hz COB Ra>80 30000h >20000 INSTANT 100% Hg IP40 RoHS EMC F CE 2+0 standard +extended 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

SKY TL809
White / Black / Grey

SKY TL808
White / Black / Grey

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP40**

TWO AND FOUR LINES SKY TL

Catalogue number WHITE	Catalogue number BLACK	Product category	Type	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Diameter (mm)	Height (mm)	Beam angle	Packing/Box (pcs)	Energy class
93TL809/WH	**93TL809/BL**	C	2L TL809			empty fixture	130	95	180		1/1	A++→E
93SKY1540		C	2L TL809	15	1275	4000	130	95	180	90°	1/1	A+ A++→E
93SKY1527		C	2L TL809	15	1275	2700	130	95	180	90°	1/1	A+ A++→E
93SKY1564		C	2L TL809	15	1275	6400	130	95	180	90°	1/1	A+ A++→E
93SKY3540	**93SKY4540**	C	2L TL808	15	1275	4000	150	100	210	90°	1/1	A+ A++→E
93SKY3527	**93SKY4527**	C	2L TL808	15	1275	2700	150	100	210	90°	1/1	A+ A++→E
93SKY3564	**93SKY4564**	C	2L TL808	15	1275	6400	150	100	210	90°	1/1	A+ A++→E
94SKY1540		C	4L TL809	15	1275	4000	130	95	180	90°	1/1	A+ A++→E
94SKY1527		C	4L TL809	15	1275	2700	130	95	180	90°	1/1	A+ A++→E
94SKY1564		C	4L TL809	15	1275	6400	130	95	180	90°	1/1	A+ A++→E
94SKY3540	**94SKY4540**	C	4L TL808	15	1275	4000	150	100	210	90°	1/1	A+ A++→E
94SKY3527	**94SKY4527**	C	4L TL808	15	1275	2700	150	100	210	90°	1/1	A+ A++→E
94SKY3564	**94SKY4564**	C	4L TL808	15	1275	6400	150	100	210	90°	1/1	A+ A++→E

15 W Lamp

white colour

black colour

Body: aluminium | **Light source:** LED lamp PAR30 | **Power factor:** λ>0.9 | **Starting time:** <1s

~230V | 50/60 Hz | COB | Ra>80 | 30000h | >20000 | INSTANT 100% | Hg | IP 40 | RoHS | EMC | 3+0 standard +extended 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

TWO & FOUR LINES CINEMA SKY
White / Black / Grey

TWO & FOUR LINES CINEMA SKY
White / Black / Grey

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP40**

TWO AND FOUR LINES CINEMA SKY

Catalogue number WHITE	Catalogue number BLACK	Catalogue number GREY	Product category	Type	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Height (mm)	Beam angle	Packing/ Box	Energy class
955CINEMA15W/WH	**955CINEMA15W/BL**	**955CINEMA15W/GR**	C	2L extendible	15	1275	4000	145	220	90°	1/6	A+ A++→E
955CINEMA15WW/WH	**955CINEMA15WW/BL**	**955CINEMA15WW/GR**	C	2L extendible	15	1275	2700	145	220	90°	1/6	A+ A++→E
955CINEMA15CW/WH	**955CINEMA15CW/BL**	**955CINEMA15CW/GR**	C	2L extendible	15	1275	6400	145	220	90°	1/6	A+ A++→E
955CINEMA115W/WH	**955CINEMA115W/BL**	**955CINEMA115W/GR**	C	2L fixed	15	1275	4000	145	220	90°	1/6	A+ A++→E
955CINEMA115WW/WH	**955CINEMA115WW/BL**	**955CINEMA115WW/GR**	C	2L fixed	15	1275	2700	145	220	90°	1/6	A+ A++→E
955CINEMA115CW/WH	**955CINEMA115CW/BL**	**955CINEMA115CW/GR**	C	2L fixed	15	1275	6400	145	220	90°	1/6	A+ A++→E
94CINEMA15W/WH	**94CINEMA15W/BL**		C	4L extendible	15	1275	4000	145	220	90°	1/6	A+ A++→E
94CINEMA15WW/WH	**94CINEMA15WW/BL**		C	4L extendible	15	1275	2700	145	220	90°	1/6	A+ A++→E
94CINEMA15CW/WH	**94CINEMA15CW/BL**		C	4L extendible	15	1275	6400	145	220	90°	1/6	A+ A++→E
94CINEMA115W/WH	**94CINEMA115W/BL**		C	4L fixed	15	1275	4000	145	220	90°	1/6	A+ A++→E
94CINEMA115WW/WH	**94CINEMA115WW/BL**		C	4L fixed	15	1275	2700	145	220	90°	1/6	A+ A++→E
94CINEMA115CW/WH	**94CINEMA115CW/BL**		C	4L fixed	15	1275	6400	145	220	90°	1/6	A+ A++→E

15 W Lamp

white colour

grey colour

black colour

Body: aluminium | **Light source:** LED lamp PAR30 | **Power factor:** λ>0.9 | **Starting time:** <1s

~230V | 50/60 Hz | COB | Ra>80 | 30000h | >20000 | INSTANT 100% | Hg | IP 40 | RoHS COMPLIANT | EMC | CE | 3+0 standard +extended | 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

TWO & FOUR LINES SKY
TL 2211

White / Black

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP40**

UNTIL SUPPLY **LAST**

TWO AND FOUR LINES SKY TL 2211

Catalogue number WHITE	Product category	Type	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Diameter (mm)	Height (mm)	Beam angle	Packing/Box	Energy class
93SKY2215WW/WH	F	2 LINES	15	1275	2700	235	100	160	90°	1/6	A+ A++→E
93SKY2215W/WH	F	2 LINES	15	1275	4000	235	100	160	90°	1/6	A+ A++→E
93SKY2215CW/WH	F	2 LINES	15	1275	6400	235	100	160	90°	1/6	A+ A++→E
94SKY2215WW/WH	F	4 LINES	15	1275	2700	230	100	160	90°	1/1	A+ A++→E
94SKY2215W/WH	F	4 LINES	15	1275	4000	230	100	160	90°	1/1	A+ A++→E
94SKY2215CW/WH	F	4 LINES	15	1275	6400	230	100	160	90°	1/1	A+ A++→E

15 W Lamp

93SKY03/W

CONNECTOR
FOUR LINES RAILS
White: 93SKY03/W
Black: 93SKY03/BL

Body: aluminium | **Light source:** LED lamp PAR30 | **Power factor:** λ>0.9 | **Starting time:** <1s

~230V | 50/60 Hz | SMD 2835 | Ra>80 | 30000h | >20000 | INSTANT 100% | Hg | IP 40 | RoHS | EMC | F | CE | 3+0 standard +extended | 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

SKY FIXTURES TLOM
White / Black

SKY FIXTURES TLBM
White / Black

LED NEUTRAL WHITE 4000K **IP40**

SKY FIXTURES TLOM / TLBM

Catalogue number WHITE	Catalogue number BLACK	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Body material	Diameter (mm)	Height (mm)	Beam angle	Packing/Box (pcs)	Energy class
93TLOM1540/WH	**93TLOM1540/BL**	C	15	1350	4000K	Aluminum	55	145	24°	1/24	A++→A
93TLOM3040/WH	**93TLOM3040/BL**	C	30	2700	4000K	Aluminum	90	240	24°	1/15	A++→A
93TLBM1540/WH	**93TLBM1540/BL**	C	15	1350	4000K	Aluminum	73	118	30°	1/50	A++→A

TLBM



TLBM

~230V 50/60 Hz COB Ra>80 30000h >20000 INSTANT 100% Hg IP 40 RoHS COMPLIANT EMC F CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

SINGLE-PHASE RAILS

ADAPTER POWER SUPPLY



I - TYPE

L - TYPE

T - TYPE

X - TYPE

IP20

TWO LINES TRACK RAILS AND ADAPTERS

Catalogue number WHITE	Catalogue number BLACK	Catalogue number GREY*	Product category	Type	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)
93101	**93301**	**93501**	C	SKYWAY 101 track rails	1000	40	20	1/20
93102	**93302**		C	SKYWAY 102 track rails	2000	40	20	1/20
93110	**93310**		C	SKYWAY 110 I-type adapter	80	40	20	1/100
93120	**93320**	**93520**	C	SKYWAY 120 L-type adapter	70	40	20	1/100
93130	**93330**	**93530**	C	SKYWAY 130 T-type adapter	106	40	20	1/100
93140	**93340**	**93540**	C	SKYWAY 140 X-type adapter	106	40	20	1/100

Body material: aluminium
* Until Supply Last: Product category F

~230V | 50/60 Hz | max. 10A | IP 20 | RoHS COMPLIANT | F | CE

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

POWER SUPPLY

I - TYPE

L - TYPE

SOFT L - TYPE

FOUR LINES TRACK RAILS



T - TYPE



X - TYPE

IP20

FOUR LINES TRACK RAILS AND ADAPTERS

Catalogue number WHITE	Catalogue number BLACK	Product category	Type	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)
94101	**94301**	C	four lines track rails*	1000	33.5	42	1/10
94102	**94302**	C	four lines track rails*	2000	33.5	42	1/10
94110	**94310**	C	four line I-type connector	160	30	42	1/50
94120	**94320**	C	four line L-type connector	100	30	100	1/70
94120M	**94320M**	C	four line soft L-type connector	100	30	100	1/70
94130	**94330**	C	four line T-type connector	160	30	100	1/50
94140	**94340**	C	four line X-type connector	160	30	160	1/25
94150	**94350**	C	four line power supply	160	30	42	1/100
94160	**94360**	C	end cap				1/100

Material: track rails- aluminium | **Accessories:** ABS antiflaming + cooper sheet

*four lines track rails come without power supply

~230V | 50/60 Hz | max. 10A | IP 20 | RoHS COMPLIANT | F | CE

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

MH 2000
982000150

MH 2001
98200170
98200170FSCH

IP21

UNTIL SUPPLY LAST

MH 2000/2001

Catalogue number	Product category	Model	Watt (W)	Lamp	Colour body	Length (mm)	Width (mm)	Diameter/Height (mm)	Energy class
982000150	F	MH 2000	-	-	white	370	185	190	A++→C
98200170	F	MH 2001	-	-	white	190	215	240	A++→C
98200170FSCH	F	MH 2001	70	MHL	white	190	215	240	A++→C

Body: aluminium casting | **Ambient Temperature:** -30°C÷ +65°C | **Diffuser:** Tempered glass | Lamp not included

~230V | 50/60 Hz | Rx7s | IP 21 | RoHS | F | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

NEUTRAL WHITE 4000K

IP44

COMERCIAL LED FIXTURES TRITON

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Beam angle	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
99TR602640/GR	C	26	3120	4000	90°	grey	600	90	57,6	1/1	A++→A
99TR903840/GR	C	38	4560	4000	90°	grey	900	90	57,6	1/1	A++→A
99TR1205040/GR	C	50	6000	4000	90°	grey	1200	90	57,6	1/1	A++→A
99TR1506440/GR	C	64	7680	4000	90°	grey	1500	90	57,6	1/1	A++→A



INSTALATION ACCESSORIES FOR LED PROFILES
Suspension wire
Catalogue number: **99ACC54**

As per personal request, COMERCIAL LED FIXTURES TRITON can be produced with beam angle of 30°, 60° , 25°/25°.



Sharp distribution apply to focusing on objects with tight gap.
Mount up to 20 meters



Narrow distribution apply to narrow passageway.
Mount up to 10 meters



Wide distribution apply to wider passageway.
Mount up to 6 meters



Double asymmetric distribution apply to large gap between shelves.
Mount up to 3 meters



Body: aluminium | **Reflector:** polycarbonate (PC)

~230V | 50/60 Hz | SMD | 90° | Ra≥80 | >15000 | INSTANT 100% | 50000h | Hg | IP 44 | RoHS COMPLIANT | EMC | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 30 days.

COMMERCIAL LED FIXTURES

95204609
95204550

LED NEUTRAL WHITE 4000K **IP40**

COMMERCIAL LED FIXTURES

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Beam angle	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95204609	F	9*	820	4000	aluminium	90°	610	65	40	1/10	A++→A
95204550	C	50	4800	4000	aluminium	120°	1200	75	35	1/10	A++→A

Body: Alu+PC | **Light source:** SMD2835| **Input voltage:** 220-240V | **Mounting:** Surface

* Until Supply Last - 3 year standard + extended warranty



Wire and fittings for hanging mounting 2,5m
2 pcs/ pack
92ACC03

Body: Alu+PC | **Light source:** SMD2835| **Input voltage:** 220-240V | **Mounting:** Surface

~230V | 50/60 Hz | SMD | Ra≥80 | >20000 | 100% | 20000h | Hg | IP 40 | RoHS | EMC | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.



LED MOD FIXTURE
9MOD18W
9MOD36W

CONNECTOR 90° L-TYPE
9MODL

COUPLING 180° I-TYPE
9MODI

T-JOINT
9MODT

LED NEUTRAL WHITE 4000K **IP40**

MOD FIXTURE

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
9MOD18W	C	18	1100	4000	white	615	54	34	1/20	A++>A
9MOD36W	C	36	2200	4000	white	1215	54	34	1/20	A++>A

Connector 90° L-type

Catalogue number
9MODL
135x135x45mm

Coupling 180° I-type

Catalogue number
9MODI
210x58x45mm

T-joint

Catalogue number
9MODT
210x135x45mm

Body: PC+Iron | **Clips:** inox | **Light source:** Sanan 2835 SMD| **Starting time:** <1s

~230V | 50/60 Hz | SMD | 120° | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | IP 40 | RoHS COMPLIANT | EMC | 3+0 standard +extended | 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

REMY STELLAR

9XREMY18LED
9XREMY18LED/CW
9XREMY36LED
9XREMY36LED/CW

LED NEUTRAL WHITE 4000K **IP40**

REMY LUMINAIRE STELLAR

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
9XREMY18LED	C	18	1650	4000K	white	600	75	46	1/20	A++→A
9XREMY18LED/CW	C	18	1650	6400K	white	600	75	46	1/20	A++→A
9XREMY36LED	C	36	3300	4000K	white	1200	75	46	1/20	A++→A
9XREMY36LED/CW	C	36	3300	6400K	white	1200	75	46	1/20	A++→A

Body: PP+PC | **LED driver:** mounted in the body | **Light source:** SMD2835 | **Input voltage:** 220-240V | **Beam angle:** 115°

~230V | 50/60 Hz | SMD | Ra≥80 | >20000 | INSTANT 100% | 15000h | Hg | IP 40 | RoHS COMPLIANT | EMC | 2+0 standard +extended 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.



ACOUSTIC BAFFLES

Catalogue number	Product category	Colour	Material	Acoustic rating	Length (mm)	Height (mm)	Depth (mm)
99ACOUSTIC1200/BL	C	Black	Polyester	0.85 NRC	1200	200	9
99ACOUSTIC1200/WH	C	White	Polyester	0.85 NRC	1200	200	9
99ACOUSTIC1200/GR	C	Grey	Polyester	0.85 NRC	1200	200	9
99ACOUSTIC2400/BL	C	Black	Polyester	0.85 NRC	2400	200	9
99ACOUSTIC2400/WH	C	White	Polyester	0.85 NRC	2400	200	9
99ACOUSTIC2400/GR	C	Grey	Polyester	0.85 NRC	2400	200	9

Acoustic sound baffle find application in many work and office spaces, conference and presentation halls, meeting rooms, retails, institutional and more. They significantly reduce noise pollution, minimizing reverberation and echo in the room, absorbing any reflect sounds from other surfaces, thereby increasing speech intelligibility and communication. They are mounted on the ceiling in rows or columns.

Features: High quality and easy mounting | Lightweight | Safe and non-toxic | Available in three colours | Possibilty to create custom design

Mounting: Hanging. Attach one piece of wire/cord onto each of the 2 eye hooks on the baffle.Then attach the other end of the wire to two equally-spaced hooks in the ceiling

RoHS COMPLIANT CE

The products are not held on stock and are supplied only by a customer`s request.



LED NEUTRAL WHITE 4000K **IP40** **HIGH POWER**

ACOUSTIC HIGH POWER LED PROFILES S36 SERIES FOR HANGING MOUNTING

Catalogue number BLACK	Catalogue number WHITE	Catalogue number GREY	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Height (mm)	Width (mm)	Packing/Box (pcs)	Energy class
99SM36S4020A/BL	**99SM36S4020A/WH**	**99SM36S4020A/GR**	C	20	1600	4000	600	200	55	1/1	A++→A
99SM36S4040A/BL	**99SM36S4040A/WH**	**99SM36S4040A/GR**	C	40	3200	4000	1200	200	55	1/1	A++→A
99SM36S4050A/BL	**99SM36S4050A/WH**	**99SM36S4050A/GR**	C	50	4000	4000	1500	200	55	1/1	A++→A



INSTALATION ACCESSORIES FOR LED PROFILES
Suspension wire
Catalogue number: **99ACC51**
Suspension wire with console
Catalogue number: **99ACC52**

Body: aluminium | **Reflector:** polycarbonate (PC) | **Driver:** 42V SELV driver | **Light Source:** SAMSUNG

~230V 50/60 Hz SMD 90° Ra≥80 >15000 INSTANT 100% 20000h Hg IP 40 RoHS EMC F CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

The products are not held on stock and are supplied only by a customer`s request.

NEUTRAL WHITE 4000K

IP40

ACOUSTIC LED RINGS

Catalogue number BLACK	Catalogue number WHITE	Catalogue number GREY	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
99RING6004035A/BL	**99RING6004035A/WH**	**99RING6004035A/GR**	C	35	3500	4000	600	25	1/1	A++→A
99RING8004060A/BL	**99RING8004060A/WH**	**99RING8004060A/GR**	C	42	4200	4000	800	25	1/1	A++→A
99RING10004075A/BL	**99RING10004075A/WH**	**99RING10004075A/GR**	C	50	5000	4000	1000	25	1/1	A++→A
99RING11504096A/BL	**99RING11504096A/WH**	**99RING11504096A/GR**	C	63	6300	4000	1150	25	1/1	A++→A

99ACC52 99ACC51

Body: aluminium | **Reflector:** polycarbonate (PC) | **Driver:** 42V SELV driver

~230V 50/60 Hz SMD 90° Ra≥80 >15000 INSTANT 100% 20000h Hg IP 40 RoHS EMC F CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

The products are not held on stock and are supplied only by a customer`s request.

LED RINGS
99RING8004060/GR

LED RINGS
99RING6004035/BL

LED NEUTRAL WHITE 4000K **IP40**

LED RINGS

Catalogue number BLACK	Catalogue number WHITE	Catalogue number GREY	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
99RING6004035/BL	**99RING6004035/WH**	**99RING6004035/GR**	C	35	3500	4000	600	25	1/1	A++→A
99RING8004060/BL	**99RING8004060/WH**	**99RING8004060/GR**	C	42	4200	4000	800	25	1/1	A++→A
99RING10004075/BL	**99RING10004075/WH**	**99RING10004075/GR**	C	50	5000	4000	1000	25	1/1	A++→A
99RING11504096/BL	**99RING11504096/WH**	**99RING11504096/GR**	C	63	6300	4000	1150	25	1/1	A++→A

Body: aluminium | **Reflector:** polycarbonate (PC) | **Driver:** 42V SELV driver

99ACC52 99ACC51

~230V | 50/60 Hz | SMD | 90° | Ra≥80 | >15000 | INSTANT 100% | 20000h | Hg | IP 40 | RoHS COMPLIANT | EMC | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 30 days.



LED | NEUTRAL WHITE 4000K | **IP40** | **ULTRA THIN**

ULTRA THIN LED PROFILES S36 SERIES, RECESSED MOUNTING

Catalogue number BLACK	Catalogue number WHITE	Catalogue number GREY	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Width 1 (mm)	Width 2 (mm)	Height (mm)	Packing/Box (pcs)	Energy class
99FM36S4009/BL	**99FM36S4009/WH**	**99FM36S4009/GR**	C	9	630	4000	600	47.74	35.33	13.5	1/1	A++→A
99FM36S4018/BL	**99FM36S4018/WH**	**99FM36S4018/GR**	C	18	1260	4000	1200	47.74	35.33	13.5	1/1	A++→A
99FM36S40225/BL	**99FM36S40225/WH**	**99FM36S40225/GR**	C	22.5	1575	4000	1500	47.74	35.33	13.5	1/1	A++→A



Body: aluminium | **Reflector:** polycarbonate (PC) | **Clamps:** inox | **Driver:** 24V | **Light Source:** SAMSUNG

~230V | 50/60 Hz | SMD | 90° | Ra≥80 | >15000 | INSTANT 100% | 20000h | Hg | IP 40 | RoHS COMPLIANT | EMC | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 30 days.



LED NEUTRAL WHITE 4000K **IP40**

LED PROFILES S48 SERIES RECESSED MOUNTING WITH EMERGENCY KIT

Catalogue number BLACK	Catalogue number WHITE	Catalogue number GREY	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Width 1 (mm)	Width 2 (mm)	Height (mm)	Packing/Box (pcs)	Energy class
99FM604012/BLE	**99FM604012/WHE**	**99FM604012/GRE**	C	12	1140	4000	600	70	47.8	22.4	1/1	A++→A
99FM1204024/BLE	**99FM1204024/WHE**	**99FM1204024/GRE**	C	24	2280	4000	1200	70	47.8	22.4	1/1	A++→A
99FM1504032/BLE	**99FM1504032/WHE**	**99FM1504032/GRE**	C	32	3040	4000	1500	70	47.8	22.4	1/1	A++→A

LED NEUTRAL WHITE 4000K **IP40**

LED PROFILES S48 SERIES RECESSED MOUNTING

Catalogue number BLACK	Catalogue number WHITE	Catalogue number GREY	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Width 1 (mm)	Width 2 (mm)	Height (mm)	Packing/Box (pcs)	Energy class
99FM604012/BL	**99FM604012/WH**	**99FM604012/GR**	C	12	1140	4000	600	70	47.8	22.4	1/1	A++→A
99FM1204024/BL	**99FM1204024/WH**	**99FM1204024/GR**	C	24	2280	4000	1200	70	47.8	22.4	1/1	A++→A
99FM1504032/BL	**99FM1504032/WH**	**99FM1504032/GR**	C	32	3040	4000	1500	70	47.8	22.4	1/1	A++→A





L-corner for LED profiles S48series recessed
White: **99FML/WH**
Black: **99FML/BL**
Grey: **99FML/GR**
size: 420x420mm

Inside corner for LED profiles S48 series recessed
White: **99FMI/WH**
Black: **99FMI/BL**
Grey: **99FMI/GR**
size: 420x420mm

Body: aluminium | **Reflector:** polycarbonate (PC) | **Clamps:** inox | **Driver:** 42V SELV driver | **Light Source:** SAMSUNG

L- corner and Inside corners are ordered within 30 days term, after a preliminary specification of power and colour temperature of LED profiles.

~230V 50/60 Hz SMD 90° Ra≥80 >15000 INSTANT 100% 20000h Hg IP 40 RoHS EMC F CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 30 days.



LED NEUTRAL WHITE 4000K **IP40** **HIGH POWER**

HIGH POWER LED PROFILES S48 SERIES FOR RECESSED MOUNTING WITH EMERGENCY KIT

Catalogue number BLACK	Catalogue number WHITE	Catalogue number GREY	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Width 1 (mm)	Width 2 (mm)	Height (mm)	Packing/Box (pcs)	Energy class
99FM604020/BLE	**99FM604020/WHE**	**99FM604020/GRE**	C	20	1600	4000	600	70	47.8	22.4	1/1	A++→A
99FM1204040/BLE	**99FM1204040/WHE**	**99FM1204040/GRE**	C	40	3200	4000	1200	70	47.8	22.4	1/1	A++→A

LED NEUTRAL WHITE 4000K **IP40** **HIGH POWER**

HIGH POWER LED PROFILES S48 SERIES FOR RECESSED MOUNTING

Catalogue number BLACK	Catalogue number WHITE	Catalogue number GREY	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Width 1 (mm)	Width 2 (mm)	Height (mm)	Packing/Box (pcs)	Energy class
99FM604020/BL	**99FM604020/WH**	**99FM604020/GR**	C	20	1600	4000	600	70	47.8	22.4	1/1	A++→A
99FM1204040/BL	**99FM1204040/WH**	**99FM1204040/GR**	C	40	3200	4000	1200	70	47.8	22.4	1/1	A++→A
99FM1504050/BL	**99FM1504050/WH**	**99FM1504050/GR**	C	50	4000	4000	1500	70	47.8	22.4	1/1	A++→A



Body: aluminium | **Reflector:** polycarbonate (PC) | **Clamps:** inox | **Driver:** 42V SELV driver | **Light Source:** SAMSUNG

~230V 50/60 Hz SMD 90° Ra≥80 >15000 INSTANT 100% 20000h Hg IP 40 RoHS EMC F CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 30 days.



LED NEUTRAL WHITE 4000K **IP40**

LED PROFILES S77 SERIES RECESSED MOUNTING WITH EMERGENCY KIT

Catalogue number BLACK	Catalogue number WHITE	Catalogue number GREY	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Width 1 (mm)	Width 2 (mm)	Height (mm)	Packing/Box (pcs)	Energy class
99BM604024/BLE	**99BM604024/WHE**	**99BM604024/GRE**	C	24	2280	4000	600	98.5	77.5	27	1/1	A++→A
99BM1204048/BLE	**99BM1204048/WHE**	**99BM1204048/GRE**	C	48	4560	4000	1200	98.5	77.5	27	1/1	A++→A

LED NEUTRAL WHITE 4000K **IP40**

LED PROFILES S77 SERIES RECESSED MOUNTING

Catalogue number BLACK	Catalogue number WHITE	Catalogue number GREY	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Width 1 (mm)	Width 2 (mm)	Height (mm)	Packing/Box (pcs)	Energy class
99BM604024/BL	**99BM604024/WH**	**99BM604024/GR**	C	24	2280	4000	600	98.5	77.5	27	1/1	A++→A
99BM1204048/BL	**99BM1204048/WH**	**99BM1204048/GR**	C	48	4560	4000	1200	98.5	77.5	27	1/1	A++→A
99BM1504064/BL	**99BM1504064/WH**	**99BM1504064/GR**	C	64	6080	4000	1500	98.5	77.5	27	1/1	A++→A





L-corner for LED profiles S77series recessed
White: **99BML/WH**
Black: **99BML/BL**
Grey: **99BML/GR**
size: 450x450mm

Inside corner for LED profiles S77 series recessed
White: **99BMI/WH**
Black: **99BMI/BL**
Grey: **99BMI/GR**
size: 450x450mm

Body: aluminium | **Reflector:** polycarbonate (PC) | **Clamps:** inox | **Driver:** 42V SELV driver

L- corner and Inside corners are ordered within 30 days term, after a preliminary specification of power and colour temperature of LED profiles.

~230V | 50/60 Hz | SMD | 90° | Ra≥80 | >15000 | INSTANT 100% | 20000h | Hg | IP 40 | RoHS COMPLIANT | EMC | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 30 days.

LED NEUTRAL WHITE 4000K **IP40** **HIGH POWER**

HIGH POWER LED PROFILES S36 SERIES FOR SURFACE MOUNTING

Catalogue number BLACK	Catalogue number WHITE	Catalogue number GREY	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Height (mm)	Width (mm)	Packing/Box (pcs)	Energy class
99SM36S4020/BL	**99SM36S4020/WH**	**99SM36S4020/GR**	C	20	1600	4000	600	65.64	35.6	1/1	A++→A
99SM36S4040/BL	**99SM36S4040/WH**	**99SM36S4040/GR**	C	40	3200	4000	1200	65.64	35.6	1/1	A++→A
99SM36S4050/BL	**99SM36S4050/WH**	**99SM36S4050/GR**	C	50	4000	4000	1500	65.64	35.6	1/1	A++→A



INSTALATION ACCESSORIES FOR LED PROFILES
Connector
Catalogue number: **99ACC50**
Suspension wire
Catalogue number: **99ACC51**
Suspension wire with console
Catalogue number: **99ACC52**

Body: aluminium | **Reflector:** polycarbonate (PC) | **Driver:** 42V SELV driver | **Light Source:** SAMSUNG

~230V | 50/60 Hz | SMD | 90° | Ra≥80 | >15000 | INSTANT 100% | 20000h | Hg | IP 40 | RoHS COMPLIANT | EMC | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 30 days.

LED NEUTRAL WHITE 4000K **IP40** **HIGH POWER**

HIGH POWER LED PROFILES S48 SERIES FOR SURFACE MOUNTING

Catalogue number BLACK	Catalogue number WHITE	Catalogue number GREY	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Height (mm)	Width (mm)	Packing/Box (pcs)	Energy class
99SM604020/BL	**99SM604020/WH**	**99SM604020/GR**	C	20	1600	4000	600	70	47.8	1/1	A++→A
99SM1204040/BL	**99SM1204040/WH**	**99SM1204040/GR**	C	40	3200	4000	1200	70	47.8	1/1	A++→A
99SM1504050/BL	**99SM1504050/WH**	**99SM1504050/GR**	C	50	4000	4000	1500	70	47.8	1/1	A++→A

LED NEUTRAL WHITE 4000K **IP40**

LED PROFILES S48 SERIES FOR SURFACE MOUNTING

Catalogue number BLACK	Catalogue number WHITE	Catalogue number GREY	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Height (mm)	Width (mm)	Packing/Box (pcs)	Energy class
99SM604012/BL	**99SM604012/WH**	**99SM604012/GR**	C	12	1140	4000	600	70	47.8	1/1	A++→A
99SM1204024/BL	**99SM1204024/WH**	**99SM1204024/GR**	C	24	2280	4000	1200	70	47.8	1/1	A++→A
99SM1504032/BL	**99SM1504032/WH**	**99SM1504032/GR**	C	32	3040	4000	1500	70	47.8	1/1	A++→A



L-corner for LED profiles
S48series surface
White: **99SML/WH**
Black: **99SML/BL**
Grey: **99SML/GR**
size: 420x420mm



99ACC50

99ACC52

99ACC51

INSTALATION ACCESSORIES FOR LED PROFILES
Connector
Catalogue number: **99ACC50**
Suspension wire
Catalogue number: **99ACC51**
Suspension wire with console
Catalogue number: **99ACC52**

Body: aluminium | **Reflector:** polycarbonate (PC) | **Driver:** 42V SELV driver | **Light Source:** SAMSUNG

L- corner and Inside corners are ordered within 30 days term, after a preliminary specification of power and colour temperature of LED profiles.

~230V | 50/60 Hz | SMD | 90° | Ra≥80 | >15000 | INSTANT 100% | 20000h | Hg | IP 40 | RoHS COMPLIANT | EMC | CE | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 30 days.



LED NEUTRAL WHITE 4000K **IP40**

LED PROFILES S77 SERIES FOR SURFACE MOUNTING WITH EMERGENCY KIT

Catalogue number BLACK	Catalogue number WHITE	Catalogue number GREY	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Height (mm)	Width (mm)	Packing/Box (pcs)	Energy class
99OM604024/BLE	**99OM604024/WHE**	**99OM604024/GRE**	C	24	2280	4000	600	100	77	1/1	A++→A
99OM1204048/BLE	**99OM1204048/WHE**	**99OM1204048/GRE**	C	48	4560	4000	1200	100	77	1/1	A++→A

LED NEUTRAL WHITE 4000K **IP40**

LED PROFILES S77 SERIES FOR SURFACE MOUNTING

Catalogue number BLACK	Catalogue number WHITE	Catalogue number GREY	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Height (mm)	Width (mm)	Packing/Box (pcs)	Energy class
99OM604024/BL	**99OM604024/WH**	**99OM604024/GR**	C	24	2280	4000	600	100	77	1/1	A++→A
99OM1204048/BL	**99OM1204048/WH**	**99OM1204048/GR**	C	48	4560	4000	1200	100	77	1/1	A++→A
99OM1504064/BL	**99OM1504064/WH**	**99OM1504064/GR**	C	64	6080	4000	1500	100	77	1/1	A++→A



L-corner for LED profiles S77series surface
White: **99OML/WH**
Black: **99OML/BL**
Grey: **99OML/GR**
size: 450x450mm



99ACC55

99ACC52

99ACC51

INSTALATION ACCESSORIES FOR LED PROFILES
Connector
Catalogue number: **99ACC55**
Suspension wire
Catalogue number: **99ACC51**
Suspension wire with console
Catalogue number: **99ACC52**

Body: aluminium | **Reflector:** polycarbonate (PC) | **Driver:** 42V SELV driver | **Light Source:** SAMSUNG

L- corner and Inside corners are ordered within 30 days term, after a preliminary specification of power and colour temperature of LED profiles.

~230V | 50/60 Hz | SMD | 90° | Ra≥80 | >15000 | INSTANT 100% | 20000h | Hg | IP 40 | RoHS COMPLIANT | EMC | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 30 days.

LED **IP20**

UNTIL SUPPLY LAST

RAINBOW LED SMD

Catalogue number	Product category	Watt (W)	Colou	LED lamp lumens (lm)	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
9RT5300/WH	F	5	White	400	320	22	35	1/25	A++→A
9RT5300/WW	F	5	Warm white	400	320	22	35	1/25	A++→A
9RT5300/R	F	5	Red	-	320	22	35	1/25	A++→A
9RT5300/G	F	5	Green	-	320	22	35	1/25	A++→A
9RT5300/B	F	5	Blue	-	320	22	35	1/25	A++→A
9RT5600/WH	F	9	White	720	555	22	35	1/25	A++→A
9RT5600/WW	F	9	Warm white	720	555	22	35	1/25	A++→A
9RT5600/R	F	9	Red	-	555	22	35	1/25	A++→A
9RT5600/G	F	9	Green	-	555	22	35	1/25	A++→A
9RT5900/WH	F	14	White	1120	860	22	35	1/25	A++→A
9RT5900/WW	F	14	Warm white	1120	860	22	35	1/25	A++→A
9RT5900/G	F	14	Green	-	860	22	35	1/25	A++→A
9RT51200/WH	F	18	White	1440	1165	22	35	1/25	A++→A
9RT51200/WW	F	18	Warm white	1440	1165	22	35	1/25	A++→A
9RT51200/G	F	18	Green	-	1165	22	35	1/25	A++→A

9RT505

Body: PVC | **Diffuser:** Glass | **Light source:** SMD 2835

~230V | 50/60 Hz | SMD 2835 | 270° | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | IP 20 | RoHS COMPLIANT | EMC | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

Light is one of the most important space-shaping elements. Therefore it is worth to consider the quality of the selected lighting fittings.

The SMD LED series of modern fittings is an innovative solution of lighting that is functional and decorative at the same time. The fittings emit high quality light and their compact form, matching contemporary furniture, enables a multitude of arrangements. The fittings can be connected in order to achieve the lighting line of the desired length, and the energy-efficient LED light makes it possible to achieve a spectacular effect in any interior.

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

IP20

UNTIL SUPPLY LAST

FLUORESCENT LIGHT FIXTURES RAINBOW

Catalogue number	Product category	Type	Watt (W)	Colour body	Ballast	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
9RT513/W	F	RAINBOW	13	white	electronic	545	24	35	1/30	B
9RT521/W	F	RAINBOW	21	white	electronic	875	24	35	1/30	B
9RT508/B	F	RAINBOW	8	blue	electronic	315	24	35	1/30	B
9RT513/B	F	RAINBOW	13	blue	electronic	545	24	35	1/30	B
9RT521/B	F	RAINBOW	21	blue	electronic	875	24	35	1/30	B
9RT528/B	F	RAINBOW	28	blue	electronic	1174	24	35	1/30	B
9RT508/G	F	RAINBOW	8	green	electronic	315	24	35	1/30	B
9RT513/G	F	RAINBOW	13	green	electronic	545	24	35	1/30	B
9RT521/G	F	RAINBOW	21	green	electronic	875	24	35	1/30	B
9RT528/G	F	RAINBOW	28	green	electronic	1174	24	35	1/30	B
9RT513/Y	F	RAINBOW	13	yellow	electronic	545	24	35	1/30	B
9RT521/Y	F	RAINBOW	21	yellow	electronic	875	24	35	1/30	B
9RT528/Y	F	RAINBOW	28	yellow	electronic	1174	24	35	1/30	B
9RT508/R	F	RAINBOW	8	red	electronic	315	24	35	1/30	B
9RT513/R	F	RAINBOW	13	red	electronic	545	24	35	1/30	B
9RT521/R	F	RAINBOW	21	red	electronic	875	24	35	1/30	B
9RT528/R	F	RAINBOW	28	red	electronic	1174	24	35	1/30	B

This lighting fixture is compatible with lamps from energy classes: B A A+ A++.

This lighting fixture comes with lamp from energy class: B

~230V | 50/60 Hz | G5 | 270° | >20000 | INSTANT 100% | 30000h | Hg | IP 20 | RoHS COMPLIANT | EMC | F | CE | 2+0 standard +extended 2 YEAR TOTAL WARRANTY

IP20

UNTIL SUPPLY LAST

COLOUR LIGHTING TUBES T5

Catalogue number	Product category	Type	Watt (W)	Colour	Length (mm)	Packing/Box (pcs)	Energy class
99217177	F	FLUORESCENT TUBE	8	blue	303	1/100	B
99217181	F	FLUORESCENT TUBE	8	green	303	1/100	B
99217182	F	FLUORESCENT TUBE	13	green	531	1/100	B
99217183	F	FLUORESCENT TUBE	21	green	863	1/100	B
99217184	F	FLUORESCENT TUBE	28	green	1160	1/100	B
99217187	F	FLUORESCENT TUBE	21	yellow	863	1/100	B
99217188	F	FLUORESCENT TUBE	28	yellow	1160	1/100	B
99217190	F	FLUORESCENT TUBE	13	red	531	1/100	B
99217191	F	FLUORESCENT TUBE	21	red	863	1/100	B
99217192	F	FLUORESCENT TUBE	28	red	1160	1/100	B

~230V | 50/60 Hz | G5 | 270° | >20000 | INSTANT 100% | 30000h | Hg | IP 20 | RoHS COMPLIANT | EMC | F | CE | 2+0 standard +extended 2 YEAR TOTAL WARRANTY

SHINA WITH LED TUBE

910109LCW
910109LW
910118LCW
910118LW

LED | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP21**

Shina with LED tubes T8 STELLAR

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
910109LCW	C	9	630	6400	white	612	33	44	1/12	A A++→A
910109LW	C	9	630	4000	white	612	33	44	1/12	A A++→A
910118LCW	C	18	1260	6400	white	1218	33	44	1/8	A A++→A
910118LW	C	18	1260	4000	white	1218	33	44	1/8	A A++→A

with LED tubes STELLAR

~230V | 50/60 Hz | LED T8 | G13 | Ra≥80 | Hg | IP 21 | RoHS | EMC | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

VIKI

9VBM214LEDW
9VOM214LEDW

LED NEUTRAL WHITE 4000K **IP21**

UNTIL SUPPLY LAST

VIKI luminaire with LED tubes T5 ELMARK

Catalogue number	Product category	Watt (W)	Mounting type	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
9VBM214LEDW	F	2X10	recessed	1800	4000	white	595	295	55	1/1	A++→A
9VOM214LEDW	F	2X10	surface	1800	4000	white	600	300	55	1/1	A++→A

Body: white powder painted steel | **Reflector:** prismatic lens | **Ballast:** fixed inside the body | **BM** - recessed fixture for mounting in suspended ceiling Armstrong type | **OM** - surface mounted fixture

with LED tubes ELMARK

~230V | 50/60 Hz | LED T5 | G5 | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | IP 21 | RoHS | EMC | F | CE | 3+0 standard +extended | 3 YEAR TOTAL WARRANTY

LENA-V OM

9LOM260LEDCW
9LOM260LED
9LOM460LEDCW
9LOM460LED
9LOM2120LEDCW
9LOM2120LED

LENA-V BM

9LBM260LEDCW
9LBM260LED
9LBM460LEDCW
9LBM460LED
9LBM2120LEDCW
9LBM2120LED

LED | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP21**

LENA-V BM/OM with LED Tubes T8 STELLAR

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
9LBM260LEDCW	C	2X9	1170	6400	white	595	295	70	1/1	A+ A++→A
9LBM260LED	C	2X9	1170	4000	white	595	295	70	1/1	A+ A++→A
9LBM460LEDCW	C	4X9	2340	6400	white	595	595	70	1/1	A+ A++→A
9LBM460LED	C	4X9	2340	4000	white	595	595	70	1/1	A+ A++→A
9LBM2120LEDCW	C	2X18	2340	6400	white	1195	295	70	1/1	A+ A++→A
9LBM2120LED	C	2X18	2340	4000	white	1195	295	70	1/1	A+ A++→A
9LOM260LEDCW	C	2X9	1170	6400	white	630	330	70	1/1	A+ A++→A
9LOM260LED	C	2X9	1170	4000	white	630	330	70	1/1	A+ A++→A
9LOM460LEDCW	C	4X9	2340	6400	white	630	630	70	1/1	A+ A++→A
9LOM460LED	C	4X9	2340	4000	white	630	630	70	1/1	A+ A++→A
9LOM2120LEDCW	C	2X18	2340	6400	white	1230	330	70	1/1	A+ A++→A
9LOM2120LED	C	2X18	2340	4000	white	1230	330	70	1/1	A+ A++→A

with LED tubes STELLAR

Body: white powder painted steel | **Reflector:** aluminium mirror double parabolic grid - type V | **BM** - recessed mounted luminaire | **OM** - surface mounted luminaire | **Light source:** LED tubes

~230V | 50/60 Hz | LED T8 | G13 | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | IP 21 | RoHS COMPLIANT | EMC | F | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 30 days.

LENA-V OM

9LOM260LEDCWE
9LOM260LEDWE
9LOM460LEDCWE
9LOM460LEDWE
9LOM2120LEDCWE
9LOM2120LEDWE

LENA-V BM

9LBM260LEDCWE
9LBM260LEDWE
9LBM460LEDCWE
9LBM460LEDWE
9LBM2120LEDCWE
9LBM2120LEDWE

LED | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP21**

LENA-V BM/OM with LED Tubes T8 and emergency kit

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
9LBM260LEDCWE	C	2X9	1170	6400K	white	595	295	70	1/1	A+ A++→A
9LBM260LEDWE	C	2X9	1170	4000K	white	595	295	70	1/1	A+ A++→A
9LBM460LEDCWE	C	4X9	2340	6400K	white	595	595	70	1/1	A+ A++→A
9LBM460LEDWE	C	4X9	2340	4000K	white	595	595	70	1/1	A+ A++→A
9LBM2120LEDCWE	C	2X18	2340	6400K	white	1195	295	70	1/1	A+ A++→A
9LBM2120LEDWE	C	2X18	2340	4000K	white	1195	295	70	1/1	A+ A++→A
9LOM260LEDCWE	C	2X9	1170	6400K	white	630	330	70	1/1	A+ A++→A
9LOM260LEDWE	C	2X9	1170	4000K	white	630	330	70	1/1	A+ A++→A
9LOM460LEDCWE	C	4X9	2340	6400K	white	630	630	70	1/1	A+ A++→A
9LOM460LEDWE	C	4X9	2340	4000K	white	630	630	70	1/1	A+ A++→A
9LOM2120LEDCWE	C	2X18	2340	6400K	white	1230	330	70	1/1	A+ A++→A
9LOM2120LEDWE	C	2X18	2340	4000K	white	1230	330	70	1/1	A+ A++→A

with LED tubes STELLAR

We offer the fixtures as per personal request with a fixed block and battery with a possibility for work in an emergency regime 60-180min

Body: white powder painted steel | **Reflector:** aluminium mirror double parabolic grid - type V | **BM** - recessed mounted luminaire | **OM** - surface mounted luminaire | **Light source:** LED tubes

~230V | 50/60 Hz | LED T8 | G13 | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | IP 21 | RoHS COMPLIANT | EMC | F | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.



NEDA



NINA

LED | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP21**

UNTIL SUPPLY LAST

NEDA / NINA Luminaire with LED Tubes T8 STELLAR

Catalogue number	Product category	Model	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95LED209CW	F	Neda	2X9	1170	6400	white	740	160	55	1/6	A+ A++→A
95LED209W	F	Neda	2X9	1170	4000	white	740	160	55	1/6	A+ A++→A
920118LED	F	Nina	1X9	585	4000	white	740	118	48	1/12	A+ A++→A
920118LEDCW	F	Nina	1X9	585	6400	white	740	118	48	1/12	A+ A++→A
920218LED	F	Nina	2X9	1170	4000	white	740	160	55	1/6	A+ A++→A
920218LEDCW	F	Nina	2X9	1170	6400	white	740	160	55	1/6	A+ A++→A

with LED tubes STELLAR

Body: white powder painted steel | **Reflector:** plastic cover (Neda); ABS plastic grid (Nina) | **Light source:** LED tubes

~230V | 50/60 Hz | LED T8 | G13 | Ra≥80 | >20000 | INSTANT 100% | 15000h | Hg | IP 21 | RoHS | EMC | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

POLA
9PBME255LEDCW

POLA
9PMBME255LEDCW

LED COOL WHITE 6400K **IP21**

UNTIL SUPPLY LAST

POLA luminaire with LED PLL ELMARK

Catalogue number	Product category	Watt (W)	Mounting type	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
9PMBME255LEDCW	F	recessed	2x20	3600	5500	white	595	595	80	1/1	A++→A
9PBME255LEDCW	F	recessed	2x20	3700	5500	white	595	595	80	1/1	A++→A

with LED PLL ELMARK

~230V | 50/60 Hz | PLL | 2G11 | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | IP 21 | RoHS COMPLIANT | EMC | F | CE | 3+0 standard +extended | 3 YEAR TOTAL WARRANTY

PRISMATIC T5

IP21

UNTIL SUPPLY LAST

PRISMATIC T5

Catalogue number	Product category	Watt (W)	Colour body	Ballast	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
9PROM249	F	2X49	white	electronic	1500	300	70	1/1	A++→B

Body: white powder painted steel | **Reflector:** prismatic lens | **Ballast:** fixed inside the body | **BM** - recessed fixture for mounting in suspended ceiling Armstrong type | **OM** - surface mounted fixture

~230V | 50/60 Hz | T5 | RoHS | EMC | F | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY

PRISMATIC
9PRBME214LEDW

PRISMATIC
9PROM214LEDW
9PROM414LEDW

LED

UNTIL SUPPLY LAST

PRISMATIC luminaire with LED tubes T5 ELMARK

Catalogue number	Product category	Watt (W)	Mounting type	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
9PRBME214LEDW	F	2X10	recessed	1700	4000	white	595	295	70	1/1	A++→A
9PROM214LEDW	F	2X10	surface	1700	4000	white	608	308	70	1/1	A++→A
9PROM414LEDW	F	4X10	surface	3400	4000	white	595	595	70	1/1	A++→A

with LED tubes ELMARK

~230V | 50/60 Hz | LED T5 | G5 | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | IP 21 | RoHS COMPLIANT | EMC | F | CE | 3+0 standard +extended | 3 YEAR TOTAL WARRANTY

PRISMATIC
9PRBME209LEDW
9PRBME209LEDCW
9PRBME218LEDW
9PRBME218LEDCW

PRISMATIC
9PROME209LEDW
9PROME209LEDCW

UNTIL SUPPLY LAST

PRISMATIC luminaire with LED tubes T8 STELLAR

Catalogue number	Product category	Watt (W)	Mounting type	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
9PRBME209LEDW	F	2X9	RECESSED	1080	4000K	white	595	295	70	1/1	A+ A++→A
9PRBME209LEDCW	F	2X9	RECESSED	1080	6400K	white	595	295	70	1/1	A+ A++→A
9PRBME218LEDW	F	2X18	RECESSED	2160	4000K	white	1195	295	70	1/1	A+ A++→A
9PRBME218LEDCW	F	2X18	RECESSED	2160	6400K	white	1195	295	70	1/1	A+ A++→A
9PROME209LEDW	F	2X9	SURFACE	1080	4000K	white	608	308	70	1/1	A+ A++→A
9PROME209LEDCW	F	2X9	SURFACE	1080	6400K	white	608	308	70	1/1	A+ A++→A

with LED tubes STELLAR

~230V | 50/60 Hz | LED T8 | G13 | Ra≥80 | >20000 | INSTANT 100% | 15000h | Hg | IP 21 | RoHS COMPLIANT | EMC | F | CE | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY



CAB-19
919LED010
919LED110

CAB-20
920LED011
920LED111

CAB-11
911LED14

CAB-12
912LED06
912LED16

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | IP20

UNTIL SUPPLY LAST

CAB

Catalogue number	Product category	Watt (W)	Lumen (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
920LED011	F	12	1050	4000	grey	500	42	15	1/60	A++→A
920LED111	F	12	1050	2700	grey	500	42	15	1/60	A++→A
919LED010	F	2,8	185	4000	grey	160	50	9	1/10	A++→A
919LED110	F	2,8	185	2700	grey	160	50	9	1/10	A++→A
911LED14	F	3,5	270	2700	grey	450	23	7	1/10	A++→A
912LED06	F	7	480	4000	grey	450	50	9	1/10	A++→A
912LED16	F	7	480	2700	grey	450	50	9	1/10	A++→A

Body: Aluminium | **Diffuser:** PMMA | **Sensor:** NO | w/o driver | **Light source:** Epistar | **Assemble:** Surface Mounted

Starting time: <0.01s | **With integrated door sensor(CAB-19)** - The lamp will switch on when the door is open and switch off when the door is closed. Reaction distance is 50mm - 100mm. | w/o driver

12V DC | SMD 5050 | 120° | Ra≥80 | >10000 | INSTANT 100% | 30000h | Hg | IP 20 | RoHS COMPLIANT | EMC | 3+0 standard +extended | 3 YEAR TOTAL WARRANTY



CAB-13
913LED11

CAB-14
914LED02
914LED12

CAB-15
915LED03
915LED13

CAB-16
916LED05
916LED15

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | **IP20**

UNTIL SUPPLY **LAST**

CAB

Catalogue number	Product category	Watt (W)	Voltage (V)	Lumen (lm)	Colour temp. (K)	Colour body	Beam angle	Length (mm)	Width (mm)	Height (mm)	Diameter (mm)	Packing/Box (pcs)	Energy class
914LED12	F	2,4	12 DC	210	2700	silver	120°	57	57	10	-	1/100	A++→A
915LED03	F	1,8	12 DC	160	4000	silver	120°	57	57	10	-	1/100	A++→A
915LED13	F	1,8	12 DC	160	2700	silver	120°	57	57	10	-	1/100	A++→A
916LED05	F	1	12 DC	90	4000	chrome	120°	52	52	10	-	1/100	A++→A
916LED15	F	1	12 DC	90	2700	chrome	120°	52	52	10	-	1/100	A++→A

JUNCTION BOX FOR CAB-18
3 mouths with 10 cm wire - **99LED456**
6 mouths with 10 cm wire - **99LED457**
12 mouths with 10 cm wire - **99LED458**

Body: ABS | **Diffuser:** PC | **Sensor:** NO | w/o driver | **Light source:** Epistar | **Assemble:** Surface Mounted | **Starting time:** <0.01s

12V DC | Ra≥80 | >10000 | INSTANT 100% | 30000h | Hg | IP 20 | RoHS | EMC | F | CE | 3+0 standard +extended | 3 YEAR TOTAL WARRANTY

CAB-08
908508
908521

CAB-03
903508
903521

IP21

UNTIL SUPPLY LAST

CAB

Catalogue number	Product category	Model	Watt (W)	Colour body	Body	Length (mm)	Width (mm)	Height (mm)	Ballast	Packing/Box (pcs)	Energy class
903508	F	CAB-03	8	grey	Aluminium	363	88	45	electronic	1/20	B A++→B
903521	F	CAB-03	21	grey	Aluminium	925	88	45	electronic	1/20	B A++→B
908508	F	CAB-08	8	grey	Aluminium	365	58	70	electronic	1/16	B A++→B
908521	F	CAB-08	21	grey	Aluminium	935	58	70	electronic	1/12	B A++→B

~230V · 50/60 Hz · T5 · G5 · 6500K · Ra≥80 · IP 21 · RoHS COMPLIANT · 2+0 standard +extended 2 YEAR TOTAL WARRANTY

EXIT

EL3LED
92EL3LED

XL102
9XL102LED

EL1LED
92EL1LED

LED COOL WHITE 6400K **IP21**

EMERGENCY FIXTURE XL102 / EL3LED / EL1LED

Catalogue number	Product category	Model	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Discharge time (h)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
92EL1LED	C	EL1LED	3W	180	6000	3	white	60	40	26.5	1/1	A++→A
92EL3LED	C	EL3LED	5 W	150	6000	3	white	140	140	20	1/1	A++→A
9XL102LED	C	XL102LED	30X0,067W	100	6000	5	white	200	54	32	1/60	A++→A

EL1LED - Voltage: 220-240V/50HZ | **Battery:** 18650 3.7V/3Ah | **Charging:** 220V- 12h; 120V | **Light source:** 1 pc 3W LED | **Cut out size:** 40mm | Auto self-test

XL102LED - Voltage: 127-220V/50HZ | **Battery:** Lithium 3.7V/1000mAh | **Charging:** 220V- 12h; 120V- 24h | **Light source:** SMD 2835 | Two files dimming | Over charge protection | **Body:** PVC

~230V | 50/60 Hz | 20000h | IP 21 | RoHS COMPLIANT | EMC | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock for EL3LED, the delivery time after order confirmation will be 45 days, and for XL102 will be 90 days.

XL101
9XL101BLED
9XL101CLED

LED COOL WHITE 6400K **IP21**

XL101

Catalogue number	Product category	Model	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
9XL101BLED	C	XL101BLED	18X0,1W	60	6200-6500	white	246	76	41	1/10	A++→A
9XL101CLED	C	XL101CLED	24X0,1W	75	6200-6500	white	327	76	43	1/10	A++→A

Body: PVC | **Diffuser:** PVC | Duration time approx 4 hours | **Battery:** 3,6V / 800mAh Ni-Cd

Note: with stickers

~230V | 50/60 Hz | Ra>70 | 20000h | Hg | IP 21 | RoHS COMPLIANT | EMC | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

XL88
9XL88 LED

XL88
9XL88A LED

LED IP21

XL88

Catalogue number	Product category	Model	Watt (W)	Whole fixture lumens (lm)	Lamp	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
9XL88LED	C	XL88 LED / DOUBLE FACE	3	35	LED	360	150	25	1/10	A++→A
9XL88A LED	C	XL88A LED / ONE FACE ONLY	3	35	LED	360	150	25	1/10	A++→A

Frame: aluminium | **Diffuser:** glass | Duration time approx 3 hours | **battery:** 2,4V / 800mAh Ni-Cd

~230V | 50/60 Hz | IP 21 | RoHS | EMC | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

9XL3114

9XL5113

9XL3115

9XL5114

9AL3116
Plasterboard Mounting

9AL3117
Plasterboard Mounting

LED **IP21**

XL/AL EMERGENCY LIGHT

Catalogue number	Product category	Model	LED Type	Discharge time (h)	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
9XL5113	C	XL5113	6 super bright SMD LED	3	220	260	22	1/20	A++→A
9XL5114	C	XL5114	6 super bright SMD LED	3	220	260	22	1/20	A++→A
9XL3114	C	XL3114	6 super bright SMD LED	3	220	260	22	1/20	A++→A
9XL3115	C	XL3115	6 super bright SMD LED	3	220	260	22	1/20	A++→A
9AL3116	C	AL3116 Plasterboard	6 pieces D5 LED	3	380	210	50	1/20	A++→A
9AL3117	C	AL3117 Plasterboard	6 pieces D5 LED	3	380	210	50	1/20	A++→A

XL Models
Frame: PVC | **Diffuser:** PVC | **Battery:** 3,6V/300mAh | **Charge time:** 8-12h | **Conversion time:** <0.2sek | **Ambient temperature:** -10+40°C | With test button

AL Model
Frame: Aluminium alloy | **Power:** 1,5W | **Battery:** 1,2V/800mAh | **Conversion time:** <0.2sek | **Ambient temperature:** -10+40°C | **Mounting:** Plasterboard

~230V | 50/60 Hz | 20000h | Hg | IP 21 | RoHS | EMC | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

AUTONOMY EMERGENCY LIGHTING

The emergency lighting is aimed to be used in all cases when the power of the normal lighting is canceled due to occur of the emergency situation – an electric shock, fire, earthquake and etc. This assures the lighting needed and its continuous visibility, needed for the unimpeded leaving of the building through the emergency exits and it assures the ability for the easy recognition of the fireproof equipment and the signalization tools, positioned on the emergency roads.
The emergency blocks, offered by us, are suitable for autonomic lighting systems. They are with built in batteries and guarantee the autonomic switching on of the lighting body to which they are connected, if an emergency situation occurs, using the energy reserve of the battery. Similar lighting bodies do not need special power lines and they can be mounted anywhere, without a special need of support. Its main advantage is their independency of special built emergency lines and even if there is a damage in one of the emergency lightings, all of the others will keep on working. This gives an additional security and reliability of the whole emergency system.

EMERGENCY DRIVER FOR LAMP WITH EXTERNAL DRIVERS

3+0 standard +extended 3 YEAR TOTAL WARRANTY

The housing of this emergency driver adopts good-quality aluminum and flame-retardant plastic. It has low weight and being convenient to install, so you can rest assure its safety. Battery adopts Li-ion battery with long lifespan. Its PCB adopts SMT technology, using IC control design in charging/discharging and power supply part. PCB uses fully automatic SMT technology, PCB core use PN8355, DW01 and M8205A IC chips which are especially for emergency lights and Li-ion battery protections. PCB circuit has the complete protection designs for over charging/discharging.

OPERATED PRINCIPE:
The emergency driver is being charged when AC power works, when fully charged, the circuit will protect the battery from over being-charged, and the emergency is standing by as soon as the battery is fully charged. When AC power is down, emergency driver supplies power to LED fixtures and they up light to the way to escape.

TECHNICAL DATA:
- Input voltage: 85-265V AC
- Battery: 3.7V 2400mAh
- Emergency switch time: <2s
- Suitable: for LED lamp with external driver and power 3-50W
- Emergency time: >120min
- Working temperature: from -5 to +45°C
- Size: 130x58x22mm
- IP 30

RECOMMENDED:
For all LED panels and fixtures with external driver and power from 3-50W

Working voltage	Charging time	Emergency time	Emergency switch time	Packing / Box (pcs)	Product category	Catalogue number
85-265V AC	24h	>120min	<2s	1/100	C	**89229**

LED PANELS STELLAR WITH EMERGENCY DRIVER 3-50W

2+0 standard +extended 2 YEAR TOTAL WARRANTY **IP40**

Model	Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
LED PANELS STELLAR	**99XPANEL020WE**	C	48	4320	4000	595	595	30	1/6	A++→A
LED PANELS STELLAR	**99XPANEL020CWE**	C	48	4320	6400	595	595	30	1/6	A++→A
LED PANELS STELLAR	**99XPANEL021WE**	C	48	4320	4000	295	1195	30	1/6	A++→A

LED PANELS IP44 WITH EMERGENCY DRIVER 3-50W

4+1 standard +extended 5 YEAR TOTAL WARRANTY **IP44**

Model	Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
LED PANEL ELMARK IP44	**92PANEL012WIP44E**	C	24	2400	4000	295	295	11	1/12	A++→A
LED PANEL ELMARK IP44	**92PANEL013WIP44E**	C	36	3600	4000	595	295	11	1/6	A++→A
LED PANEL ELMARK IP44	**92PANEL020WIP44E**	C	48	4800	4000	595	595	30	1/6	A++→A
LED PANEL ELMARK IP44	**92PANEL020CWIP44E**	C	48	4800	6400	595	595	30	1/6	A++→A
LED PANEL ELMARK IP44	**92PANEL018WIP44E**	C	45	4500	4000	595	595	9	1/5	A++→A
LED PANEL ELMARK IP44	**92PANEL021WIP44E**	C	48	4800	4000	1195	295	30	1/6	A++→A

LED PANELS WITH EMERGENCY DRIVER 3-50W

4+1 standard +extended 5 YEAR TOTAL WARRANTY **IP40**

Model	Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
LED PANEL ELMARK	**92PANEL012WE**	C	24	2400	4000	295	295	11	1/12	A++→A
LED PANEL ELMARK	**92PANEL013WE**	C	36	3600	4000	595	295	11	1/6	A++→A
LED PANEL ELMARK	**92PANEL018WE**	C	45	4500	4000	595	595	9	1/5	A++→A
LED PANEL ELMARK	**92PANEL020WE**	C	48	4800	4000	595	595	30	1/6	A++→A
LED PANEL ELMARK	**92PANEL020CWE**	C	48	4800	6400	595	595	30	1/6	A++→A
LED PANEL ELMARK	**92PANEL021WE**	C	48	4800	4000	1195	295	30	1/6	A++→A
LED PANEL ELMARK	**92PANEL030WE**	C	48	4800	4000	595	595	9	1/6	A++→A
LED PANEL ELMARK	**92PANEL030CWE**	C	48	4800	6400	595	595	9	1/6	A++→A

LED PANEL STELLAR ROUND BM WITH EMERGENCY DRIVER 3-50W

2+0 standard +extended 2 YEAR TOTAL WARRANTY

IP40

Model	Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Height (mm)	Diameter1 (mm)	Packing/Box (pcs)	Energy class
LED PANELS ROUND STELLAR	**99XLED610E**	C	6	330	2700	118	18	100	1/30	A++→A
LED PANELS ROUND STELLAR	**99XLED609E**	C	6	330	4000	118	18	100	1/30	A++→A
LED PANELS ROUND STELLAR	**99XLED609CWE**	C	6	330	6500	118	18	100	1/30	A++→A
LED PANELS ROUND STELLAR	**99XLED612E**	C	12	840	2700	167	18	150	1/24	A++→A
LED PANELS ROUND STELLAR	**99XLED611E**	C	12	840	4000	167	18	150	1/24	A++→A
LED PANELS ROUND STELLAR	**99XLED611CWE**	C	12	840	6500	167	18	150	1/24	A++→A
LED PANELS ROUND STELLAR	**99XLED615E**	C	18	1350	2700	225	18	205	1/20	A++→A
LED PANELS ROUND STELLAR	**99XLED614E**	C	18	1350	4000	225	18	205	1/20	A++→A
LED PANELS ROUND STELLAR	**99XLED614CWE**	C	18	1350	6500	225	18	205	1/20	A++→A
LED PANELS ROUND STELLAR	**99XLED621E**	C	24	1800	2700	295	18	268	1/24	A++→A
LED PANELS ROUND STELLAR	**99XLED620E**	C	24	1800	4000	295	18	268	1/24	A++→A
LED PANELS ROUND STELLAR	**99XLED620CWE**	C	24	1800	6500	295	18	268	1/20	A++→A

LED PANEL ROUND IP44 WITH EMERGENCY DRIVER 3-50W

3+2 standard +extended 5 YEAR TOTAL WARRANTY

IP44

Model	Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
LED PANELS ROUND ELMARK IP44	**99LED609IP44E**	C	5	400	4000	90	21	40	A++→A
LED PANELS ROUND ELMARK IP44	**99LED609IP44CWE**	C	5	400	6500	90	21	40	A++→A
LED PANELS ROUND ELMARK IP44	**99LED611IP44E**	C	12	960	4000	175	21	20	A++→A
LED PANELS ROUND ELMARK IP44	**99LED611IP44CWE**	C	12	960	6500	175	21	20	A++→A
LED PANELS ROUND ELMARK IP44	**99LED617IP44E**	C	18	1440	4000	225	21	20	A++→A
LED PANELS ROUND ELMARK IP44	**99LED617IP44CWE**	C	18	1440	6500	225	21	20	A++→A

LED PANEL ROUND IP65 WITH EMERGENCY DRIVER 3-50W

3+2 standard +extended | 5 YEAR TOTAL WARRANTY | IP65

Model	Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Diameter 1 (mm)	Height (mm)	Packing/ Box (pcs)	Energy class
LED PANELS ROUND ELMARK IP65	**99LED607IP65E**	C	7	660	4000	115	100-110	27	1/20	A++→A
LED PANELS ROUND ELMARK IP65	**99LED607IP65CWE**	C	7	660	6500	115	100-110	27	1/20	A++→A
LED PANELS ROUND ELMARK IP65	**99LED610IP65E**	C	10	770	4000	170	150-160	27	1/20	A++→A
LED PANELS ROUND ELMARK IP65	**99LED610IP65CWE**	C	10	770	6500	170	150-160	27	1/20	A++→A
LED PANELS ROUND ELMARK IP65	**99LED616IP65E**	C	16	1300	4000	220	200-210	27	1/20	A++→A
LED PANELS ROUND ELMARK IP65	**99LED616IP65CWE**	C	16	1300	6500	220	200-210	27	1/20	A++→A
LED PANELS ROUND ELMARK IP65	**99LED623IP65E**	C	23	1750	4000	240	220-230	39	1/20	A++→A
LED PANELS ROUND ELMARK IP65	**99LED623IP65CWE**	C	23	1750	6500	240	220-230	39	1/20	A++→A

LED PANEL STELLAR ROUND OM WITH EMERGENCY DRIVER 3-50W

2+0 standard +extended | 2 YEAR TOTAL WARRANTY | IP40

Model	Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
LED PANELS ROUND STELLAR	**99XLED623E**	C	18	1350	2700	219	32	1/20	A++→A
LED PANELS ROUND STELLAR	**99XLED622E**	C	18	1350	4000	219	32	1/20	A++→A
LED PANELS ROUND STELLAR	**99XLED622CWE**	C	18	1350	6500	219	32	1/20	A++→A
LED PANELS ROUND STELLAR	**99XLED628E**	C	24	1800	2700	295	32	1/20	A++→A
LED PANELS ROUND STELLAR	**99XLED627E**	C	24	1800	4000	295	32	1/20	A++→A
LED PANELS ROUND STELLAR	**99XLED627CWE**	C	24	1800	6500	295	32	1/20	A++→A

LED PANEL STELLAR SQUARE OM/BM WITH EMERGENCY DRIVER 3-50W

2+0 standard +extended | 2 YEAR TOTAL WARRANTY | IP40

Model	Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
LED PANELS SQUARE STELLAR BM	**99XLED633E**	C	12	840	2700	167	167	18	1/24	A++>A
LED PANELS SQUARE STELLAR BM	**99XLED632E**	C	12	840	4000	167	167	18	1/24	A++>A
LED PANELS SQUARE STELLAR BM	**99XLED632CWE**	C	12	840	6500	167	167	18	1/24	A++>A
LED PANELS SQUARE STELLAR BM	**99XLED635E**	C	18	1350	2700	221	221	18	1/20	A++>A
LED PANELS SQUARE STELLAR BM	**99XLED634E**	C	18	1350	4000	221	221	18	1/20	A++>A
LED PANELS SQUARE STELLAR BM	**99XLED634CWE**	C	18	1350	6500	221	221	18	1/20	A++>A
LED PANELS SQUARE STELLAR BM	**99XLED637E**	C	24	1800	2700	296	296	18	1/20	A++>A
LED PANELS SQUARE STELLAR BM	**99XLED636E**	C	24	1800	4000	296	296	18	1/20	A++>A
LED PANELS SQUARE STELLAR BM	**99XLED636CWE**	C	24	1800	6500	296	296	18	1/20	A++>A
LED PANELS SQUARE STELLAR OM	**99XLED969E**	C	18	1350	4000	220	220	32	1/20	A++>A
LED PANELS SQUARE STELLAR OM	**99XLED970E**	C	24	1800	4000	300	300	32	1/20	A++>A

LED PANEL SQUARE OM/BM WITH EMERGENCY DRIVER 3-50W

3+2 standard +extended | 5 YEAR TOTAL WARRANTY | IP40

Model	Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
LED PANELS SQUARE ELMARK BM	**99LED967CWE**	C	12	890	6400	175	175	13	1/20	A++>A
LED PANELS SQUARE ELMARK BM	**99LED967E**	C	12	890	4000	175	175	13	1/20	A++>A
LED PANELS SQUARE ELMARK BM	**99LED967WWE**	C	12	890	2700	175	175	13	1/20	A++>A
LED PANELS SQUARE ELMARK BM	**99LED968CWE**	C	18	1420	6400	225	225	13	1/20	A++>A
LED PANELS SQUARE ELMARK BM	**99LED968E**	C	18	1420	4000	225	225	13	1/20	A++>A
LED PANELS SQUARE ELMARK BM	**99LED968WWE**	C	18	1420	2700	225	225	13	1/20	A++>A
LED PANELS SQUARE ELMARK OM	**99LED969CWE**	C	18	1420	6400	220	220	32	1/20	A++>A
LED PANELS SQUARE ELMARK OM	**99LED969E**	C	18	1420	4000	220	220	32	1/20	A++>A
LED PANELS SQUARE ELMARK OM	**99LED969WWE**	C	18	1420	2700	220	220	32	1/20	A++>A

LED GLASS PANELS SQUARE WITH EMERGENCY DRIVER 3-50W

3+2 standard +extended 5 YEAR TOTAL WARRANTY **IP40**

Model	Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter/ Length (mm)	Height (mm)	Packing/Box (pcs)	Energy class
LED GLASS PANELS SQUARE ELMARK	**99LED642E**	C	6	480	4000	97	40	1/100	A++→A
LED GLASS PANELS SQUARE ELMARK	**99LED643E**	C	6	480	2700	97	40	1/100	A++→A
LED GLASS PANELS SQUARE ELMARK	**99LED644E**	C	18	1440	4000	200	40	1/20	A++→A
LED GLASS PANELS SQUARE ELMARK	**99LED645E**	C	18	1440	2700	200	40	1/20	A++→A

LED GLASS PANELS ROUND WITH EMERGENCY DRIVER 3-50W

3+2 standard +extended 5 YEAR TOTAL WARRANTY **IP40**

Model	Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Diameter 1 (mm)	Height (mm)	Packing/ Box (pcs)	Energy class
LED GLASS PANELS ROUND ELMARK	**99LED638E**	C	6	480	4000	100	35	60	1/100	A++→A
LED GLASS PANELS ROUND ELMARK	**99LED639E**	C	6	480	2700	100	35	60	1/100	A++→A
LED GLASS PANELS ROUND ELMARK	**99LED640E**	C	18	1440	4000	200	35	148	1/20	A++→A
LED GLASS PANELS ROUND ELMARK	**99LED641E**	C	18	1440	2700	200	35	148	1/20	A++→A

DEEP RECESSED LED DOWNLIGHT, WITH EMERGENCY DRIVER 3-50W

4+1 standard +extended 5 YEAR TOTAL WARRANTY **IP44**

Model	Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
LED DOWNLIGHT ELMARK	**92FLD1530/WHE**	C	15	1350	3000	128	70	1/40	A++→A
LED DOWNLIGHT ELMARK	**92FLD1540/WHE**	C	15	1350	4000	128	70	1/40	A++→A
LED DOWNLIGHT ELMARK	**92FLD1565/WHE**	C	15	1350	6500	128	70	1/40	A++→A
LED DOWNLIGHT ELMARK	**92FLD2530/WHE**	C	25	2250	3000	183	97	1/20	A++→A
LED DOWNLIGHT ELMARK	**92FLD2540/WHE**	C	25	2250	4000	183	97	1/20	A++→A
LED DOWNLIGHT ELMARK	**92FLD2565/WHE**	C	25	2250	6500	183	97	1/20	A++→A
LED DOWNLIGHT ELMARK	**92FLD3530/WHE**	C	35	3150	3000	220	100	1/20	A++→A
LED DOWNLIGHT ELMARK	**92FLD3540/WHE**	C	35	3150	4000	220	100	1/20	A++→A
LED DOWNLIGHT ELMARK	**92FLD3565/WHE**	C	35	3150	6500	220	100	1/20	A++→A

LED PROFILES S48 RECESSED WITH EMERGENCY DRIVER 3-50W

3+2 standard +extended | 5 YEAR TOTAL WARRANTY | IP40

Model	Catalogue number BLACK	Catalogue number WHITE	Catalogue number GREY	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Energy class
PROFILES S48 SERIES BM	**99FM604012/BLE**	**99FM604012/WHE**	**99FM604012/GRE**	C	12	1140	4000	600	A++→A
PROFILES S48 SERIES BM	**99FM604020/BLE**	**99FM604020/WHE**	**99FM604020/GRE**	C	20	1600	4000	600	A++→A
PROFILES S48 SERIES BM	**99FM1204024/BLE**	**99FM1204024/WHE**	**99FM1204024/GRE**	C	24	2280	4000	1200	A++→A
PROFILES S48 SERIES BM	**99FM1204040/BLE**	**99FM1204040/WHE**	**99FM1204040/GRE**	C	40	3200	4000	1200	A++→A
PROFILES S48 SERIES BM	**99FM1504032/BLE**	**99FM1504032/WHE**	**99FM1504032/GRE**	C	32	3040	4000	1500	A++→A



LED PROFILES S77 RECESSED WITH EMERGENCY DRIVER 3-50W

3+2 standard +extended | 5 YEAR TOTAL WARRANTY | IP40

Model	Catalogue number BLACK	Catalogue number WHITE	Catalogue number GREY	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Energy class
PROFILES S77 SERIES BM	**99BM604024/BLE**	**99BM604024/WHE**	**99BM604024/GRE**	C	24	2280	4000	600	A++→A
PROFILES S77 SERIES BM	**99BM1204048/BLE**	**99BM1204048/WHE**	**99BM1204048/GRE**	C	48	4560	4000	1200	A++→A



LED PROFILES S48 SURFACE WITH EMERGENCY DRIVER 3-50W

3+2 standard +extended | 5 YEAR TOTAL WARRANTY | IP40

Model	Catalogue number BLACK	Catalogue number WHITE	Catalogue number GREY	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Energy class
PROFILES S77 SERIES OM	**99OM604024/BLE**	**99OM604024/WHE**	**99OM604024/GRE**	C	24	2280	4000	600	A++→A
PROFILES S77 SERIES OM	**99OM1204048/BLE**	**99OM1204048/WHE**	**99OM1204048/GRE**	C	48	4560	4000	1200	A++→A



BELLA SMD2835 AND EMERGENCY DRIVER 3-50W

4+1 standard +extended | 5 YEAR TOTAL WARRANTY | IP65

Model	Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
BELLA SMD2835	**9BR40LEDE**	C	40	3800	4000	1200	80	70	1/12	A++→A
BELLA SMD2835	**9BR40LEDCWE**	C	40	3800	6500	1200	80	70	1/12	A++→A
BELLA SMD2835	**9BR55LEDE**	C	55	5000	4000	1476	80	70	1/9	A++→A
BELLA SMD2835	**9BR55LEDCWE**	C	55	5000	6500	1476	80	70	1/9	A++→A

EMERGENCY DRIVER FOR LAMP WITH INTERNAL IC DRIVERS

3+0 standard +extended 3 YEAR TOTAL WARRANTY

The housing of this emergency driver adopts good-quality steel models with powder coating. It has low weight and being convenient to install, so you can rest assure its safety. It mainly includes housing, PCB and battery etc. Its battery adopts Li-ion battery with long lifespan. Its PCB adopts automatic SMT technology, uses IC control design in charging/discharging and power supply part. PCB uses fully automatic SMT technology, PCB core use 3525 IC chips which is especially for emergency lights and Li-ion battery protections. PCB circuit has the complete protection for over charging/discharging,output Short Circuit, Open Circuit,input/output reverse connection.

OPERATED PRINCIPE:
The emergency driver is being charged when AC power works, when fully charged, the circuit will protect the battery from over being-charged, and the emergency is standing by as soon as the battery is fully charged. When AC power is down, emergency driver supplies power to LED fixtures and they up light to the way to escape.

TECHNICAL DATA:
- Input voltage: 85-265V AC
- Battery: 11.1V 2600mAh
- Emergency switch time: <2s
- Suitable: for LED lamp with internal driver and power 3-20W
- Emergency time: 60-180min
- Working temperature: from -10 to +50°C
- Size: 248x40x28mm
- IP 30

RECOMMENDED:
For all LED tubes and bulbs with external IC driver and power from 3-20W

Working voltage	Charging time	Emergency time	Emergency switch time	Packing / Box (pcs)	Product category	Catalogue number
85-265V AC	24h	60-180min	<2s	1/50	C	**89231**

LENA-V WITH LED TUBES T8 STELLAR AND EM 3-20W

2+0 standard +extended 2 YEAR TOTAL WARRANTY

IP21

Model	Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
LENA-V BM	**9LBM260LEDCWE**	C	2X9	1170	6400K	595	295	70	1/1	A++>A
LENA-V BM	**9LBM260LEDWE**	C	2X9	1170	4000K	595	295	70	1/1	A++>A
LENA-V BM	**9LBM460LEDCWE**	C	4X9	2340	6400K	595	595	70	1/1	A++>A
LENA-V BM	**9LBM460LEDWE**	C	4X9	2340	4000K	595	595	70	1/1	A++>A
LENA-V BM	**9LBM2120LEDCWE**	C	2X18	2340	6400K	1195	295	70	1/1	A++>A
LENA-V BM	**9LBM2120LEDWE**	C	2X18	2340	4000K	1195	295	70	1/1	A++>A
LENA-V OM	**9LOM260LEDCWE**	C	2X9	1170	6400K	630	330	70	1/1	A++>A
LENA-V OM	**9LOM260LEDWE**	C	2X9	1170	4000K	630	330	70	1/1	A++>A
LENA-V OM	**9LOM460LEDCWE**	C	4X9	2340	6400K	630	630	70	1/1	A++>A
LENA-V OM	**9LOM460LEDWE**	C	4X9	2340	4000K	630	630	70	1/1	A++>A
LENA-V OM	**9LOM2120LEDCWE**	C	2X18	2340	6400K	1230	330	70	1/1	A++>A
LENA-V OM	**9LOM2120LEDWE**	C	2X18	2340	4000K	1230	330	70	1/1	A++>A

BELLA WITH LED TUBES T8 ELMARK AND EMERGENCY DRIVER 3-20W

3+0 standard +extended 3 YEAR TOTAL WARRANTY

IP65

Model	Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
BELLA T8 ELMARK	**9BM218LEDCWE**	C	2X18	2880	6500	1270	131	100	1/6	A++>A
BELLA T8 ELMARK	**9BM218LEDE**	C	2X18	2880	4000	1270	131	100	1/6	A++>A
BELLA T8 ELMARK	**9BM224LEDCWE**	C	2X24	3840	6500	1570	166	110	1/4	A++>A
BELLA T8 ELMARK	**9BM224LEDE**	C	2X24	3840	4000	1570	166	110	1/4	A++>A

EMERGENCY CEILING LAMP NEPTUN

3+2 standard +extended 5 YEAR TOTAL WARRANTY

IP65

Model	Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
NEPTUN	**95NEPTUN18LEDE**	C	18	1800	6000K	280	65	1/10	A++>A

EMERGENCY DRIVER FOR INDUSTRIAL LAMP WITH INTERNAL IC DRIVERS

3+0 standard +extended 3 YEAR TOTAL WARRANTY

This emergency driver is suitable for all 20-100W LED lamps with internal IC driver (This device CANNOT be used for the LED lights with RC driver). It can be used in public places to ensure LED lights work normally when power fail suddenly because of fire and earthquake and etc. The housing of this emergency driver adopts good-quality steel models with powder coating. It has low weight and being convenient to install, so you can rest assure its safety. It mainly includes housing, PCB and battery etc. Its battery adopts Li-ion battery with long lifespan. Its PCB adopts automatic SMT technology, uses IC control design in charging/discharging and power supply part. PCB uses fully automatic SMT technology, PCB core use 3525 IC chips which is especially for emergency lights and Li-ion battery protections. PCB circuit has the complete protection for over charging/discharging,output Short Circuit, Open Circuit,input/output reverse connection.

OPERATED PRINCIPE:
The emergency driver is being charged when AC power works, when fully charged, the circuit will protect the battery from over being-charged, and the emergency is standing by as soon as the battery is fully charged. When AC power is down, emergency driver supplies power to LED fixtures and they up light to the way to escape.

TECHNICAL DATA:
- Input voltage: 85-265V AC
- Battery: 18.5V 8800mAh
- Emergency switch time: <5s
- Suitable: for LED lamp with internal driver and power 20-100W
- Emergency time: 60-120min
- Working temperature: from -10 to +50°C
- Size: 290x105x50mm
- IP 44

RECOMMENDED:
For all LED road fixturec, high bayc, flood lights and lighting fixtures with internal IC driver and power from 20-100W

Working voltage	Charging time	Emergency time	Emergency switch time	Packing / Box (pcs)	Product category	Catalogue number
85-265V AC	24h	60-120min	<5s	1/10	C	**89228**

HELIOS SMD, BLACK
WITH EMERGENCY DRIVER 20-100W

2+0 standard +extended 2 YEAR TOTAL WARRANTY IP65

Model	Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
HELIOS SMD	**98HELIOS30E**	C	30	2400	5000-5500	153	25	111	1/20	A++→A
HELIOS SMD	**98HELIOS50E**	C	50	4000	5000-5500	205	30	160	1/20	A++→A
HELIOS SMD	**98HELIOS100E**	C	100	8000	5000-5500	300	30	205	1/10	A++→A
HELIOS SMD WITH SENSOR	**98HELIOS30SENE**	C	30	2400	5000-5500	173	35	136	1/10	A++→A
HELIOS SMD WITH SENSOR	**98HELIOS50SENE**	C	50	4000	5000-5500	210	35	163	1/10	A++→A

HELIOS SMD, WHITE
WITH EMERGENCY DRIVER 20-100W

2+0 standard +extended | 2 YEAR TOTAL WARRANTY | IP65

Model	Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
HELIOS SMD	**98HELIOS30/WHE**	C	30	2400	4000	153	25	111	1/30	A++→A
HELIOS SMD	**98HELIOS50/WHE**	C	50	4000	4000	205	30	160	1/20	A++→A
HELIOS SMD	**98HELIOS100/WHE**	C	100	8000	4000	300	30	205	1/10	A++→A

VEGA SLIM, BLACK
WITH EMERGENCY DRIVER 20-100W

3+2 standard +extended | 5 YEAR TOTAL WARRANTY | IP65

Model	Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
VEGA SLIM	**98VEGA30SLIME**	C	30	2700	5500	95	130	22	1/20	A++→A
VEGA SLIM	**98VEGA50SLIME**	C	50	4500	5500	132	186	25	1/20	A++→A
VEGA SLIM	**98VEGA100SLIME**	C	100	9000	5500	190	280	28	1/10	A++→A
VEGA SLIM WITH SENSOR	**98VEGA30SSE**	C	30	2700	5500	118	158	25	1/20	A++→A
VEGA SLIM WITH SENSOR	**98VEGA50SSE**	C	50	4500	5500	145	200	26	1/10	A++→A

VEGA SLIM, WHITE
WITH EMERGENCY DRIVER 20-100W

3+2 standard +extended | 5 YEAR TOTAL WARRANTY | IP65

Model	Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
VEGA SLIM	**98VEGA30S/WHE**	C	30	2700	4000	95	130	22	1/20	A++→A
VEGA SLIM	**98VEGA50S/WHE**	C	50	4500	4000	132	186	25	1/20	A++→A
VEGA SLIM	**98VEGA100S/WHE**	C	100	9000	4000	190	280	28	1/10	A++→A
VEGA SLIM WITH SENSOR	**98VEGA30SS/WHE**	C	30	2700	4000	118	158	25	1/20	A++→A
VEGA SLIM WITH SENSOR	**98VEGA50SS/WHE**	C	50	4500	4000	145	200	26	1/10	A++→A

MADRID SMD, GREY, WITH EMERGENCY DRIVER 20-100W

5+0 standard +extended | 5 YEAR TOTAL WARRANTY | IP65

Model	Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Beam angle	Diameter of the pole (mm)	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
MADRID SMD	**98MADRID30SMDE**	C	30	3600	5500	90°	38	362	54	143	1/10	A++→A
MADRID SMD	**98MADRID50SMDE**	C	50	6000	5500	90°	60	476	74	194	1/5	A++→A
MADRID SMD	**98MADRID100SMDE**	C	100	12000	5500	90°	60	567	87	233	1/4	A++→A

ROUTE SMD STELLAR, WITH EMERGENCY DRIVER 20-100W

2+0 standard +extended | 2 YEAR TOTAL WARRANTY | IP65

Model	Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Beam angle	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
ROUTE SMD STELLAR	**98ROUTE30SMDE**	C	30	3000	5000-5500	90°	130	57	316	1/20	A++→A
ROUTE SMD STELLAR	**98ROUTE50SMDE**	C	50	5000	5000-5500	90°	155	57	355	1/10	A++→A
ROUTE SMD STELLAR	**98ROUTE100SMDE**	C	100	10000	5000-5500	90°	160	67	420	1/10	A++→A

DUBLIN SMD STELLAR, WITH EMERGENCY DRIVER 20-100W

2+0 standard +extended | 2 YEAR TOTAL WARRANTY | IP65

Model	Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Beam angle	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
DUBLIN SMD STELLAR	**98DUBLIN100SMDE**	C	100	10000	5500	100°	Grey	237	90	1/10	A++→A

VIENA SMD, WITH EMERGENCY DRIVER 20-100W

5+0 standard +extended | 5 YEAR TOTAL WARRANTY | IP65

Model	Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Beam angle	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
VIENA SMD	**98VIENA100SMDE**	C	100	13000	5500	90°	290	140	1/1	A++→A

BATHROOM

POSEIDON
955POSEIDON12
955POSEIDON18
955POSEIDON24

TRITON
955TRITON7

LED NEUTRAL WHITE 4000K **IP44**

POSEIDON / TRITON

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Width/Diameter (mm)	Length (mm)	Height (mm)	Packing/Box (pcs)	Energy class
955TRITON7	C	7	576	4000	Chrome	60	480	125	1/20	A++→A
955POSEIDON12	C	12	960	4000	Chrome	60	420	40	1/10	A++→A
955POSEIDON18	C	18	1440	4000	Chrome	60	655	40	1/10	A++→A
955POSEIDON24	C	24	1920	4000	Chrome	60	965	40	1/10	A++→A

Body: aluminium alloy | LED Bath Light.

~230V 50/60 Hz SMD 30° Ra>80 >50000 INSTANT 100% 30000h Hg IP 44 RoHS COMPLIANT EMC F CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

MIRROR LIGHT
95IP4411/2
over cabinet

MIRROR LIGHT
95IP4411
95IP4414

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | IP44

LED MIRROR LIGHT

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Beam angle	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95IP4411	C	8	504	4000	120°	400	106	42	1/20	A++→A
95IP4414	C	8	504	2700	120°	400	106	42	1/20	A++→A
95IP4411/2	C	8	504	4000	120°	400	106	42	1/20	A++→A

Body: Aluminium + PC | **Light source:** SMD 2835

~230V | 50/60 Hz | SMD | 120° | Ra≥80 | >20000 | INSTANT 100% | 30000h | IP 44 | RoHS | EMC | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

MIRROR LIGHT
95IP4412

MIRROR LIGHT
95IP4413

LED | WARM WHITE 2700K | NEUTRAL WHITE 4000K | IP44

LED MIRROR LIGHT

Catalogue number	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Beam angle	Length (mm)	Width (mm)	Height (mm)	Packing/Box (pcs)	Energy class
95IP4412	C	15	1200	4000	133°	600	65	53	1/12	A++→A
95IP4413	C	20	1600	4000	133°	900	65	53	1/12	A++→A

Body: Aluminium + PC | **Light source:** SMD 2835

~230V | 50/60 Hz | SMD | 120° | Ra≥80 | >20000 | INSTANT 100% | 30000h | IP 44 | RoHS COMPLIANT | EMC | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

DORIA
955DORIA2

DORIA
955DORIA3



DORIA
955DORIA4

IP44

DORIA

Catalogue number	Product category	Description	Body	Colour	Width/Diameter (mm)	Length (mm)	Height (mm)	Lampholder	Packing/Box (pcs)	Energy class
955DORIA2	C	Wall lamp	Stainless steel + Glass	Chrome	300	70	50	G9	1	A++→B
955DORIA3	C	Wall lamp	Stainless steel + Glass	Chrome	400	70	50	G9	1	A++→B
955DORIA4	C	Wall lamp	Stainless steel + Glass	Chrome	500	70	50	G9	1	A++→B

Material: Steel + Glass | **Lamps not included**

RoHS COMPLIANT CE 3+2 standard +extended 5 YEAR TOTAL WARRANTY

OCEAN
95IP4409

OCEAN
95IP4410

RODA
95IP4403

IP44

UNTIL SUPPLY LAST

MIRROR LIGHT

Catalogue number	Product category	Description	Body	Colour	Width/Diameter (mm)	Length (mm)	Height (mm)	Lampholder	Packing/Box (pcs)	Energy class
95IP4403	F	Wall lamp	Metal and glass	Satin nickel	275	70	120	1 x E14	1/1	A++→E
95IP4409	F	Wall lamp	Metal and glass	Chrome	55	421	67	1 x T5 / 8W	1/1	A++→A
95IP4410	F	Wall lamp	Metal and glass	Chrome	55	650	67	1 x T5 / 14W	1/1	A++→A

~230V 50/60 Hz IP 44 RoHS F CE 2+0 standard +extended 2 YEAR TOTAL WARRANTY

LED PANEL ROUND IP44
99LED609IP44
99LED609IP44CW

LED PANEL ROUND IP44
99LED611IP44
99LED611IP44CW

LED PANEL ROUND IP44
99LED617IP44
99LED617IP44CW

LED | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP44**

LED PANEL ROUND IP44

Catalogue number	Catalogue number with Emergency kit	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
99LED609IP44	**99LED609IP44E**	C	5	400	4000	white	90	21	40	A++→A
99LED609IP44CW	**99LED609IP44CWE**	C	5	400	6500	white	90	21	40	A++→A
99LED611IP44	**99LED611IP44E**	C	12	960	4000	white	175	21	20	A++→A
99LED611IP44CW	**99LED611IP44CWE**	C	12	960	6500	white	175	21	20	A++→A
99LED617IP44	**99LED617IP44E**	C	18	1440	4000	white	225	21	20	A++→A
99LED617IP44CW	**99LED617IP44CWE**	C	18	1440	6500	white	225	21	20	A++→A

Emergency kit with a possibility for work in an emergency regime more than two hours.

Body: aluminium | **Light source:** SMD 2835 | **Recessed mounted luminaire** | **Beam angle:** 120°| **Driver:** Isolated
Easy installation due to handy clips | Recessed mounted luminaire.

~230V | 50/60 Hz | SMD | 120° | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | RoHS COMPLIANT | EMC | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

LED PANEL ROUND WATERPROOF, DUSTPROOF AND OILY SMOKE
99LED607IP65
99LED607IP65CW

LED PANEL ROUND WATERPROOF, DUSTPROOF AND OILY SMOKE
99LED610IP65
99LED610IP65CW

LED PANEL ROUND WATERPROOF, DUSTPROOF AND OILY SMOKE
99LED616IP65
99LED616IP65CW

LED PANEL ROUND WATERPROOF, DUSTPROOF AND OILY SMOKE
99LED623IP65
99LED623IP65CW

LED | NEUTRAL WHITE 4000K | COOL WHITE 6400K | **IP65**

LED PANEL ROUND WATERPROOF, DUSTPROOF AND OILY SMOKE

Catalogue number	Catalogue number with Emergency kit	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Diameter1 (mm)	Height (mm)	Packing/Box (pcs)	Energy class
99LED607IP65	**99LED607IP65E**	C	7	660	4000	white	115	100-110	27	1/20	A++→A
99LED607IP65CW	**99LED607IP65CWE**	C	7	660	6500	white	115	100-110	27	1/20	A++→A
99LED610IP65	**99LED610IP65E**	C	10	770	4000	white	170	150-160	27	1/20	A++→A
99LED610IP65CW	**99LED610IP65CWE**	C	10	770	6500	white	170	150-160	27	1/20	A++→A
99LED616IP65	**99LED616IP65E**	C	16	1300	4000	white	220	200-210	27	1/20	A++→A
99LED616IP65CW	**99LED616IP65CWE**	C	16	1300	6500	white	220	200-210	27	1/20	A++→A
99LED623IP65	**99LED623IP65E**	C	23	1750	4000	white	240	220-230	39	1/20	A++→A
99LED623IP65CW	**99LED623IP65CWE**	C	23	1750	6500	white	240	220-230	39	1/20	A++→A

Emergency kit with a possibility for work in an emergency regime more than two hours.

Body: policarbonate (pc) | **Reflector:** policarbonate (pc) | Light source: SMD2835 | **Starting time:** <0.5s | Power factor: >0.9
Waterproof, dustproof and oily smoke|Milky white mask, soft light, not dazzling| Ultra-thin lamp body

~230V | 50/60 Hz | SMD | 120° | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | RoHS COMPLIANT | EMC | F | CE | 3+2 standard +extended | 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.



WATERPROOF LED PANEL ROUND
99LED609IP65

WATERPROOF LED PANEL ROUND
99LED611IP65CW

WATERPROOF LED PANEL ROUND
99LED617IP65CW

LED NEUTRAL WHITE 4000K COOL WHITE 6400K **IP65**

UNTIL SUPPLY **LAST**

WATERPROOF LED PANEL ROUND

Catalogue number	Catalogue number with Emergency kit	Product category	Watt (W)	Whole fixture lumens (lm)	Colour temp. (K)	Colour body	Diameter (mm)	Height (mm)	Packing/Box (pcs)	Energy class
99LED609IP65	**99LED609IP65E**	F	5	400	4000	white	90	27	1/40	A++→A
99LED611IP65CW	**99LED611IP65CWE**	F	10	800	6500	white	150	27	1/40	A++→A
99LED617IP65CW	**99LED617IP65CWE**	F	18	1440	6500	white	225	27	1/20	A++→A

Emergency kit with a possibility for work in an emergency regime more than two hours.

Body: policarbonate (pc) | **Reflector:** policarbonate (pc) | **Light source:** Epistar | **Starting time:** <0.5s | **Power factor:** λ>0.8
Easy installation due to handy clips | Recessed mounted luminaire.

~230V | 50/60 Hz | SMD | 120° | Ra≥80 | >20000 | INSTANT 100% | 30000h | Hg | IP 65 | RoHS COMPLIANT | EMC | F | CE | 3+2 standard +extended 5 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

ELR627
92627/W

ELR627
92627/SN

IP44

ELR627 - BATHROOM, IP44

Catalogue number	Product category	Model	Diameter (mm)	Height (mm)	Diameter1 (mm)	Colour body	Packing/Box (pcs)	Energy class
92627/W	C	ELR627	90	33	60	white	1/100	A++→E
92627/SN	C	ELR627	90	33	60	satin nickel	1/100	A++→E

Body: steel | **Diffuser:** glass

~230V | 12V | 50/60 Hz | max. 50W | IP 44 | RoHS COMPLIANT | III | F | CE | 3+0 standard +extended | 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

ELR627
92627/CH

ELR627
92627/AB

IP44

ELR627 - BATHROOM, IP44

Catalogue number	Product category	Model	Diameter (mm)	Height (mm)	Diameter1 (mm)	Colour body	Packing/Box (pcs)	Energy class
92627/CH	C	ELR627	90	33	60	chrome	1/100	A++→E
92627/AB	C	ELR627	90	33	60	antique brass	1/100	A++→E

Body: steel | **Diffuser:** glass

~230V | 12V | 50/60 Hz | max. 50W | IP 44 | RoHS COMPLIANT | 3+0 standard +extended | 3 YEAR TOTAL WARRANTY

In case of insufficient quantity in stock of any item listed on this page, the delivery time after order confirmation will be 90 days.

SA-044
92044/G

SA-144
92144/RAB

IP44

UNTIL SUPPLY LAST

SA

Catalogue number	Product category	Model	Diameter (mm)	Length (mm)	Height (mm)	Diameter1 (mm)	Colour body	Packing/Box (pcs)	Energy class
92144/RAB	F	SA-144	-	85	48	72	red antique brass	1/50	A++→E
92044/G	F	SA-044	80	-	37	71	gold	1/50	A++→E

Body: steel | **Diffuser:** glass | **Ring:** aluminium alloy

With the purchase of additional lampholder GU10, spotlights can be used with 230V GU10 lamps.

12V | 50/60 Hz | MR-16 | GU5.3 | max. 50W | IP 20 IP 44 | RoHS COMPLIANT | 2+0 standard +extended | 2 YEAR TOTAL WARRANTY